ASIAN JOURNAL OF CIVIL ENGINEERING (BHRC) VOL. 14, NO. 5 (2013) PAGES 735-746



DECISION-MAKING ANALYSIS FOR SEISMIC RETROFIT BASED ON RISK MANAGEMENT

M. Banazadeh¹, H. Parvini Sani^{*2}and M. Gholhaki² ¹Department of Civil Engineering and Environmental Engineering, Amirkabir University of Technology (Tehran Polytechnic), Tehran, Iran ²Department of Civil Engineering, Semnan University, Semnan, Iran

Received: 4 October 2012; Accepted: 5 March 2013

ABSTRACT

This paper presents a methodology to make informed decisions for seismic retrofitting considering risk management and expected economic benefit based on seismic loss estimation. Three performance measures: Repair cost, Casualties, Downtime is considered for loss estimation. Time-based performance assessment is used with utilizing Performance Assessment Calculation Tool (PACT). By using probabilistic framework, Annual Loss (AL) has been estimated. AL within a reasonable relationship is combined with retrofit cost and discount rate to obtain the amount of net losses and minimum time required for the economic feasibility of each retrofit alternative. The prescribed methodology is used for assessing the steel resisting frame that has been retrofitted with three different methods. According to this study, various retrofit strategies will have reasonable comparability and loss estimation eases decision process for stakeholders.

Keywords: Decision-Making; Seismic Retrofit; Loss Estimation; Expected Economic Benefit; Risk Management.

1. INTRODUCTION

Current seismic design codes provide guidelines for the design and detailing of structures with the primary goal of preventing global collapse during strong ground motion shaking. However, observations from worldwide earthquakes in the past two decades illustrated the severe economic consequences resulting from earthquakes in highly developed regions of society. These economic consequences can be primarily attributed to: 1-direct economic losses associated with repairing damage within a structure; 2- direct losses associated with

^{*} E-mail address of the corresponding author: hosseinp@aut.ac.ir (H. Parvini Sani)

injuries and casualties; and 3- indirect losses associated with downtime. Some examples from the United States include the 1994 Northridge earthquake (\$17-26 billion loss), and 1989 Loma Prieta earthquake (\$11 billion loss) [1], from Japan include 1995 Hyogo-Ken Nambu, Kobe earthquake (\$100 billion loss) [2], from Turkey include 1999 Kocaeli earthquake (\$16 billion loss) [3], from Iran include 2003 Bam earthquake (\$1.5 billion loss) and from China include 2008 Eastern Sichuan earthquake (\$86 billion loss). In response to these observed losses, it has become apparent that seismic design of structures should consider all of these potential consequences and their risk of occurrence.

Probabilistic seismic risk based on loss estimation in a building due to earthquake damage is a topic of interest to decision makers and an area of active research. In order to incorporate seismic risk of facilities into a decision-making framework, procedures are needed to quantify such risk for stakeholders. Quantification of seismic risk is a difficult task that is subject to inherent variability. One promising approach to the problem, proposed by the Pacific Earthquake Engineering Research (PEER) Center, involves breaking the analysis into separate components associated with ground motion hazard, structural response, damage to components and repair costs [4].

This paper presents a discussion of the seismic loss estimation for retrofit decisionmaking. Seismic loss estimation methods combine seismic hazard, structural response, damage fragility, and damage consequences to allow quantification of seismic risk [5-6]. Loss is measured in the forms of direct structural and non-structural repair costs, casualties and downtime. The methodology uses the concept of performance groups (PGs) that account for damage and repair of individual components [7].

In addition, this study makes informed decision about economic feasibility for seismic retrofit. To this end, after estimating Annual Loss (AL) [8], the impact of factors such as discount rate and seismic retrofit cost is studied in the technical-economic justification of seismic retrofit [1]. In other words, this paper tries turning existing uncertainty in the earthquake occurrence parameters, structural response and damage models into decision parameters in a logical framework based on principles of seismic risk assessment.

An outline of the state-of-the-art seismic loss estimation is given with reference to a specific case study of a 5-story steel moment residential building in Tehran. Using the case study structure a full loss assessment is performed and discussion is given to each of the possible outputs for decision-making.

2. LOSS ESTIMATION METHOD

According to damages induced from earthquakes to structures, clients are faced with the decision of whether or not to retrofit existing structures in order to lower their potential losses that needs respecting associated risk. In response to perceived insufficiencies of risk assessment methodologies, performance-based guidelines have been developed to consider quantitative measures that can be used to objectively assess seismic performance in terms of a decision variable (DV) which is used for considering economic standpoint of clients. One of the key developments of Pacific Earthquake Engineering Research (PEER) Center was the development of the PEER framework formula considering all potential uncertainty in the

estimation of the DV. PEER framework formula expressed as follows [6]:

$$\lambda[DV] = \iiint G(DV \mid DM) dG(DM \mid EDP) dG(EDP \mid IM) d\lambda(IM). dEDP. dDM$$
(1)

Where terms λ [X], G(X|Y), DV, DM, EDP and IM represent, the Mean Annual Frequency (MAF) of exceeding X, the Complementary Cumulative Distribution Function (CCDF) of X conditioned on Y, Decision Variable, Damage measure, Engineering Demand Parameter and Intensity Measure, respectively. Eq. (1) domains are:

2.1 Hazard Analysis

Intensity measures are quantities that describe the magnitude (M) of ground motion characteristics that significantly affect the upstream variables of the performance assessment approach. In the context of Eq. (1), this implies an evaluation of the Mean Annual Frequency (MAF) of IMs through seismic hazard analysis. The 5%-damped first-mode spectral acceleration $S_a(T_1, 5\%)$ is indeed the best choice from simplicity and accuracy standpoints [9].

2.2 Structural Analysis

The amount of demand induced in structure and nonstructural component is represented by term G(EDP|IM) in Eq. (1) Once identified, they can be computed from different procedures such as, incremental dynamic analysis (IDA) procedure [10], which accounts for the record-to record uncertainty that attributed to the aleatory nature of earthquake hazard. In this procedure, the soil–foundation–structure system is subjected to a ground motion whose intensity is incremented after each inelastic dynamic analysis. The result is a curve that shows the EDP plotted against the IM used to control the increment of the ground motion. IDAs can be carried out for a sufficiently large number of ground motions to perform statistical evaluation of the results.

2.3 Damage and Loss Analysis

According to uncertainty in damage extent at a specific response level term, G(DM|EDP) is used. To estimate the damage in structural elements, a relationship between relevant EDPs and different levels of damage, referred to here as Damage Measures (DM) are required. The damage analysis methodology used in this paper is based on ATC-58 [11]. The state of damage in structural and nonstructural components is estimated using response vector comprised of peak floor acceleration (PFA) for each floor level (also the base) and interstory drift (θ_{max}) for each story, that is of order 2n+1 (n represent for number of stories) all developed from IDA results. According to ATC-58, the methodology uses the concept of performance groups (PGs) that account for damage state (DS) of individual components of frame [12].

Because of uncertainties in the number of people and facilities and their location (when an earthquake occurs) term G(DV|DM) is used.

After an earthquake, the repair cost will not be the only "loss" suffered by building stakeholder and a variety of factors can affect the consequences of a decision as a Decision Variable (DV). Assuredly considering as many factors as possible in the decision-making

process will cause the most precise results. For decisions regarding the effects of seismic events on the buildings, these consequences include mortality as well as direct and indirect economic losses [13]. The challenge lies in incorporating these factors and their consequences, given a particular course of action, into a measurable quantity that can be used to define performance measures. Addressing this challenge is crucial as any decision is ultimately judged on the consequences of its outcome [5]. In this study, three performance measures as DV are considered here:

1. Repair costs (defined as the cost of repairing or replacing damaged buildings, and their contents).

2. Casualties (defined as deaths and serious injuries that would normally require hospitalization).

3. Downtime (defined as the period between the occurrence of a seismic event and the completion of the building repair effort. There are various factors that can affect building downtime: building inspection, damage assessment, finance planning, architect/engineering consultations, a possible competitive bidding process, and the repair effort needed to return a building back to its undamaged state [14].

A probabilistic mapping between a structural response parameter and the level of damage in a particular component may be referred to as a fragility function. Fragility functions associate a relevant EDP with the probability of exceeding a certain level of damage. The best source of information for the development of fragility functions is a laboratory test (Fema-461), analytical research, and observations from past earthquakes, engineering judgment or combination of them in which damage states are documented as a function of the EDP that has the largest influence on the extent of damage. Example family of fragility curves for special steel moment frames is depicted in Figure 1.A. The monetary value of repair cost is calculated utilizing cost functions. A sample cost function considering uncertainty is represented in Figure 1.B.

A large part of moving the frontier of performance-based earthquake engineering (PBEE) forward is making both the tools and the methodologies accessible. This has become the focus of numerous recent efforts, for example ATC-58 includes the performance assessment calculation tool (PACT) that allows anyone interested to use off-the-shelf software to compute probabilistic loss estimates [7].

For estimating repair costs, PACT [15] software is used. PACT will automatically develop the necessary performance groups based on the input of key building descriptive data including Number of stories, typical story height, typical E-W and N-W building dimension, occupancy of each floor. PACT also contains component fragilities for each damage state and consequence functions for performance measures.



Figure 1. (a) Family of fragility curves for special steel moment frames, (b) Sample cost function considering the uncertainty [15].

Casualty and downtime are considered as a total collapse of structure, so a monetary value for them should based on social judgment and importance of life loss, and downtime in observed region. In this study, a cumulative density function is assumed a median cost equal to 3 times the high repair cost (repair cost for most severe damage state resulted from all components) with coefficient of variation equal to 0.4.

2.4 Estimating Final Loss

It should be noted that precise quantification of performance measures is impossible so probabilistic framework should be utilized. According to probability theorem, final loss can be obtained from Eq. (2) considering the two probable cases: 1. Collapse (CO) 2. No-collapse (NC):

$$G (\$Loss \ge L \mid IM) = G (\$RepairCost \ge L \mid IM \& NC) \times P(NC \mid IM)$$

$$+ G(\$Loss \ge L \mid CO) \times P(CO \mid IM) *$$

$$* P(CO \mid IM) = 1 - P (NC \mid IM)$$
(2)
(3)

In Eq. (2), G(\$RepairCost \geq L|IM&NC) denotes the repair cost for "NC" condition and conditioned on IM, P(NC|IM) is the probability of NC case conditioned on IM which obtained from IDA results (collapse fragility), term G(\$Loss \geq L|CO) represent total cost greater than or equal to L for downtime and casualty conditioned on "CO" case and finally result of equation is G(\$Loss \geq L|IM) that specifies building total loss for three performance measures greater than or equal to L.

Loss curves conditioned on IM are integrated with hazard curves to outcome exceeding probability for various $S_a(T_1,5\%)$ values as presented in Eq. (4):

M. Banazadeh, H. Parvini Sani and M. Gholhaki

$$\lambda(\text{Loss} \ge L) = \int_{\text{IM}=0}^{\text{IM}=\infty} G(\text{Loss} \ge L \mid \text{IM}).d\lambda(\text{IM})$$
(4)

Annual loss (AL) can be extracted from product of various loss values and their corresponding $\lambda(\text{Loss}\geq L)$ and integrating over full range of loss values. AL is a seismic performance measure that is particularly useful for decision makers as it contains information on the seismic performance of a structure over a range of different levels of ground motion intensity within a single number. In essence, the annualized loss for repair costs represents the premium that one should be willing to pay for an insurance policy. The annual loss (AL) is also a valuable result for property stakeholders, which accounts for the frequency and severity of various seismic events [8]. Above methodology is summarized in Figure 2.



2.5 Application of EAL for retrofit decision making Net value of expected loss over time accounting for the discount rate is computed by [1]:

$$E_{L} = \frac{\left(1 - e^{-\lambda t}\right)}{\lambda} AL + C_{R}$$
(5)

Where λ is the discount rate; *t* is the time in years; and C_R is the retrofit cost. Then by equating Eq. (5) for the as-is structured (C_R = 0) and retrofitted structure the time after which the retrofit is economically feasible can be found by:

$$t_{\rm cr} = \frac{-1}{\lambda} \ln \left(1 - \frac{\lambda}{1 - \alpha} \frac{C_{\rm R}}{AL} \right)$$
(6)

Where α is a parameter indicating the reduction in the AL due to the retrofit.

740

3. CASE STUDY STRUCTURE

Case Study was performed on the 5-story perimeter steel resisting frame that is located Tehran downtown. The frame has excessive drift at floor 3, 4 concerning Iranian code of practice for seismic resistant design of buildings (standard No. 2800-5). In this code like UBC-97, calculated story drift using Δ_M shall not exceed 0.025 times the story height for structures having a fundamental period of less than 0.7 second. For structures having a fundamental period of 0.7 second or greater, the calculated story drift shall not exceed 0.020 times the story height. According to Figure 3 three alternatives for retrofitting are introduced.



Figure 3. (a) Plan of case study, (b) Alternative-1 (c) Alternative-2, (d) Alternative-3 of retrofit

3.1 Modeling Details

Concerning the symmetry in plan, the structures are modeled in two-dimensional format in OpenSees software [16]. Nonlinear beam-column elements with concentrated plastic hinges in two ends, connected by an elastic element, are adopted for modeling the frames. The nonlinear behavior in plastic hinges is modeled implementing rotational springs (with

M. Banazadeh, H. Parvini Sani and M. Gholhaki

stiffness and strength deterioration). Cyclic moment-rotation of steel beams and columns are represented by Lignos and Krawinkler [17] which focuses on development of a steel component database that can serve as the basis for validation and improvement of analytical models that explicitly model deterioration in structural steel components and can be used in collapse assessment of steel moment resisting frames. In addition, in order to consider the cyclic deterioration, the modified model suggested by Ibarra et al. [18] have been used. In this model, cyclic deterioration parameter is accounted for deterioration criterion by using energy dissipation. The following four modes of deterioration are included: basic strength, post-capping strength, unloading stiffness, and accelerated reloading stiffness deterioration. The definition of plastic hinges has been performed using Joint2D-5spr element [19] in OpenSees with panel zone modeled with Gupta et al. model [20]. Column base uplift, as expectable in a braced frame, has been considered through definition of zero-tension spring elements at the column-foundation interface.



Besides, braces are modeled with distributed inelasticity and fiber discretization of the cross section. The brace member is subdivided into two inelastic beam-column elements. An initial camber displacement of 0.08% of the brace length should be specified at brace midspan. The inelastic response of each element is monitored at five integration points [21].

3.2 Ground Motions

To reflect variability in ground motion, we drew on a set of horizontal-component pairs of 22 far field ground-motion time histories compiled by FEMA P695 [22].

3.3 IDA Outcomes

Figure 5 represents IDA curves for frames, $S_a(T_1,5\%)$ vs. the maximum peak interstorey drift ratio $\theta_{max} = max(\theta_1,...,\theta_5)$, that median and 16%, 84% S_a values as fractile IDAs are highlighted in it and summarized S_a for each limit state are shown in Table 1. CP fragility curves are compared in Figure 6.



M. Banazadeh, H. Parvini Sani and M. Gholhaki

3.4 Loss Estimation and decision-making

By calculating Eq. (2) and integrating over specific hazard curve [23], AL based on Eq. (4) is achieved and decision parameters are calculated for primary frame and retrofitted alternatives that are denoted in Table 2. In this table Scenario Expected Loss (SEL) is the mean loss obtained from an intensity-based assessment and Upper Bound Loss (SUL) is obtained from an intensity-based loss assessment as that loss having a 10% chance of exceedance typically for 475-year earthquake shaking and Internal Rate of Return on the Investment (IRRI) for a long duration investment can be approximated as the annualized benefit of the investment divided by the net present value or cost. Expected Loss over time for alternatives are depicted in Figure 7. It can be inferred, alternative-2 is suitable for performing retrofit from economic standpoint.



Figure 7. Expected Loss over time for alternatives

Table 2: Decision parameters for case studies				
Cases	Primary	Alternative-1	Alternative-2	Alternative-3
$\lambda_{\text{Collapse}} \times 10^{-4}$	1.03	0.9618	0.8416	1.113
CMR	2.385	2.483	2.837	2.473
C_R (\$ (USD))		14000	10000	10000
AL(\$ (USD))	2223.1	1083.565	1257.027	1376.487
SEL(\$ (USD))	304.68	280.73	279.57	294.52
SUL(\$ (USD))	306.79	282.84	281.67	296.63
IRRI	-	8.1 %	9.66 %	8.47%
t _{cr} (λ=7%)	-	28 years	19 years	25 years
Best Choice			Alternative-2	

4. CONCLUSIONS

The present study makes informed decision about economic feasibility for seismic retrofit. In essence, this paper tries turning existing uncertainty in the earthquake occurrence

744

parameters, structural response and damage models into decision parameters. Noteworthy results of this paper are:

1. According to this study, various retrofit strategies will have reasonable comparability and eases decision process for stakeholders with accessible information. The results of methodology make stakeholders and decision-makers to communicate more easily according to expected economic benefits.

2. An illustrative benefit-cost analysis is performed in which three disparate performance attribute repair cost, casualties and downtime are combined into one economical performance measure based on the expected annual losses.

3. Estimating Annual loss (AL) can be a valuable tool to estimate insurance amount for seismic vulnerability of buildings and assess performance of existing structures.

4. Decision maker should estimate AL and the mean annual frequency of collapse $(\lambda_{Collapse})$ and also study economic feasibility of retrofit (Internal Rate of Return on the Investment (IRRI) and time after which the retrofit is economically feasible (t_{cr})) to mitigate seismic risk within a reasonable manner by trying different alternatives for retrofitting.

REFERENCES

- 1. Bradley BA. *Structure-Specific Probabilistic Seismic Risk Assessment*, Department of Civil and Natural Resources Engineering, Ph.D Thesis College of Engineering, University of Canterbury, Christchurch, New Zealand, 2009.
- Watanabe E, Sugiura K, Nagata K, Kitane Y. Performances and damages to steel structures during the 1995 Hyogoken-Nanbu earthquake, *Engineering Structures*, 20(1998) 282-90.
- 3. Fallahi A, Kitaura M, Miyajima M. Comparison among Iran, Turkey, and Kobe earthquake from the View Point of Ground Motion Characteristics and Damage, *Proceedings of the JSCE Earthquake Engineering Symposium*, **26**(2001) 1-4.
- 4. Baker JW, Cornell CA. Uncertainty propagation in probabilistic seismic loss estimation, *Structural Safety*, **30**(2008) 236–52.
- 5. Williams R, Gardoni P, Bracci J. Decision analysis for seismic retrofit of structures, *Structural Safety*, **31**(2009) 188-96.
- Krawinkler H, Zareian F, Ricardo A. Medina, Luis F. Ibarra. Decision support for conceptual performance-based design, Published Online in Wiley InterScience, 35(2005) 115–33.
- 7. Mackie KR, Wong JM, Stojadinovi B. Post-earthquake bridge repair cost and repair time estimation methodology, *Earthquake Engineering and Structural Dynamics*, Published Online in Wiley InterScience, DOI: 10.1002/eqe.942, 2009.
- 8. Goulet CA, et al. Evaluation of the seismic performance of a code-conforming reinforced-concrete frame building-from seismic hazard to collapse safety and economic losses, *Earthquake Engineering and Structural Dynamics*, **36**(2007) 1973-97.
- 9. Bozorgnia Y, Bertero VV. Earthquake Engineering: from Engineering Seismology to Performance-based Engineering, CRC Press, New York, 2004.
- 10. Vamvatsikos D, Cornell CA. Incremental Dynamic Analysis. Earthquake Engineering

and Structural Dynamics, *Earthquake Engineering and Structural Dynamics*, **31**(2002) 491–514.

- 11. Applied Technology Council. ATC-58. Guidelines for Seismic Performance Assessment of Buildings, Redwood City, CA, 2011.
- 12. Tafakori E, Banazadeh M, Jalali SA, Tehranizadeh M. Risk-based optimal retrofit of a tall steel building by using friction dampers, *The Structural Design of Tall and Special Buildings published Online*, DOI: 10.1002/tal.720, 2011.
- 13. Ellingwood BR, Wen YK. Risk-benefit-based design decisions for low-probability/high consequence earthquake events in mid-America, *Progress in Structural Engineering and Materials*, 7(2005) 56-70.
- 14. Comerio MC. Estimating downtime in loss modeling, Earthquake Spectra, *Earthquake Engineering Research Institute*, Oakland, **22**(2006) 349-65.
- 15. PEER. Performance Assessment Calculation Tool (PACT), 2007.
- 16. OpenSees. *Open System for Earthquake Engineering Simulation*, Pacific Earthquake Engineering Research Center, University of California, Berkeley, 2006.
- 17. Lignos DG, Krawinkler H. A Database in Support of Modeling of Component Deterioration for Collapse Prediction of Steel Frame Structures, *Structural Engineering Research Frontiers*, *ASCE*, 2007.
- 18. Ibarra LF, Krawinkler H. Global *Collapse of Frame Structures under Seismic Excitations*, Uni. of California at Berkeley, Berkeley, California, Report No. PEER 2005-05.
- 19. Altoontash A. Simulation and Damage Models for Performance Assessment of Reinforced Concrete Beam-Column Joints, Ph.D Thesis, Stanford University, 2004.
- 20. Gupta A, Krawinkler H. Seismic Demands for Performance Evaluation of Steel Moment Resisting Frame Structures, Department of Civil and Environmental Engineering and the Committee on the Graduate Studies of the Stanford University, 1999.
- 21. Uriz P, Filippou FC, Mahin SA. Model for Cyclic Inelastic Buckling of steel Braces, *Journal of Structural Engineering, ASCE*, **134**(2008) 619-28.
- 22. APPLIED TECHNOLOGY COUNCIL. FEMA P695, *Quantification of Building Seismic Performance Factors*, Redwood City, California, 2009.
- 23. Mahdavi Adeli M, Banazadeh M, Deylami A. Bayesian approach for determination of drift hazard curves for generic steel moment-resisting frames in territory of Tehran, *International Journal of Civil Engineering*, **9**(2011) 146-54.