



## Transient free convective flow of a micropolar fluid between two vertical walls

S. K. Ravi \*<sup>†</sup>, A. K. Singh <sup>‡</sup>, R. K. Singh <sup>§</sup>, A. J. Chamkha <sup>¶</sup>

### Abstract

The aim of this paper is to present numerically the transport mechanism of an incompressible micropolar fluid between two vertical walls when the motion occurs due to the buoyancy force. The governing equations in non-dimensional form are solved numerically using the Matlab software. The obtained numerical solutions for the velocity and micro-rotation profiles are displayed using the graphs for various values of the vortex viscosity parameter and material parameter. It is found that the material parameter has retarding effect on the velocity of micropolar fluid and to make the flow steady state earlier for both thermal conditions. The effect of the vortex viscosity parameter is to decrease the steady state time of the velocity and micro-rotation.

*Keywords* : Micropolar fluid; Matlab R2008a; Vertical walls; Unsteady flow.

### Nomenclature

$g$  Acceleration due to gravity  
 $G_r$  Grashof number  
 $L$  Distance between two vertical walls  
 $Pr$  Prandtl number  
 $R$  Material parameter  
 $t$  Time in non – dimensional form  
 $t'$  Time  
 $T'_c$  Temperature of the wall at  $y'=L$   
 $T'_h$  Temperature of the wall at  $y'=0$   
 $T'_m$  Initial temperature of the fluid  
 $u$  Velocity in non – dimensional form  
 $u'$  Velocity of fluid

$y$  Dimensionless coordinate perpendicular to the walls

$y'$  Co – ordinate perpendicular of the wall

### Greek symbols

$\omega$  Dimensionless angular velocity  
 $j$  Micro-inertia density  
 $k$  Vortex viscosity  
 $\mu$  Dynamic viscosity  
 $\theta$  Temperature of the fluid in non-dimensional form  
 $\nu$  Kinematic viscosity of the fluid

\*Corresponding author. santosravi@rediffmail.com

<sup>†</sup>Department of Mathematics, Faculty of Science, Banaras Hindu University, Varanasi, India.

<sup>‡</sup>Department of Mathematics, Faculty of Science, Banaras Hindu University, Varanasi, India.

<sup>§</sup>Department of Mathematics, Faculty of Science, Banaras Hindu University, Varanasi, India.

<sup>¶</sup>Engineering Department, The Public Authority for Applied Education and Training, Shuweikh 70654, Kuwait.

## 1 Introduction

The dynamics of micropolar fluids has attracted considerable attention by research workers during the last few decades because traditional Newtonian fluids cannot precisely describe the

characteristics of fluid flow with suspended particles. The basic idea about micropolar fluids has originated from the need to model the flow of fluids containing rotating micro-constituents. Beside the usual equations for Newtonian flow, this theory introduces some new material parameters, an additional independent vector field the microrotation and new constitutive equations that must be solved simultaneously with the usual Newtonian flow equations. In the history of fluid mechanics, Eringen [1, 2], a pioneering researcher, has first formulated the theory of micropolar fluids. This theory in formulating the governing equations takes into account the effects arising from the local structure and micro-motions of the fluid elements, and is able to describe the behavior of the polymeric additives, animal blood, lubricants, liquid crystals, dirty oils, solutions of colloidal suspensions, etc.. The micropolar fluids exhibit certain microscopic effects arising from local structure and microrotation of fluid elements.

Sastry and Rao [3] have focused the numerical solution of a micropolar fluid flow in a channel with porous walls. Further, Bhargava and Rani [4] have found the numerical solution on the heat transfer phenomenon of the micropolar fluid flowing in a channel having porous walls. Agarwal and Dhanapal [5] have analyzed numerically the free convective flow of the micropolar fluid between two parallel porous vertical plates while Gorla et al. [6] have studied on mixed convective flow of a micropolar fluid. Kim [7] considered unsteady convection flow of micropolar fluids past a vertical porous medium. Srinivasacharya et al. [8] have investigated the unsteady Stokes flow of a micropolar fluid between two parallel porous plates. Kim [9] has studied the unsteady MHD convective flow of the polar fluids past a vertical moving porous plate in a porous medium. Further, Kim and Fedorov [10] have discussed on the transient mixed radiative convection of the micropolar fluid past a moving semi-infinite vertical porous plate while Bhargava et al. [11] have studied the numerical solution of MHD free convective flow of the micropolar fluid flow between two parallel porous vertical plates. Chamkha et al. [12] reported the solution of fully developed free convection of a micropolar fluid in a vertical channel.

Singh and Paul [13] have investigated the transient natural convective flow between two vertical walls heated/cooled asymmetrically. Chen [14] has studied the non-linear stability characterization of the thin micropolar liquid film flowing down the inner surface of a rotating vertical cylinder. Recently, Rahman [15] has investigated the convective flows of the micropolar fluids from isothermal porous surfaces with viscous dissipation and Joule heating where as Ishak et al. [16] have shown the dual solutions in mixed convective boundary layer flow of the micropolar fluids. Sajid et al. [17] have considered the exact solutions for thin film flows of a micropolar fluid. Further, Ishak et al. [18] have conducted the MHD boundary-layer flow of a micropolar fluid past a wedge with constant wall heat flux. Pal and Chatterjee [19] have presented the heat and mass transfer in MHD non-Darcian flow of a micropolar fluid over a stretching sheet embedded in a porous media with non-uniform heat source and thermal radiation.

In this paper, we have solved the unsteady free convective flow formation of a micropolar fluid between two infinitely long vertical walls as a result of symmetric and asymmetric heating. A non-dimensional parameter is used in order to characterize the temperature of the vertical walls with respect to the fluid temperature. The partial differential equations of governing flow and heat transfer have been solved by using the Matlab R2008a software. Finally, the results are displayed using the graphs and table.

## 2 Governing Equations

We consider the unsteady free-convective flow of a micro-polar fluid between two vertical walls separated by a distance  $L$  apart. For mathematical formulation, we take the  $x'$ -axis along one of the vertical walls in the upward direction and the  $y'$ -axis normal to it. Initially, the temperatures of walls and the fluid are same says  $T'_m$ . At time  $t' > 0$ , the temperature of the walls at  $y' = 0$  and  $L$  is instantaneously raised or lowered to  $T'_h$  and  $T'_c$  respectively such that  $(T'_h > T'_c)$  which is there after maintained constant. As the walls are of infinite extent, the flow depends only on the transverse co-ordinate  $y'$  and time  $t'$ . We have

assumed that the fluid properties are not affected by the temperature difference except the density in the body force term. Under these assumptions, the governing equations corresponding to the considered model are derived as follows:

$$\rho \frac{\partial u'}{\partial t'} = (\mu + k) \frac{\partial^2 u'}{\partial y'^2} + k \frac{\partial \omega'}{\partial y'} + \rho g \beta (T' - T'_m), \quad (2.1)$$

$$\rho \frac{\partial \omega'}{\partial t'} = (\mu + 0.5k) \frac{\partial^2 \omega'}{\partial y'^2} - k \left( 2\omega' + \frac{\partial u'}{\partial y'} \right), \quad (2.2)$$

$$\rho \frac{\partial T'}{\partial t'} = \alpha \frac{\partial^2 T'}{\partial y'^2}. \quad (2.3)$$

The initial and boundary conditions for the velocity, angular velocity field and temperature are as follows:

$$\begin{aligned} t \leq 0 & \quad u' = \omega' = 0 & \quad T' = T'_m, & \quad 0 \leq y' \leq L; \\ t > 0 & \quad u' = \omega' = 0 & \quad T' = T'_h, & \quad y' = 0; \\ & \quad u' = \omega' = 0 & \quad T' = T'_c, & \quad y = L. \end{aligned} \quad (2.4)$$

In order to non-dimensionalize the above equations, we introduce the following non dimensional variables and physical parameters defined as follows:

$$\begin{aligned} Y &= y'/L, & t &= vt'/L^2, \\ u &= u'v/\beta gL^2(T'_h - T'_m), \\ \theta &= (T' - T'_m)/(T'_h - T'_m), \\ \omega &= \omega'v/\beta gL(T'_h - T'_m), & Pr &= v/\alpha, \\ m &= (T'_c - T'_m)/(T'_h - T'_m), & b &= L^2/j, \\ R &= k/\mu. \end{aligned} \quad (2.5)$$

The physical quantities used in the above equations are defined in the Nomenclature. Use of non-dimensional variables and parameters defined in (2.5) into Equations (2.1) - (2.3), have resulted the following equations in non-dimensional form:

$$\frac{\partial u}{\partial t} = (1 + R) \frac{\partial^2 u}{\partial y^2} + \theta + R \frac{\partial \omega}{\partial y}, \quad (2.6)$$

$$\frac{\partial \omega}{\partial t} = (1 + 0.5R) \frac{\partial^2 \omega}{\partial y^2} - Rb \left( \frac{\partial u}{\partial y} + 2\omega \right), \quad (2.7)$$

$$\frac{\partial \theta}{\partial t} = \frac{1}{Pr} \frac{\partial^2 \theta}{\partial y^2}. \quad (2.8)$$

The boundary conditions corresponding to the considered model in dimensionless form are derived as follows:

$$\begin{aligned} t \leq 0 & \quad u = \omega = \theta = 0, & \quad 0 \leq y \leq 1; \\ t > 0 & \quad u = \omega = 0, & \quad \theta = 1 \quad y = 0; \\ & \quad u = \omega = 0, & \quad \theta = m \quad y = 1. \end{aligned} \quad (2.9)$$

### 3 Numerical solution

The linear parabolic partial differential equations (2.6), (2.7) and (2.8) with their appropriate initial and boundary conditions are solved numerically by using Matlab R2008a software. The numerical solution is obtained on a mesh produced by 20 equally spaced points for the spatial interval [0, 1] starting from initial value of time to steady state value.

### 4 Steady state solution

In order to check the accuracy of the numerical solutions obtained with MATLAB software, we compare the steady-state numerical solution with the analytical solutions of the corresponding steady flow. Denoting these solutions as  $u_s$  and  $\omega_s$ , it can be shown that

$$\begin{aligned} u_s &= -2c_1y + c_2k_{11}e^{\sqrt{k_4}y} - c_3k_{11}e^{-\sqrt{k_4}y} \\ &\quad - k_{12}y^3 - k_8y^2 + k_{13}y + c_4, \end{aligned} \quad (4.10)$$

$$\begin{aligned} \omega_s &= c_1 + c_2e^{\sqrt{k_4}y} + c_3e^{-\sqrt{k_4}y} \\ &\quad + k_7y^2 + k_8y. \end{aligned} \quad (4.11)$$


where

$$\begin{aligned} k_1 &= 2Rb/(2 + R), & k_2 &= 1/k_1, \\ k_3 &= (1 + R)k_2, & k_4 &= (2 + R)/k_3, \\ k_5 &= (m - 1)/k_3, & k_6 &= 1/k_3, \\ k_7 &= k_5/2k_4, & k_8 &= k_6/k_4, \\ k_9 &= k_2k_4, & k_{10} &= (k_9 - 2), \\ k_{11} &= k_{10}/\sqrt{k_4}, & k_{12} &= 2k_7/3, \\ k_{13} &= 2k_2k_7, \\ k_{14} &= k_{13} - k_8 - k_{12}, \\ k_{15} &= 2 + k_{11}e^{\sqrt{k_4}} - k_{11}, \\ k_{16} &= 2 - k_{11}e^{-\sqrt{k_4}} + k_{11}, & k_{17} &= e^{\sqrt{k_4}} - 1, \\ k_{18} &= e^{-\sqrt{k_4}} - 1, & k_{19} &= k_7 + k_8, \\ k_{20} &= -k_{16}/\sqrt{k_{15}}, & k_{21} &= -k_{14}/k_{15}, \\ k_{22} &= k_{20}k_{17} + k_{18}, & k_{23} &= k_{21}k_{17} + k_{19}, \\ k_{24} &= -k_{23}/k_{22}, & k_{25} &= k_{20}k_{24} + k_{21}, \\ k_{26} &= -k_{25} - k_{24}, \\ k_{27} &= k_{24}k_{11} - k_{25}k_{11}, \\ c_1 &= k_{26}, & c_2 &= k_{25}, \\ c_3 &= k_{24}, & c_4 &= k_{27}. \end{aligned}$$


In Table 1, we have given the numerical values of the steady-state velocity and microrotation obtained by using Matlab software with  $u_s$  and  $\omega_s$  for  $m = 0$  and 1. One can see that the numerical and analytical results agree very well. The

**Table 1:** Numerical values of steady state velocity field and microrotation profile for  $m=0$  and  $m = 1.0$ .


$M$	$R$	$b$	$y$	velocity field Matlab-R2008a By Eq. (4.10)		microrotation profile Matlab-R2008a By Eq. (4.11)	
0.0	0.5	1.0	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.032050	0.032063	-7.94E-04	-0.000790
			0.4	0.042770	0.042781	6.84E-05	0.000074
			0.6	0.037410	0.037429	0.001110	0.001121
			0.8	0.021350	0.021364	0.001300	0.001308
1.0	0.5	0.1	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.053330	0.053343	-2.13E-04	-0.000210
			0.4	0.080000	0.080021	-1.06E-04	-0.000110
			0.6	0.080000	0.080021	1.06E-04	0.000106
			0.8	0.053330	0.053343	2.13E-04	0.000213
0.0	0.5	2.0	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.032110	0.032123	-0.001600	-0.001590
			0.4	0.042870	0.042892	8.35E-05	0.000093
			0.6	0.037500	0.037521	0.002140	0.002148
			0.8	0.021380	0.021394	0.002530	0.002538
1.0	0.5	2.0	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.053510	0.053518	-0.004130	-0.004130
			0.4	0.080390	0.080413	-0.002050	-0.002060
			0.6	0.080300	0.080413	0.002050	0.002055
			0.8	0.053510	0.053518	0.004130	0.004131
0.0	0.5	0.5	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.032020	0.032032	-3.42E-04	-0.000390
			0.4	0.042700	0.042724	-1.14E-04	0.000045
			0.6	0.037360	0.037381	5.93E-04	0.000573
			0.8	0.021330	0.021348	6.40E-04	0.000665
1.0	0.5	0.5	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.053340	0.053380	-0.001060	-0.001060
			0.4	0.080040	0.080106	-5.28E-04	-0.000530
			0.6	0.080040	0.080106	-5.28E-04	0.000528
			0.8	0.053340	0.053380	0.001060	0.001058
0.0	2.0	0.5	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.016070	0.016079	-5.00E-04	-0.000500
			0.4	0.021470	0.021476	3.79E-05	0.000042
			0.6	0.018780	0.018786	6.92E-04	0.000696
			0.8	0.010700	0.010705	8.12E-04	0.000814
1.0	2.0	0.5	0.0	0.000000	0.000000	0.000000	0.000000
			0.2	0.026750	0.026783	-0.001310	-0.001310
			0.4	0.040210	0.040262	-6.54E-04	-0.000650
			0.6	0.040210	0.040262	-6.54E-04	0.000654
			0.8	0.026750	0.026783	0.001310	0.001312
			1.0	0.000000	0.000000	0.000000	0.000000




**Figure 1:** Velocity profile for different values of  $t$  at  $m = 0.0, R = 0.5, Pr = 1.0$ .



**Figure 3:** Velocity Profile for different values of  $t$  at  $m = 0.0, b = 0.5, Pr = 1.0$ .



**Figure 2:** Velocity Profile for different values of  $t$  at  $m = 1.0, R = 0.5, Pr = 1.0$ .




**Figure 4:** Velocity Profile for different values of  $t$  at  $m = 1.0, b = 0.5, Pr = 1.0$ .


physical parameters appearing into the model are vortex viscosity parameter  $R$ , material parameter  $b$ , Prandtl number  $Pr$  and temperature ratio parameter  $m$  having values 0 and 1 for asymmetric and symmetric heating of the vertical walls, respectively. In this study, we have focused our attention on the physical parameters  $R, b$  and  $Pr$  and presented their influences through Figs. 1-12 on the velocity as well as micro-rotation profiles for asymmetric and symmetric heating of the vertical walls.

Figures 1 and 2 show the effect of material parameter  $b$  on the velocity profiles for different values of  $t$  when  $Pr = 1.0$  and  $R = 0.5$  for the cases of asymmetric and symmetric heating, respectively. In both thermal cases, we can observe that the velocity of fluid has attained steady state by increasing with the time and steady state times are 0.85 and 0.75 for asymmetric

heating case while 0.95 and 0.85 for symmetric heating case when  $b = 0.1$  and 1.0, respectively. Thus the steady state is achieved in the case of asymmetrical heating faster than in the case of symmetric heating. The effect of material parameter  $b$  is to make the flow steady state earlier. The influence of the vortex viscosity as well as time parameter on magnitude of the velocity profile for  $b = 0.5$  and  $Pr = 1.0$  is presented in Figs. 3 and 4 corresponding to the asymmetric and symmetric thermal cases. For both thermal cases, the velocity profiles have increasing tendency with time and have attained steady state profiles at  $t = 0.90$  and 0.85 for  $R = 0.4$  and 0.6, respectively. Hence, the vortex viscosity parameter has decreasing tendency on the velocity profiles and as well as on the steady state time. Figures 5 and 6 present the effect of Prandtl number  $Pr$  on the velocity profile for



**Figure 5:** Velocity Profile for different values of  $t$  at  $m = 0.0, R = 0.5, b = 0.5$ .




**Figure 6:** Velocity Profile for different values of  $t$  at  $m = 1.0, R = 0.5, b = 0.5$ .

the cases of asymmetric and symmetric heating at  $R = 0.5$  and  $b = 0.5$ . From these figures we can observed that the magnitude of the velocity profile decreases with increase in the value of Prandtl number for both cases. The steady state time is increasing with the  $Pr$ .

Figures 7 and 8 illustrate that the effect of material parameter  $b$  on the micro-rotation profiles for different values of  $t$  when  $Pr = 1.0$  and  $R = 0.5$  in the cases of asymmetric and symmetric heating, respectively. In both thermal cases, the steady state time and the magnitude of the micro-rotation have increasing tendency with the material parameter. A close study of these figures reveals that the steady state time in case of asymmetric heating is more than the symmetric heating. Figures 9 and 10 show the micro rotation profiles corresponding to the asymmetric and symmetric thermal cases for




**Figure 7:** Micro-rotation profile for different values of  $t$  at  $m = 0.0, R = 0.5, Pr = 1.0$ .




**Figure 8:** Micro-rotation profile for different values of  $t$  at  $m = 1.0, R = 0.5, Pr = 1.0$ .

$Pr = 1.0$  and  $b = 0.5$ . From these figures we find that steady state time are  $0.90(R = 0.4)$  and  $0.85(R = 0.6)$  for both thermal cases and thus the steady state time decreases as  $R$  increases. Also, the magnitudes of the micro-rotation profiles show the increasing tendency with  $R$ . Figures 11 and 12 show the effect of Prandtl number  $Pr$  at  $R = b = 0.5$  for asymmetric and symmetric heating, respectively. As discussed earlier, the variation in the magnitude of micro-rotation profile decreases. We found that the steady state times are  $0.95$  and  $0.80$  for  $Pr = 1.0$  and  $0.71$  for both thermal conditions and thus the steady state time of micro-rotation increases with the Prandtl number  $Pr$  for both thermal cases.



**Figure 9:** Micro-rotation profile for different values of  $t$  at  $m = 0.0, Pr = 1.0, b = 0.5$ .



**Figure 11:** Micro-rotation profile for different values of  $t$  at  $m = 0.0, R = 0.5, b = 0.5$ .



**Figure 10:** Micro-rotation profile for different values of  $t$  at  $m = 1.0, Pr = 1.0, b = 0.5$ .



**Figure 12:** Micro-rotation profile for different values of  $t$  at  $m = 1.0, R = 0.5, b = 0.5$ .

## 5 Conclusion

Here, we have investigated the effects of vortex viscosity parameter, material parameter and Prandtl number on free convective flow along vertical walls in case of asymmetric and symmetric heating or cooling of walls by obtaining the numerical solutions using the Matlab R2008a programming language code. It is seen that the steady state time of velocity profile is more for symmetric case than asymmetric case while the steady state time of micro-rotation profile for asymmetric heating is more than the symmetric heating with respect to the material parameter. The velocity profile decreases and micro-rotation profile of fluid increases at any point of fluid regime with vortex viscosity parameter. As the Prandtl number increases the steady state time for the velocity profile and micro-rotation

profile increases for both thermal cases.

## References

- [1] A. C. Eringen, *Theory of micropolar fluids*, Journal of Mathematics and Mechanics 16 (1966) 1-18.
- [2] A. C. Eringen, *Theory of thermo-micro-polar fluids*, Journal of Mathematical Analysis and Applications 38 (1972) 480-496.
- [3] V. U. K. Sastry, V. R. M. Rao, solution of micropolar fluid flow in a Channel with porous walls, International Journal of Engineering Science 20 (1982) 631-642.
- [4] R. Bhargava, M. Rani, *Numerical solution of heat transfer in micropolar fluid flow in a*

- channel with porous walls*, International Journal of Engineering Science 23 (1985) 409-413.
- [5] R. S. Agarwal, C. Dhanapal, *Numerical solution of free convection micropolar fluid flow between two parallel porous vertical plates*, International Journal of Engineering Science 26 (1988) 1247- 1255.
- [6] R. S. R. Gorla, B. Ghorashi, P. Wangskarn, *Mixed convection in vertical internal flow of a micropolar fluid*, International Journal of Engineering Science 27 (1989) 1553-1561.
- [7] Y. J. Kim, *Unsteady convection flow of micropolar fluids past a vertical porous medium*, Acta Mechanica 148 (2001) 106-116.
- [8] D. Srinivasacharya, J. V. R. Murthy, D. Venugopalam, *Unsteady stokes flow of micropolar fluid between two parallel porous plates*, International Journal of Engineering Science 39 (2001) 1557- 1563.
- [9] Y. J. Kim, *Unsteady MHD convection flow of polar fluids past a vertical moving porous plate in a porous medium*, International Journal Heat Mass Transfer 44 (2001) 2791-2799.
- [10] Y. J. Kim, A. G. Fedorov, *Transient mixed radiative convection flow of micropolar fluid past a moving semi-infinite vertical porous plate*, International Journal of Heat and Mass Transfer 46 (2003) 1751-1758.
- [11] R. Bhargava, L. Kumar, H. S. Takhar, *Numerical solution of free convection MHD micropolar fluid flow between two parallel porous vertical plates*, International Journal of Engineering Science 41 (2003) 123-136.
- [12] A. J. Chamkha, T. Grosan, I. Pop, *Fully developed free convection of a micropolar fluid in a vertical channel*, International Communications in Heat and Mass Transfer 29 (2002) 1119-1127.
- [13] A. K. Singh, T. Paul, *Transient natural convection between two vertical walls heated/cooled asymmetrically*, International Journal of Applied Mechanics and Engineering 11 (2006) 67-73.
- [14] C. I. Chen, *Non-linear stability characterization of the thin micropolar liquid film flowing down the inner surface of a rotating vertical cylinder*, Communications in Nonlinear Science and Numerical Simulation 12 (2007) 760-775.
- [15] M. M. Rahman, *Convective flows of micropolar fluids from radiate isothermal porous surfaces with viscous dissipation and Joule heating*, Communications in Nonlinear Science and Numerical Simulation 14 (2009) 3018-3030.
- [16] A. Ishak, R. Nazar, I. Pop, *Dual solutions in mixed convection boundary layer flow of micropolar fluids*, Communications in Nonlinear Science and Numerical Simulation 14 (2009) 1324-1333.
- [17] M. Sajid, N. Ali, T. Hayat, *On exact solutions for thin film flows of a micropolar fluid*, Communications in Nonlinear Science and Numerical Simulation 14 (2009) 451-461.
- [18] A. Ishak, R. Nazar, I. Pop, *MHD boundary-layer flow of a micropolar fluid past a wedge with constant wall heat flux*, Communications in Nonlinear Science and Numerical Simulation 14 (2009) 109-118.
- [19] D. Pal, S. Chatterjee, *Heat and mass transfer in MHD non-Darcian flow of a micropolar fluid over a stretching sheet embedded in a porous media with non-uniform heat source and thermal radiation*, Communications in Nonlinear Science and Numerical Simulation 15 (2010) 1843-1857.



Santos Kumar Ravi is an Assistant Development Officer in vikash khand Agra. He earned his PhD in Mathematics from Banaras Hindu University, Varanasi, India, in 2012. His research interests include fluid flow in porous media, heat and mass transfer and magnetohydrodynamics. He has authored and co-authored over 13 papers in journals and conferences.





A. K. Singh is a Professor in the Department of Mathematics, Banaras Hindu University, Varanasi, India. He earned his PhD in Mathematics from Banaras Hindu University, Varanasi, India, in 1979.

He earned his D.Sc in Mathematics from Banaras Hindu University, Varanasi, India, in 1986. His research interests include Differential Equations, Fluid Dynamics and Numerical Analysis, Magnetohydrodynamic flows, Flow through porous media, Non-Newtonian fluids, Heat and Mass Transfer and Transport processes in Cavity. He is currently the Editor-in-Chief for the Mathematical Society Banaras Hindu University, Varanasi, India. He has authored and co-authored over 140 papers in reputed journals.

and co-authored over 370 papers in archival journals and conferences.



R. K. Singh is an assistant Professor in Department of Mathematics Uka Tarsadia University, Bardoli, Surat. He earned his PhD in Mathematics from Banaras Hindu University, Varanasi, India, in 2010.

His research interests include Non-newtonian fluid, heat and mass transfer and magnetohydrodynamics. He has authored and co-authored over 10 papers in reputed journals.



Ali J. Chamkha is a Professor in the Manufacturing Engineering Department, College of Technological Studies at the Public Authority for Applied Education and Training in Kuwait. He earned his PhD in Mechanical Engineering

from Tennessee Technological University, USA, in 1989. His research interests include multi-phase fluid-particle dynamics, fluid flow in porous media, heat and mass transfer, magnetohydrodynamics and fluid particle separation. He has served as an Associate Editor for many journals such as International Journal of Numerical Method for Heat and Fluid Flow, Journal of Applied Fluid Mechanics, International Journal for Microscale and Nanoscale Thermal and Fluid Transport Phenomena and he is currently the Deputy Editor-in-Chief for the International Journal of Energy Technology. He has authored

Archive of SID