

Estimating of sesame crop water requirement in Sabzevar climate

Gholamabbas Fallah Ghalhari*

Assistant Professor, Faculty of Geography and Environmental Sciences, Hakim Sabzevari University, Sabzevar, Iran.

Mahdi rahchamani

M.Sc Student of Applied Climatology, Hakim Sabzevari University, Sabzevar, Iran.

Fereshteh Bayranvand

M.Sc Student of Applied Climatology, Hakim Sabzevari University, Sabzevar, Iran.

Extended Abstract

Introduction

Oilseeds after Cereals make up the second world food supply. Sesame is one of the oldest cultivated plants and possibly the world's oldest oil plants. Nowadays, sesame is used as a source of edible oil. Sesame home is warm and semi-warm areas, but its cultivation spread to temperate regions (Weise, 2000). To effectively and efficiently use the available water sources to meet the possible variation of cropping pattern, studies of crop water requirements for upland and paddy crops based on derived crop coefficient are crucial (Sheng et.al, 2006). Irrigation is a vital input in the agricultural productivity and agricultural growth. More than 80% of available water resources worldwide as well as in India are being presently utilized for irrigation purposes (Pradeep, 2015). World sesame cultivation in 2007 amounted to 3.7 million hectares and 3.3 million tons of production have been reported.

Research Methodology

Sabzevar City has expanded from 56° '04 to 58° '15 E and 35° '30 to 36° ' 58 N and has an elevation of 977 meters above sea level and with an area of 20502 square kilometers is located in West of Khorasan Razavi. To estimate crop water requirements (CWR) and irrigation water requirements (IWR) CROPWAT model was used. In this study, for the calculation of reference evapotranspiration, FAO - Penman-Monteith equation is used. To calculate the reference evapotranspiration using FAO-Penman-Monteith equation, climate data such as minimum and maximum air temperature, relative humidity, sunshine hours and wind speed is required. Other inputs of the model is cultivation pattern, the plant coefficient, the area under cultivation (1 to 100 percent of area), irrigation scheduling, soil type, the available soil moisture, root depth and water content in the soil.

Discussion and Results

According to the obtained results, the mountainous regions of northern Sabzevar in all phases have the lowest water requirement and southern regions have the greatest need of water. The results also showed that by moving from north to south, water requirement increases. Most of the irrigation requirement is related to the early and middle stages of growth. Soil moisture curve shows the least amount of soil moisture occur on the intermediate and final stages of product development. Results also showed that the crop coefficient in the middle stages of growth season is the highest value. The lowest water requirements occur in the final stages of growth season. The results indicated that the irrigation depth is occurred two to three months after the date of sesame cultivation.

Conclusion

Based on the results of the model, sesame crop water requirements in Sabzevar plain because of low rainfall and high temperature during the year and the long-term of the dry period shows a high level.

* Email: Ab_fa789@yahoo.com

The results showed that sesame plants to complete their growth needs to at least 20 times irrigation. It should be noted that to prevent soil crusting and emergence of a plant, round and deep of irrigation in the early stages of growth is low, but with the passage of time from planting date and getting to the middle phase of growth, both irrigation and water depth increases. Given that the final stages of development and ripening seeds in Sabzevar is consistent with the onset of the dry season, soil faced with moisture deficit and continuing of this process causing plant stress and lack of growth. Because the sesame plant is resistant to drought, in plain of Sabzevar produces good and economic products. In term of climatic conditions and compatibility of this product with environment, sesame can be cultivated but in the southern areas, it needs to repeat more frequently.

Keywords: Sabzevar plain, Sesame, water requirement, CROPWAT model.

References

1. Bouraima A.K., Zhang W., and Wei C., (2015). Irrigation water requirements of rice using Cropwat model in Northern Benin, international journal of agricultural and biological engineering, 8(2): pp 58-64.
2. Evemoje T., (2007). Variable Irrigation Scheduling Effects on Growth Parameters of Celosia Argentea in Humid Tropical Environment, Agricultuerral engineerin Internatial the CIGR Ejournal. Manuscript LW 06 018. Vol. IX.
3. Frenken K and Gillet V., (2012). Irrigation water requirement and water withdrawal by Country, AQUASTAT, http://www.fao.org/nr/water/aquastat/water_use_agr/index.stm.
4. Golestani M., Pakniyat H., (2007). Evaluation of drought tolerance indices in Sesame lines, Journal of Science and Technology of Agriculture and Natural Resources, 11(4): 141-149.
5. Janick J and Whipkey A., (2007). Issues in new crops and new uses, ASHS Press, Alexandria, VA.
6. Khani M., Heydarabadi Shirifabad H., Madani H., Noormohammadi Gh., Darvish F., (2010). Selection for drought resistance in genotypes of sesame, New findings in Agriculture, 4(4): 347-359.
7. Lashkari H., Keykhosravi Gh., Rezaei A., (2009). Analysis of the performance of CROPWAT model to estimate crop water demand in West Kermanshah: Cities of West Eslamabad, Sar-e Pol Zahab and Rawansar, professor of humanities Journal, 13(1): 247-270.
8. Mohajerani H., Mosaedi A., Kholghi M., Meftah Talaghi M., Sadodin A., (2010). The estimate of wheat crop water demand by using CROPWAT model in Kordkoy city –Golestan province, National conference on managing water deficit and drought stress in agriculture, 23-24 February 2010, Islamic Azad University of Arsanjan.
9. Nazeer, M. (2009). Simulation of maize crop under irrigated and rained conditions with CROPWAT model. ARPN J. Agric. Biol. Sci, 4(2), pp 68-73.
10. Pradeep B , Jadia B.B. , Sangale S.T. ., (2015). Case Studies of Innovative Irrigation Management Techniques, Aquatic Procedia, 4: pp1197-1202.
11. Rahimi D., Salahshour F., (2014). Estimation of Water Requirement, Evaporation and Potential Transpiration of Brassica Napus L Plant in Ahwaz Town Using CROWPWAT Model, 2(4): pp1377-1387.
12. Salehi M., Saeidi Gh., 2012. Select indicators to improve yield of sesame seeds, Journal of Iran agricultural researches, 10(4): 667-673.
13. Sheng-Feng Kuo, Shin-Shen Ho, Chen-Wuing Liu., (2006). Estimation irrigation water requirements with derived crop coefficients for upland and paddy crops in ChiaNan Irrigation Association, Taiwan, Agricultural Water Management, 82, pp 433–451.
14. Stancalie G., Marica A., Toullos L., (2010). Using earth observation data and CROPWAT model to estimate the actual crop evapotranspiration, Physics and Chemistry of the Earth, Parts A/B/C, 35(1-2): pp25-30.
15. Surendran U., Sushanth C.M., George M, and Joseph.J., (2015). Modelling the crop water requirement using FAO CROPWAT and assessment of water resources for sustainable water resource management: A case study in Palakkad district of humid tropical Kerala, India., Aquatic Procedia, 4, pp 1211 – 1219.
16. Vaziri J., Salamat A., Entesari M.R., Meschi M., Heydari N and Dehghani Sanich H., 2008. Plant Evapotranspiration (guidelines of water consumption required by the plants), Publications of the National Committee on Irrigation and Drainage, First Edition, 389 PP.
17. Weise, E. A. (2000). Oilseed crops. Blackwell Sci., Ltd Oxford, UK. p 364.