ORIGINAL ARTICLE

Seismic response of torsionally coupled building with passive and semi-active stiffness dampers

Snehal V. Mevada · R. S. Jangid

Received: 26 February 2014/Accepted: 12 January 2015/Published online: 4 February 2015 © The Author(s) 2015. This article is published with open access at Springerlink.com

Abstract The seismic response of single-storey, oneway asymmetric building with passive and semi-active variable stiffness dampers is investigated. The governing equations of motion are derived based on the mathematical model of asymmetric building. The seismic response of the system is obtained by numerically solving the equations of motion using state-space method under different system parameters. The switching and resetting control laws are considered for the semi-active devices. The important parameters considered are eccentricity ratio of superstructure, uncoupled lateral time period and ratio of uncoupled torsional to lateral frequency. The effects of these parameters are investigated on peak lateral, torsional and edge displacements and accelerations as well as on damper control forces. The comparative performance is investigated for asymmetric building installed with passive stiffness and semi-active stiffness dampers. It is shown that the semi-active stiffness dampers reduce the earthquake-induced displacements and accelerations significantly as compared to passive stiffness dampers. Also, the effects of torsional coupling on effectiveness of passive dampers in reducing displacements and accelerations are found to be more

S. V. Mevada (🖂)
Structural Engineering Department, Birla Vishvakarma
Mahavidyalaya (Engineering College),
Vallabh Vidyanagar 388 120, India
e-mail: svmevada@bvmengineering.ac.in
R. S. Jangid
Department of Civil Engineering, Indian Institute
of Technology Bombay, Powai, Mumbai 400 076, India

e-mail: rsjangid@civil.iitb.ac.in

significant to the variation of eccentricity as compared to semi-active stiffness dampers.

Keywords Seismic response · Torsionally coupled · Eccentricity · Passive stiffness damper · Semi-active stiffness damper

List of symbols

a	Plan dimension of building, parallel to the
	direction of ground motion
a_0, a_1	Coefficients for mass and stiffness matrices
	for Rayleigh's damping matrix
A	System matrix
A_d	Discrete-time system matrix
b	Plan dimension of building, perpendicular to
	the direction of ground motion
B	Distribution matrix of control forces
B_d	Discrete-time counterpart of distribution
	matrix of control forces
С	Structural damping matrix of the system
e_x	Structural (superstructure) eccentricity
	between CM and centre of rigidity (CR) of
	the system
Ε	Distribution matrix of excitation forces
E_d	Discrete-time counterpart of distribution
	matrix of excitation forces
F_{dy}	Resultant damper force in y-direction
$F_{d\theta}$	Resultant damper force in θ -direction
F_{df}	Control force of damper installed at flexible
	edge of building
F_{di}	Control force in <i>i</i> th damper
F_{ds}	Control force of damper installed at stiff
	edge of building
F_{dT}	Total (resultant) damper control force



E	Domnon control fores vestor
Г	Damper control force vector
g	Acceleration due to gravity
1	Identity matrix
k	Time step
k_f	Stiffness of stiffness damper
k _r	Stiffness ratio
k_{bs}	Bracing stiffness of stiffness damper
k_{hi}	Effective damper stiffness for <i>i</i> th stiffness
	damper
k _{si}	Stiffness of <i>i</i> th storey
K_{xi}, K_{vi}	Lateral stiffness of <i>i</i> th column in <i>x</i> -direction
	and y-direction, respectively
K_{v}	Total lateral stiffness of the system in y-
y	direction
$K_{\theta_{m}}, K_{\Theta\Theta}$	Torsional stiffness of system about vertical
1107, 1100	axis at the CR and CM respectively
K	Stiffness matrix of the system
K and Kaa	Stiffness matrices in y direction and A
\mathbf{K}_{y} and $\mathbf{K}_{\theta\theta}$	direction respectively
100	Lumpad mass of the deak (floor)
m M	Lumped mass of the deck (noor)
IVI	Mass matrix of the system
r	Mass radius of gyration about a vertical axis
D	through CM
R_e	Response ratio to study the effectiveness of
_	control system
R_t	Response ratio to study the effects of
	torsional coupling
T_y	Uncoupled lateral time period of system
u_i	Relative displacement at the location of <i>i</i> th
	stiffness damper
<i>u_{ri}</i>	Resetting position of <i>i</i> th stiffness damper
u_{y} and \ddot{u}_{y}	Lateral displacement and acceleration at CM
	of floor, in <i>y</i> -direction
u_{vf} and \ddot{u}_{vf}	Displacement and acceleration at flexible
	edge of building
u_{vs} and \ddot{u}_{vs}	Displacement and acceleration at stiff edge
	of building
u_{θ} and \ddot{u}_{θ}	Torsional displacement and acceleration at
	CM of floor, in θ -direction
u	Displacement vector
<i>ù</i>	Velocity vector
ü	Acceleration vector
н И а	Ground acceleration vector
ü ü	Ground acceleration in v-direction
u gy	Switching parameter of <i>i</i> th stiffness damper
	r coordinate and y coordinate distances of
$x_i y_i$	ith alament from CM respectively
7	State vector
۰. ۲-	December for resulting stiffness control law
α_L	rataneter for resetting sufficient vector
1	Time interval
Δt	1 ime interval
Λ	Location matrix for control forces

ω_y	Uncoupled lateral frequency of the system
ω_{θ}	Uncoupled torsional frequency of the system
$\Omega_{ heta}$	Ratio between uncoupled torsional to lateral
	frequency

Introduction

The asymmetry in buildings may be due to the uneven distribution of mass and/or stiffness of the structural members. In the past, many such asymmetric buildings have got severe damage during the seismic events. To prevent such damage, the eccentricity which is produced due to irregular distribution of mass and/or stiffness should be avoided. However, it may not be possible all the times to avoid the eccentricity due to stringent architectural and functional requirements, hence in such cases, the use of energy dissipation devices shall be beneficial to minimize the lateral–torsional responses.

In the past, many researchers have investigated the performance of base isolation, passive controls and active controls for asymmetric buildings. Hejal and Chopra (1989) studied the effects of lateral-torsional couplings and found that the response of building depends on structural eccentricity and frequency ratio. Jangid and Datta (1994) found that the effectiveness of base isolation reduces for higher eccentricity for torsionally coupled system. Jangid and Datta (1997) investigated that the effectiveness of multiple tuned mass dampers is overestimated by ignoring the system asymmetry. Goel (1998) investigated that the edge deformations in asymmetric-plan systems can be reduced than those in the corresponding symmetric systems by implementing proper supplemental damping. Date and Jangid (2001) carried out the study for asymmetric system with active control system and found that the effectiveness is overestimated by ignoring the effects of torsional coupling. Lin and Chopra (2003) investigated the effectiveness of nonlinear viscous and visco-elastic dampers and concluded that the asymmetric distribution of damping reduces the response more effectively as compared to the symmetric distribution. De La Llera et al. (2005) proposed the weak torsional balance condition for system installed with friction dampers such as to minimize the correlation between translation and rotation. Matsagar and Jangid (2005) investigated the effects of torsional coupling on seismic response of base-isolated buildings and observed that for torsionally flexible system, the displacement response is more than that in case of the torsionally rigid system. Petti and De Iuliis (2008) proposed a method to optimally locate the viscous dampers for torsional response control in asymmetric-plan systems. Matsagar and Jangid (2010) studied the seismic response of asymmetric base-isolated structure during impact with adjacent structures and without impact. It was found that the torsionally coupled response becomes adverse with increasing eccentricities. Mevada and Jangid (2012a) investigated the performance of linear and non-linear viscous dampers for asymmetric systems and found that the effects of torsional coupling are less for asymmetric systems with non-linear dampers as compared to linear dampers.

Moreover, some of the researchers have studied the effects of semi-active control systems for asymmetric buildings in the recent past. Chi et al. (2000) investigated the performance of base isolation and semi-active magnetorheological (MR) damper in asymmetric building and found them very effective for controlling the lateral-torsional responses. Yoshida et al. (2003) investigated the effectiveness of semi-active MR damper to control the torsional response of asymmetric building and concluded that the asymmetry leads to an increase in torsional response and decrease in translational response. Shook et al. (2009) studied the effectiveness of semi-active MR damper with fuzzy logic controller and found that it is effective in reducing the displacement and acceleration responses. Li and Li (2009) investigated the effectiveness of MR damper based on semi-geometric model for asymmetric building and found a greater reduction in displacement and acceleration responses compared to passive control case. Mevada and Jangid (2012b) investigated the seismic response of asymmetric building installed with semi-active variable dampers. It was observed that for torsionally flexible and strongly coupled systems, the effects of torsional coupling are more pronounced as compared to torsionally stiff systems. Mevada and Jangid (2012c) studied the effects of torsional coupling for asymmetric building installed with semi-active MR dampers and found that the effects of torsional coupling on effectiveness of semi-active MR damper system are more sensitive to the variation of eccentricity and torsional to lateral frequency ratio. Although, above studies reflect the effectiveness of passive and some of the semiactive systems in controlling the lateral-torsional responses, however, no specific study has been done to investigate the effectiveness of semi-active stiffness dampers for asymmetric buildings. Also, a comparative study to investigate the performance of passive stiffness and semi-active stiffness dampers for torsionally coupled building has not been done so far. Further, the effects of torsional coupling on the effectiveness of passive and semi-active stiffness dampers for the asymmetric systems are also not studied.

In this paper, the seismic response of single-storey, oneway asymmetric building is investigated under various earthquake ground motions. The objectives of the study are summarized as (i) to investigate the comparative seismic response of asymmetric building installed with passive stiffness damper (PSD) and two types of semi-active variable stiffness dampers (SAVSDs) namely, switching semi-active stiffness damper (SSASD) and resetting semi-active stiffness damper (RSASD) in controlling lateral, torsional and edge displacements as well as accelerations, and (ii) to study the effects of torsional coupling on the effectiveness of passive and semi-active variable stiffness dampers for asymmetric building as compared to the corresponding symmetric building. The important parameters considered are eccentricity ratio of superstructure, uncoupled time period and ratio of uncoupled torsional to lateral frequency.

Structural model and solution of equations of motion

The system considered is an idealized single-storey building which consists of a rigid deck supported on columns as shown in Fig. 1. Following assumptions are made for the



(a) Plan of one-way asymmetric building



(b) Isometric view of system showing arrangement of dampers

Fig. 1 Plan and isometric view of one-way asymmetric building showing arrangement of dampers



structural system under consideration: (i) floor of the superstructure is assumed as rigid, (ii) force-deformation behaviour of the superstructure is considered as linear and within elastic range (iii) the structure is excited by unidirectional horizontal component of earthquake ground motion and the vertical component of earthquake motion is neglected, and (iv) mass of the columns is ignored and the columns are considered to only provide lateral stiffness. The mass of deck is assumed to be uniformly distributed and hence centre of mass (CM) coincides with the geometrical centre of the deck. The columns are arranged in a way such that it produces the stiffness asymmetry with respect to the CM in one direction and hence, the centre of rigidity (CR) is located at an eccentric distance, e_x from CM in x-direction. The system is symmetric in x-direction and therefore, two degrees of freedom are considered for model namely the lateral displacement in y-direction, u_y and torsional displacement, u_{θ} as represented in Fig. 1. The governing equations of motion of the building with lateral and torsional degrees of freedom are obtained by assuming that the control forces provided by the dampers are adequate to keep the response of the structure in the linear range. The equations of motion of the system in the matrix form are expressed as

$$M\ddot{u} + C\dot{u} + Ku = -M\Gamma\ddot{u}_g + \Lambda F,\tag{1}$$

where M, C and K are mass, damping and stiffness matrices of the system, respectively; $\boldsymbol{u} = \{u_y u_\theta\}^T$ is the displacement vector; Γ is the influence coefficient matrix; $u_g =$ $\{\ddot{\boldsymbol{u}}_{gy}0\}^{\mathrm{T}}$ is the ground acceleration vector; $\ddot{\boldsymbol{u}}_{gy}$ is the ground acceleration in y-direction; Λ is the matrix that defines the location of control devices and $F = \{F_{dy} F_{d\theta}\}^{T}$ is the vector of control forces; and F_{dy} and $F_{d\theta}$ are resultant control forces of dampers along y- and θ -direction, respectively.

The mass matrix can be expressed as:

$$\boldsymbol{M} = \begin{bmatrix} \boldsymbol{m} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{m}\boldsymbol{r}^2 \end{bmatrix},\tag{2}$$

where m represents the lumped mass of the deck; and r is the mass radius of gyration about the vertical axis through CM which is given by, $r = \sqrt{(a^2 + b^2)/12}$; where a and *b* are the plan dimensions of the building.

The stiffness matrix of the system is obtained as follows,

$$\boldsymbol{K} = \boldsymbol{K}_{y} \begin{bmatrix} 1 & e_{x} \\ e_{x} & e_{x}^{2} + r^{2} \Omega_{\theta}^{2} \end{bmatrix}$$
(3)

$$e_x = \frac{1}{K_y} \sum_i K_{yi} x_i \tag{4}$$

$$\Omega_{\theta} = \frac{\omega_{\theta}}{\omega_{v}} \tag{5}$$

$$\omega_{\theta} = \sqrt{\frac{K_{\theta r}}{mr^2}} \quad \text{and} \quad \omega_y = \sqrt{\frac{K_y}{m}} \tag{6}$$

$$K_{\theta r} = K_{\theta \theta} - e_x^2 K_y$$
 and $K_{\theta \theta} = \sum_i K_{xi} y_i^2 + \sum_i K_{yi} x_i^2$, (7)

where K_{y} denotes the total lateral stiffness of the building in ydirection; e_x is the structural eccentricity between CM and CR of the system; Ω_{θ} is the ratio of uncoupled torsional to lateral frequency of the system; K_{vi} indicates the lateral stiffness of *i*th column in y-direction; x_i is the x-coordinate distance of *i*th column with respect to CM; ω_v is uncoupled lateral frequency of the system; ω_{θ} is uncoupled torsional frequency of the system; $K_{\theta r}$ is torsional stiffness of the system about a vertical axis at the CR; $K_{\theta\theta}$ is torsional stiffness of the system about a vertical axis at the CM; K_{xi} indicates the lateral stiffness of *i*th column in x-direction; and y_i is the y-coordinate distance of *i*th column with respect to CM.

The damping matrix of the system is not known explicitly and it is constructed from the Rayleigh's damping considering mass and stiffness proportional as,

$$C = a_0 M + a_1 K, \tag{8}$$

in which a_0 and a_1 are the coefficients depending on damping ratio of two vibration modes. For the present study, 5 % damping is considered for both modes of vibration of system.

The governing equations of motion are solved using the state-space method (Hart and Wong 2000; Lu 2004) and rewritten as:

$$\dot{z} = Az + BF + E\ddot{u}_g,\tag{9}$$

where $z = \{u \ \dot{u}\}^{T}$ is a state vector; A is the system matrix; B is the distribution matrix of control forces; and E is the distribution matrix of excitations. These matrices are expressed as,

$$\boldsymbol{A} = \begin{bmatrix} \boldsymbol{0} & \boldsymbol{I} \\ -\boldsymbol{M}^{-1}\boldsymbol{K} & -\boldsymbol{M}^{-1}\boldsymbol{C} \end{bmatrix}; \ \boldsymbol{B} = \begin{bmatrix} \boldsymbol{0} \\ \boldsymbol{M}^{-1}\boldsymbol{\Lambda} \end{bmatrix} \text{ and } \boldsymbol{E} = -\begin{bmatrix} \boldsymbol{0} \\ \boldsymbol{\Gamma} \end{bmatrix},$$
(10)

in which *I* is the identity matrix.

While Eq. (9) is discretized in time domain and the excitation and control forces are assumed to be constant within any time interval, the solution may be written in an incremental form (Hart and Wong 2000; Lu 2004),

$$\boldsymbol{z}[k+1] = \boldsymbol{A}_{\boldsymbol{d}}\boldsymbol{z}[k] + \boldsymbol{B}_{\boldsymbol{d}}\boldsymbol{F}[k] + \boldsymbol{E}_{\boldsymbol{d}}\boldsymbol{u}_{\boldsymbol{g}}[k], \qquad (11)$$

where k denotes the time step; and $A_d = e^{A\Delta t}$ represents the discrete-time system matrix with Δt as the time interval. The constant coefficient matrices B_d and E_d are the discrete-time counterparts of the matrices **B** and **E** and can be written as



$$B_d = A^{-1}(A_d - I)B$$
 and $E_d = A^{-1}(A_d - I)E$. (12)

Model of damper and control laws

Semi-active stiffness control devices are utilized to modify the stiffness and thus the natural vibration characteristics of the structure to which they are attached. The system primarily controls the stiffness of a building to establish a non-resonant condition during earthquakes. The semiactive stiffness devices are engaged or released so as to include or not include, respectively, the stiffness of the bracing system of the structure. Normally, the device is composed of a hydraulic cylinder with a normally closed solenoid control valve inserted in the tube connecting the two cylinder chambers. The solenoid valve can either be on or off, thus opening or closing, respectively, the fluid flow path through the tube. When the valve is closed, the fluid cannot flow and effectively locks the beam to the braces below. In contrast, when the valve is open, the fluid flows freely and disengages the stiffness control devices. The system may be regarded as fail-safe in the sense that the interruption of power causes the semi-active stiffness devices to automatically engage, thus increasing the stiffness of the structure (Kamagata and Kobori 1994; Kobori et al. 1993; Yang et al. 1996).

In past, many researchers have investigated the seismic response of symmetric structures using stiffness dampers. The non-resonant-type control system called as active variable systems were proposed by Kamagata and Kobori (1994) and Kobori et al. (1993). This system produces a non-stationary, non-resonant condition during earthquakes which is achieved by altering the building's stiffness based on the nature of the earthquake. Yang et al. (1996) proposed the control methods based on sliding mode control to control the response of building installed with active variable systems. The semi-active stiffness and damping control device which are capable of modifying stiffness and damping in a continuous manner is proposed by Nagarajaiah and Mate (1997). Yang et al. (2000) proposed a general resetting control law for semi-active stiffness dampers and compared the performance of resetting and switching control laws for seismic response of symmetric buildings. Nasu et al. (2001) described the non-resonant control algorithm for the active variable stiffness system and verification of effectiveness of this control system. Kori and Jangid (2007) modified the switching control law based on the feedback from the displacement response.

Figure 2 shows the schematic and mathematical model of stiffness damper. When the valve is closed, the damper serves as a stiffness element in which the stiffness (k_f) is provided by the bulk modulus of the fluid in the cylinder.





(b) Mathematical model of damper

Fig. 2 Schematic and mathematical model of semi-active variable stiffness damper (Yang et al. 2000)

When the valve is open, the piston is free to move and the damper provides only a small damping without stiffness. The effective stiffness of the device consists of damper stiffness (k_f) and bracing stiffness (k_{bs}) and it is given by Yang et al. (2000) as follows:

$$k_{hi} = \frac{k_{fi}k_{bsi}}{(k_{fi} + k_{bsi})}.$$
(13)

Switching semi-active control law

This control law has been derived based on sliding mode control by Kamagata and Kobori (1994) and Yang et al. (1996). In this control, the valve of hydraulic damper is pulsed to open during a certain time interval and close during another time interval, which can be referred as switching semi-active stiffness damper (SSASD). When a valve of the *i*th damper is closed, the effective stiffness, k_{hi} , is added to the storey unit and when a valve is open, the effective stiffness, k_{hi} , is zero. When the valve is switched off from on, a certain amount of energy is taken out of the structural system and when it is on, energy is added to the structural system.

The control force of *i*th SSASD can be obtained as

$$F_{di} = k_{hi} v_{si} u_i, \tag{14}$$

where k_{hi} is the effective stiffness of *i*th damper; u_i is the relative displacement at the location of *i*th damper; and v_{si} is the switching parameter of *i*th damper which is based on the switching control law expressed as (Yang et al. 2000)



$$v_{si}(t) = \begin{cases} 1 & \text{if } u_i \dot{u}_i \ge 0\\ 0 & \text{otherwise} \end{cases}$$
(15)

when $v_{si}(t) = 1$, indicates that the *i*th SSASD is locked (i.e. valve is closed) and $v_{si}(t) = 0$, indicates the *i*th SSASD is unlocked (i.e. valve is open).

Resetting semi-active control law

In this control, the valve of hydraulic damper is closed for most of the time. Hence, the energy is stored in the damperbracing systems in the form of potential energy. At appropriate time instants, the valve is pulsed to open and close quickly. The position of the piston of damper at that moment is referred as resetting position, u_{ri} , and energy is released during this stage. The hydraulic damper in resetting mode is referred as resetting semi-active stiffness damper (RSASD) (Yang et al. 2000). The control force of *i*th RSASD can be obtained as

$$F_{di} = k_{hi}(u_i - u_{ri}), \tag{16}$$

where u_{ri} is resetting position of *i*th damper. When the RSASD is reset (valve is pulsed to open and close), $u_{ri} = u_i$. At that instant, the applied damper force is zero. Yang et al. (2000) derived a resetting control law considering the Lyapunov function V as follows:

$$V = 0.5 \ \boldsymbol{u}^T \boldsymbol{K} \boldsymbol{u} + 0.5 \ \boldsymbol{\dot{u}}^T \boldsymbol{M} \underline{\boldsymbol{u}} + \alpha_L \boldsymbol{u}^T \boldsymbol{M} \underline{\boldsymbol{u}}, \tag{17}$$

where α_L is constant such that the Lyapunov function is positive definite as follows:

$$\begin{bmatrix} \mathbf{K} & \alpha_L \mathbf{M} \\ \alpha_L \mathbf{M} & \mathbf{M} \end{bmatrix} > 0.$$
 (18)

Based on this, by minimizing \dot{V} , Yang et al. (2000) derived the resetting control law as follows:

$$u_{ri} = u_i \text{ when } \dot{u}_i + \alpha_L u_i = 0.$$
(19)

Passive control

In passive mode of control, the valve is either always open or always closed. When the valve is always closed, the switching parameter v_{si} is always considered equal to unity and the damper force of passive stiffness damper (PSD) is calculated as expressed in Eq. (14).

Numerical study

The seismic response of linearly elastic, single-storey, oneway asymmetric building installed with passive stiffness dampers (PSDs) and semi-active variable stiffness dampers (SAVSDs) is investigated by numerical simulation study.



Total two stiffness dampers (either passive or semi-active, one at each edge) are installed in building as shown in Fig. 1. The force-deformation behaviour of the superstructure with dampers is assumed as linear and within elastic range. The response quantities of interest are lateral and torsional displacements of the floor obtained at the CM (u_v and u_θ), displacements at stiff and flexible edges of the system (u_{vs} and $u_{vf} = u_y \pm b \, u_{\theta}/2$), lateral and torsional accelerations of the floor obtained at the CM (\ddot{u}_{y} and \ddot{u}_{θ}), accelerations at stiff and flexible edges of the system (\ddot{u}_{vs} and $\ddot{u}_{vf} = \ddot{u}_v \pm b \ddot{u}_{\theta}/2$) as well as control forces of dampers located at stiff edge (F_{ds}) and at flexible edge (F_{df}) of the building. The response is investigated under following parametric variations: structural eccentricity ratio (e_x/r) , uncoupled lateral time period of system $(T_v = 2\pi/\omega_v)$ and uncoupled torsional to lateral frequency ratio ($\Omega_{\theta} = \omega_{\theta}/\omega_{v}$). The peak responses are obtained corresponding to the system parameters which are listed above and variations are plotted for the four real earthquake ground motions namely, Imperial Valley (1940), Loma Prieta (1989), Northridge (1994) and Kobe (1995) as per the details summarized in Table 1. The time histories of the ground motions of the earthquakes are shown in Fig. 3. These considered earthquakes are most accurately recorded and are widely used by the researchers and they cover the range of all varieties of earthquakes and hence shall be helpful to lead to the generalized conclusions. Total seismic weight of building considered for the present study is W = 250 kN and the aspect ratio between plan dimensions is considered as unity. For the numerical study carried out herein, the MATLAB tool has been used to solve the equations of motion. To study the effectiveness of implemented control system, the response is expressed in terms of indices, R_e and R_t , defined as follows:

$$R_e = \frac{\text{Peak response of controlled asymmetric system}}{\text{Peak response of corresponding uncontrolled system}}$$
(20)

$$R_t = \frac{\text{Peak response of controlled asymmetric system}}{\text{Peak response of corresponding symmetric system}}.$$
(21)

The value of R_e less than one indicates that the implemented control system is effective in reducing the responses. On the other hand, the value of R_t reflects the effects of torsional coupling on the effectiveness of control system. The value of R_t greater than one indicates that the response of controlled asymmetric system increases due to torsional coupling as compared to the corresponding symmetric system.

For the stiffness damper, the effective damper stiffness (k_{hi}) plays an important role while designing the control system. For the present study, the stiffness ratio, (k_r) is defined as follows

Earthquake	Recording station	Component	Duration (sec)	PGA (g)
Imperial Valley, 19 May 1940	El Centro (USGS 117, Array# 9)	ELC 180	40	0.31
Loma Prieta, 18 October 1989 Los Gatos Presentation Center (LGPC, UCSC 16)		LGP 000	25	0.96
Northridge, 17 January 1994	Sylmar Converter Station (DWP 74)	SCS 142	40	0.89
Kobe, 16 January 1995	Japan Meteorological Agency (JMA, 99999 KJMA)	KJM 000	48	0.82

Table 1 Details of earthquake motions considered for the numerical study



Fig. 3 Earthquake ground motions considered for the study

$$k_r = \frac{k_{hi}}{k_{si}},\tag{22}$$

where k_{si} is the storey stiffness.

To arrive at the optimum value of stiffness ratio (k_r) , a parametric study is carried out for torsionally flexible $(\Omega_{\theta} = 0.5)$, strongly coupled $(\Omega_{\theta} = 1)$ and torsionally stiff $(\Omega_{\theta} = 2)$ systems with lateral time period, $T_y = 1$ s, and intermediate eccentricity ratio, $e_x/r = 0.3$, installed with RSASDs. The response ratio, R_e , are obtained for various displacements and accelerations and plotted against k_r (which is varied from 0 to 2) in Figs. 4, 5 and 6 for systems with $\Omega_{\theta} = 0.5$, 1 and 2, respectively. Initially, the constant α_L of resetting control law is considered as zero (Yang et al. 2000). It is observed from the individual trends of various earthquakes as well as from average trends (of four earthquakes) from Figs. 4, 5 and 6 that with the increase in k_r , the ratio, R_e , for various displacements (u_{θ} , u_{y} , u_{ys} and u_{vf}), decreases continuously. This implies that the control system is more effective in reducing displacement with higher values of k_r . On the other hand, R_e for various accelerations $(\ddot{u}_{\theta}, \ddot{u}_{y}, \ddot{u}_{ys})$ and \ddot{u}_{yf} decreases initially with increase in k_r and then increases with further increase in k_r . This implies that there exists an optimum range of stiffness ratio, k_r , to achieve the optimum reduction in torsional, lateral and edge accelerations. It is to be noted that the similar trends are observed for other values of Ω_{θ} (i.e. =1 and 2) Moreover, the variation of normalized peak resultant damper force against ratio, k_r , is also shown in Figs. 4, 5, and 6. The damper forces are normalized with the total weight of building, W. It is observed that for larger values of k_r , the control forces developed in the dampers are more. Thus, for asymmetric buildings, the torsional, lateral and edge displacements decrease with the increase in stiffness ratio (i.e. ratio between effective damper stiffness to storey stiffness). On the other hand, there exists an optimum value of stiffness ratio for torsional, lateral and edge accelerations. Hence, to achieve the optimum compromise between reduction in various displacement and acceleration responses as well as damper capacity, the suitable value of stiffness ratio, k_r , is considered as 0.5 for the present study.

The constant α_L used for resetting control law also plays an important role in performance of control system. Figure 7 shows the variations of ratio, R_e , for lateral-torsional displacements and accelerations against α_L . Initially the constant α_L is considered as zero and varied as long as the check for Lyapunov function (given by Eqs. 17 and 18) holds good. For the considered structural model, the Lyapunov function does not hold good beyond the value of $\alpha_L = 5$. It is observed from the Fig. 7 that the ratios, R_e , for various responses mildly increase with increase in α_L , in general. However, the variation of R_e for u_{θ} is little more sensitive to the change in α_L . Thus, for the study carried out herein, the constant α_L is considered as zero which led to higher reduction in various responses for structural system under consideration.





Fig. 4 Effect of stiffness ratio (k_r) on response ratio, R_e , for various responses for system installed with RSASD ($\Omega_{\theta} = 0.5$)

Comparative performance of PSDs and SAVSDs

To study the comparative performance of passive stiffness damper and semi-active stiffness dampers, various responses are obtained for the system with $T_{\rm y} = 1$ s, $\Omega_{\theta} =$ 1 and $e_x/r = 0.3$ by considering the optimum value of stiffness ratio. The controlled responses are obtained by considering three control strategies namely, passive damper (PSD), switching semi-active stiffness damper (SSASD), and resetting semi-active stiffness damper (RSASD). The time histories of various uncontrolled and controlled responses like torsional displacement (u_{θ}) and lateral displacement at CM (u_v) as well as torsional acceleration (\ddot{u}_{θ}) and lateral acceleration at CM (\ddot{u}_{y}) are obtained under Imperial Valley (1940) earthquake and plotted in Figs. 8 and 9, respectively. It can be observed from the time histories that the reduction in various lateral-torsional responses is significantly higher for the system installed with RSASDs as compared to SSASDs and PSDs. On the contrary, the installation of PSDs increases the accelerations as compared to that of uncontrolled system. This is due to the fact that passive stiffness dampers in the building may increase the stiffness of the building to great extent and hence accelerations are higher. The valve for PSD is always opened or closed and a damper behaves as a bracing. It is further observed that the RSASDs are more effective in reducing torsional displacement and accelerations as compared to their lateral components. It is to be noted that the similar results are obtained under other three earthquakes.

To compare the effectiveness of various control strategies in reducing the peak responses, the ratios, R_e , are obtained for peak values of various displacements and accelerations such as torsional displacement (u_{θ}) , lateral displacement at CM (u_y) , stiff edge displacement (u_{ys}) and stiff edge displacement (u_{yf}) as well as torsional acceleration (\ddot{u}_{θ}) , lateral acceleration at CM (\ddot{u}_y) , stiff edge acceleration (\ddot{u}_{ys}) , and flexible edge acceleration (\ddot{u}_{yf}) . The results are obtained for the system with $T_y = 1$ s, $\Omega_{\theta} = 1$ and $e_x/r = 0.3$ for PSD, SSASD and RSASD under considered earthquakes and shown in Table 2. It is observed from Table 2 that ratios, R_e , for torsional, lateral and edge displacements as well as their acceleration counterparts are more for PSD as compared to SSASD and RSASD implying



Fig. 5 Effect of stiffness ratio (k_r) on response ratio, R_e , for various responses for system installed with RSASD $(\Omega_0 = 1)$

the effectiveness of semi-active systems. It is further observed that R_e for various accelerations responses for system installed with PSD is more than unity indicating that the passive dampers are not effective in reducing the accelerations. Moreover, the bold numbers in parentheses for the cases of SSASD and RSASD indicate the percentage reduction in response ratio, R_e , as compared to passive case. It is noticed that nearly all numbers in bold letters are positive indicating that the higher reduction can be achieved with semi-active devices as compared to passive device. Furthermore, the percentage reduction for RSASD case is more as compared to SSASD. The last column of table represents the average values of percentage reduction. It can be observed from that the percentage reduction in ratio, R_{e} . for RSASD case is significantly higher as compared to that of SSASD and PSD cases. This implies that RSASDs are quite effective in reducing lateral-torsional and edge responses. In addition, the last set of rows of Table 2 shows the normalized peak resultant damper force for each case. It is noticed that the control force developed for RSASD is less than the corresponding force for PSD. Thus, the resetting semi-active stiffness dampers (RSASDs) perform better in reducing lateral, torsional and edge displacement

as well as acceleration responses as compared to switching semi-active stiffness dampers (SSASDs) and passive stiffness dampers (PSDs) for asymmetric building.

Figure 10 shows the typical hysteresis loops for normalized damper force–displacement for dampers located at stiff and flexible edges of the building installed with PSDs, SSASDs and RSASDs for $T_y = 1$ s, $\Omega_{\theta} = 1$ and $e_x/r = 0.3$ under Imperial Valley, 1940 earthquake. It is observed from the hysteresis loops that the semi-active switching and resetting dampers are more effective than passive stiffness dampers. The similar trends are observed for other cases also. Figure 11 shows the time instants of switching and resetting positions of dampers which are located at stiff and flexible edges of the building under Imperial Valley, 1940 earthquake for the period of 10 s for the system with $T_y = 1$ s, $\Omega_{\theta} = 1$ and $e_x/r = 0.3$.

Effects of torsional coupling for system installed with PSDs and SAVSDs

The effects of torsional coupling also play an important role while designing the control system. To study this, the ratio,





Fig. 6 Effect of stiffness ratio (k_r) on response ratio, R_e , for various responses for system installed with RSASD ($\Omega_0 = 2$)



Fig. 7 Effect of parameter, α_L on response ratio, R_e , for various responses

 R_t , (which is between the peak response of controlled asymmetric and corresponding symmetric system) is obtained for lateral and edge displacement as well as acceleration responses for the system with $T_v = 1$ s and $\Omega_{\theta} = 0.5, 1$ and 2 and plotted against e_x/r in Figs. 12, 13 and 14, respectively. The values of eccentricity ratio, e_x/r , are varied from 0 to 1. The first row of Fig. 12a represents the variations obtained with PSDs and the second row represents the variations obtained with RSASDs for torsionally flexible system ($\Omega_{\theta} = 0.5$). It can be observed from that the ratio, R_t , for lateral displacement at CM (u_v) and edge displacements (u_{ys} and u_{yf}) varies significantly with change in e_x/r for the system installed with PSDs as compared to RSASD. Further, from the average trend, it is observed that the ratio, R_t , for stiff edge displacement, u_{vs} , decreases and remains less than unity with increase in e_x r. This indicates that the effectiveness of control system is more for asymmetric system in reducing u_{ys} as compared to the corresponding symmetric system. Thus, the effectiveness will be underestimated by ignoring the effects of eccentricity. On the other hand, the opposite trend is





Fig. 8 Time histories for various displacements for different control strategies under Imperial Valley, 1940 earthquake



Fig. 9 Time histories for various accelerations for different control strategies under Imperial Valley, 1940 earthquake

observed for flexible edge displacement, u_{yf} . Further, a little variation is observed in the values of ratio, R_t , for the response, u_y , corresponding to the change in e_x/r . Moreover, the difference between the responses of edge displacements of asymmetric and corresponding symmetric system increases with increase in superstructure eccentricity.

Furthermore, Fig. 12b represents the variations of ratio, R_t , against e_x/r for lateral and edge acceleration responses.

It can be observed from that the ratio, R_t , for lateral acceleration at CM (\ddot{u}_y) and edge accelerations (\ddot{u}_{ys} and \ddot{u}_{yf}) varies significantly with change in e_x/r for the system installed with PSDs as compared to RSASDs. The values of ratio, R_t , for various responses remain near to the unity for the system installed with RSASDs as compared to the system installed with PSDs. This implies that the effects of torsional coupling ARE higher for the system installed with



Ratio (R_e)	Control Strategy	Imperial Valley (1940)	Loma Prieta (1989)	Northridge (1994)	Kobe (1995)	Average
u _θ	PSD	0.391	0.765	0.206	0.404	
	SSASD	0.259 (33.84 %)	0.271 (64.55 %)	0.168 (18.04 %)	0.271 (32.89 %)	37.33 %
	RSASD	0.080 (79.85 %)	0.084 (89.05 %)	0.057 (72.51 %)	0.101 (75.07 %)	79.07 %
<i>u</i> _y	PSD	0.597	1.238	0.519	0.810	
	SSASD	0.464 (22.26 %)	0.566 (54.34 %)	0.401 (22.88 %)	0.732 (9.65 %)	27.28 %
	RSASD	0.334 (44.17 %)	0.377 (69.53 %)	0.247 (52.52 %)	0.441 (45.58 %)	52.95 %
u_{ys}	PSD	0.588	0.639	0.604	0.482	
	SSASD	0.492 (16.25 %)	0.503 (21.25 %)	0.430 (28.71 %)	0.529 (-9.72 %)	14.12 %
	RSASD	0.352 (40.03 %)	0.291 (54.49 %)	0.294 (51.29 %)	0.343 (28.97 %)	43.70 %
u_{yf}	PSD	0.755	1.325	0.354	0.791	
	SSASD	0.517 (31.53 %)	0.417 (68.50 %)	0.362 (-2.35 %)	0.617 (21.96 %)	29.91 %
	RSASD	0.291 (61.47 %)	0.278 (79.02 %)	0.166 (53.11 %)	0.347 (56.16 %)	62.44 %
\ddot{u}_{θ}	PSD	0.813	1.583	0.472	0.910	
	SSASD	0.545 (32.96 %)	0.666 (57.95 %)	0.498 (-5.48 %)	0.607 (33.24 %)	29.67 %
	RSASD	0.352 (56.71 %)	0.349 (77.96 %)	0.370 (21.63 %)	0.380 (58.25 %)	53.64 %
\ddot{u}_y	PSD	1.187	2.489	1.119	1.525	
	SSASD	0.914 (23.05 %)	1.041 (58.18 %)	0.803 (28.25 %)	1.364 (10.55 %)	30.01 %
	RSASD	0.899 (24.31 %)	0.920 (63.03 %)	0.746 (33.32 %)	1.060 (30.51 %)	37.79 %
\ddot{u}_{ys}	PSD	1.018	1.064	1.040	0.776	
	SSASD	0.866 (14.97 %)	0.933 (12.32 %)	0.750 (27.86 %)	0.907(-16.79 %)	9.59 %
	RSASD	0.780 (23.35 %)	0.588 (44.77 %)	0.665 (36.02 %)	0.769 (0.96 %)	26.27 %
ü _{yf}	PSD	1.830	3.505	0.865	1.874	
	SSASD	1.295 (29.23 %)	1.108 (68.38 %)	0.922 (-6.64 %)	1.478 (21.15 %)	28.03 %
	RSASD	1.049 (42.68 %)	0.867 (75.26 %)	0.663 (23.31 %)	1.044 (44.31 %)	46.39 %
F_{dT}/W	PSD	0.253	1.179	0.784	0.929	
	SSASD	0.188 (25.73 %)	0.442 (62.53 %)	0. 578 (26.35 %)	0.797 (14.19 %)	32.20 %
	RSASD	0.235 (6.84 %)	0.478 (59.42 %)	0.672 (14.30 %)	0.749 (19.38 %)	24.98 %

Table 2 Response ratio, R_e , for peak responses for different control strategies ($T_y = 1$ s, $\Omega_{\theta} = 1$ and $e_x/r = 0.3$)

Numbers in parentheses indicate percentage reduction as compared to the passive (PSD) case. Positive numbers correspond to a reduction in response ratio

PSDs. The similar results and trends are also observed for strongly coupled system ($\Omega_{\theta} = 1$) and torsionally stiff system ($\Omega_{\theta} = 2$) as represented in Figs. 13, 14. It is further observed that the ratio, R_t , for various displacement and acceleration responses varies greatly for the systems with $\Omega_{\theta} = 0.5$ and 1 as compared to system with $\Omega_{\theta} = 2$. Thus, the effects of torsional coupling are higher for torsionally flexible and strongly coupled systems as compared to torsionally stiff systems installed with passive and semi-active stiffness dampers. Thus, the difference between various displacement and acceleration responses of asymmetric and corresponding symmetric system is significantly higher for system installed with PSDs and comparatively very less for the system installed with RSASDs and the difference increases with increase in superstructure eccentricity. Hence, the effects of torsional coupling are very less for the system installed with RSASDs as compared to PSDs.

While designing the control system, the damper capacity is the key issue. Hence, to study the effects of torsional coupling on damper control forces, the variations of response ratio, R_t , for normalized peak damper forces against eccentricity ratio for PSDs and RSASDs under various earthquakes are shown in Fig. 15 for the system with $T_v = 1$ s and $\Omega_{\theta} = 1$. From the figure, in general, it can be observed that the ratio, R_t , for normalized stiff edge damper force (F_{ds}/W) , flexible edge damper force (F_{df}/W) W) and resultant damper force (F_{dT}/W) varies significantly with change in e_x/r for the system installed with PSDs as compared to RSASDs. From the average trends, it can be observed that, the ratio, R_t , for F_{ds} decreases with increase in e_x/r and remains less than unity and for F_{df} , it increases and remains more than unity. Hence, by ignoring the effects of torsional coupling, control forces at stiff edge, F_{ds} , will be overestimated and at flexible edge, F_{df} , it will





Fig. 10 Normalized damper force-displacement loops for dampers located at stiff and flexible edges for different control strategies under Imperial Valley, 1940 earthquake



Fig. 11 Control actions of switching and resetting dampers located at stiff and flexible edges under Imperial Valley, 1940 earthquake

be underestimated as compared to the corresponding symmetric systems. Further, the resultant damper force, F_{Dr} , remains slightly less than unity for the system installed with RSASDs. Hence, resultant damper force will be slightly overestimated by ignoring the asymmetry. Further,

the values of ratio, R_t , for control forces for system installed with RSASDs are close to the unity as compared to system installed with PSDs. Thus, the effects of torsional coupling on damper control forces are less for the asymmetric system installed with resetting semi-active





Fig. 12 Variation of response ratio, R_t for various peak displacements and accelerations against eccentricity ratio for PSD and RSASD under various earthquakes ($\Omega_{\theta} = 0.5$)

stiffness dampers (RSASDs) as compared to system installed with passive stiffness dampers (PSDs). Further, the difference between the control forces of dampers for asymmetric systems as compared to those of corresponding symmetric systems is very less for the systems installed with semi-active dampers, whereas the difference is significant for systems installed with passive dampers.

Conclusions

The seismic response of linearly elastic, single-storey, one-way asymmetric building installed with passive stiffness dampers (PSDs) and semi-active dampers namely, switching semi-active stiffness dampers (SSASDs), and resetting semi-active stiffness dampers (RSASDs), subjected to real earthquake ground motions is



Fig. 13 Variation of response ratio, R_i , for various peak displacements and accelerations against eccentricity ratio for PSD and RSASD under various earthquakes ($\Omega_{\theta} = 1$)

investigated. The lateral-torsional responses are obtained with important system parameters such as eccentricity ratio of superstructure, uncoupled lateral time period, and ratio of uncoupled torsional to lateral frequency. The comparative performance of passive and semi-active control systems is studied. Further, the effects of torsional couplings are also studied for torsionally flexible, strongly coupled, and torsionally stiff systems installed with passive and resetting semi-active stiffness dampers. From the present numerical study, the following conclusions can be drawn:

1. For asymmetric buildings, the torsional, lateral and edge displacements decrease with the increase in stiffness ratio (i.e. ratio between effective damper stiffness to storey stiffness). On the other hand, there





Fig. 14 Variation of response ratio, R_i , for various peak displacements and accelerations against eccentricity ratio for PSD and RSASD under various earthquakes ($\Omega_{\theta} = 2$)

exists an optimum value of stiffness ratio for torsional, lateral and edge accelerations.

- The resetting semi-active stiffness dampers (RSASDs) perform better in reducing lateral, torsional and edge displacement as well as acceleration responses as compared to switching semi-active stiffness dampers (SSASDs) and passive stiffness dampers (PSDs) for asymmetric building.
- 3. The difference between various displacement and acceleration responses of asymmetric and corresponding symmetric system is significantly higher for system installed with PSDs and comparatively very less for the system installed with RSASDs and the difference increases with increase in superstructure eccentricity. Hence, the effects of torsional coupling are very less for the system installed with RSASDs as compared to PSDs.

Fig. 15 Variation of response ratio, R_t , for normalized peak damper forces against eccentricity ratio for PSD and RSASD under various earthquakes



4. The effects of torsional coupling on damper control forces are less for the asymmetric system installed with resetting semi-active stiffness dampers (RSASDs) as compared to system installed with passive stiffness dampers (PSDs). Further, the difference between the control forces of dampers for asymmetric systems as compared to those of corresponding symmetric systems is very less for the systems installed with semi-active dampers, whereas the difference is significant for systems installed with passive dampers.

Open Access This article is distributed under the terms of the Creative Commons Attribution License which permits any use, distribution, and reproduction in any medium, provided the original author(s) and the source are credited.

References

Chi Y, Sain MK, Pham KD, Spencer Jr BF (2000) Structural control paradigms for an asymmetric building. In: Proceedings of the 8th ASCE Specialty Conference on Probabilistic Mechanics and Structural Reliability, PMC2000-152, University of Notre Dame, Notre Dame, Indiana, Jul 2000

- Date VA, Jangid RS (2001) Seismic response of torsionally coupled structures with active control device. J Struct Control 8(1):5–15
- De La Llera JC, Almazan JL, Vial IJ (2005) Torsional balance of plan-asymmetric structures with frictional dampers: analytical results. Earthq Eng Struct Dynam 34(9):1089–1108
- Goel RK (1998) Effects of supplemental viscous damping on seismic response of asymmetric-plan systems. Earthq Eng Struct Dynam 27(2):125–141
- Hart GC, Wong K (2000) Structural dynamics for structural engineers. Wiley, New York
- Hejal R, Chopra AK (1989) Lateral-torsional coupling in earthquake response of frame buildings. J Struct Eng (ASCE) 115(4):852–867
- Jangid RS, Datta TK (1994) Nonlinear response of torsionally coupled base isolated structure. J Struct Eng ASCE 120(1):1–22
- Jangid RS, Datta TK (1997) Performance of multiple tuned mass dampers for torsionally coupled system. Earthq Eng Struct Dynam 26(3):307–317
- Kamagata, S., and Kobori, T. (1994) Autonomous adaptive control of active variable stiffness systems for seismic ground motion. In: Proceedings of 1st world conference on structural control, pp 4–33
- Kobori T, Takahashi M, Nasu T, Niwa N, Ogasawara K (1993) Seismic response controlled structure with active variable stiffness system. Earthq Eng Struct Dynam 22(11):925–941



- Kori JG, Jangid RS (2007) Semi-active Stiffness Dampers for Seismic Control of Structures. Adv Struct Eng 10(5):501–524
- Li HN, Li XL (2009) Experiment and analysis of torsional seismic responses for asymmetric structures with semi-active control by MR dampers. Smart Mater Struct 18(7):075007
- Lin WH, Chopra AK (2003) Asymmetric one-storey elastic systems with non-linear viscous and viscoelastic dampers: simplified analysis and supplemental damping system design. Earthq Eng Struct Dynam 32(4):579–596
- Lu LY (2004) Predictive control of seismic structures with semi-active friction dampers. Earthq Eng Struct Dynam 33(5):647–668
- Matsagar VA, Jangid RS (2005) Base-isolated building with asymmetries due to the isolator Parameters. Adv Struct Eng 8(6):603– 622
- Matsagar VA, Jangid RS (2010) Impact response of torsionally coupled base isolated structure. J Vib Control 16(11):1623–1649
- Mevada SV, Jangid RS (2012a) Seismic response of asymmetric systems with linear and non-linear viscous dampers. Int J Adv Structu Eng 4(5):1–20
- Mevada SV, Jangid RS (2012b) Seismic response of torsionally coupled system with semi-active variable dampers. J Earthq Eng 16(7):1043–1054

- Mevada SV, Jangid RS (2012c) "Seismic response of torsionally coupled system with magnetorheological dampers. Adv Civil Eng 2012(381834):1–26
- Nagarajaiah S, Mate D (1997) Semi-active control of continuously variable stiffness system. In: Proceedings of the Second World Conference on Structural Control, Japan, pp 397-406
- Nasu T, Kobori T, Takahashi M, Niwa N, Ogasawara K (2001) Active variable stiffness system with non-resonant control. Earthq Eng Struct Dynam 30(11):1597–1614
- Petti L, De Iuliis M (2008) Torsional seismic response control of asymmetric-plan systems by using viscous dampers. Eng Struct 30(11):3377–3388
- Shook DA, Roschke PN, Lin PY, Loh CH (2009) Semi-active control of torsionally-responsive structure. Eng Struct 31(1):57–68
- Yang JN, Wu JC, Li Z (1996) Control of seismic-excited buildings using active variable stiffness systems. Eng Struct 18(8):589–596
- Yang JN, Kim JH, Agrawal AK (2000) Resetting semiactive stiffness damper for seismic response control. J Struct Eng(ASCE) 126(12):1427–1433
- Yoshida O, Dyke SJ, Giacosa LM, Truman KZ (2003) Experimental verification of torsional response control of asymmetric buildings using MR dampers. Earthq Eng Struct Dynam 32(13):2085–2105

🖄 Springer