

## Letter to the Editor: Regarding the “Simultaneous Removal of Turbidity and Humic Acid Using Electrocoagulation/Flotation Process in Aqua Solution”

Ghasem Azarian<sup>1</sup> and Ali Reza Rahmani<sup>1,\*</sup>

<sup>1</sup>Department of Environmental Health Engineering, Faculty of Health and Research Center for Health Sciences, Hamadan University of Medical Sciences, Hamadan, IR Iran

\*Corresponding author: Ali Reza Rahmani, Department of Environmental Health Engineering, Faculty of Health and Research Center for Health Sciences, Hamadan University of Medical Sciences, Hamadan, IR Iran. Tel: +98-8118381641, Fax: +98-8118381641, E-mail: rahmani@umsha.ac.ir

Received 2015 April 4; Accepted 2015 May 16.


**Keywords:** Electrochemical treatment, Economic aspects, Energy consumption, Reaction mechanism

### Dear Editor,


We would like to comment on the above paper, which was published in *Avicenna J Environ Health Eng* 2(1) 2015 (1). The study is worthwhile in terms of its application of green methods for removing humic acid (HA) and turbidity. However, we would like to point out some deficiencies in the study design.

The authors have claimed that they have employed an electrocoagulation process for the coagulation and flocculation of the pollutants and air spray through an air pump for floatation; the role of sacrificed anode of aluminum and iron is to produce metal ions and, in turn, coagulant agents  $\text{Fe}(\text{OH})_3$  and  $\text{Al}(\text{OH})_3$ , but, in this study, the authors have not dealt with the role of cathodes because, based on the following reactions, water is reduced and hydrogen gas is created. This plays an important role in floatation. It should be noted that an air spray can only contribute to the electrocoagulation process. The process of electrocoagulation includes a series of reactions, such as coagulation, flocculation and floatation; the authors have not mentioned these reactions, as follows (2):

Equilibrium 1.



Equilibrium 2.



The authors have applied the hybrid process of electrocoagulation/flotation to treat the pollutants and optimized only the variables of electrocoagulation: solution pH, electrical potentials, initial turbidity concentration, and reaction time with or without HA. It is also important to optimize floatation variables such as airflow rate and the size of gas bulbs.

Another point to make here is to question why the authors have optimized the electrical potential. We believe that they should have optimized the current density. It

is thought that current density is entirely important in industrial and economical applications. The use of fixed potential to make sure of oxidation or the reduction of a certain species is clear. Therefore, in order to optimize electrochemical methods, the fixed current phase is used. This enables us to study projects in terms of economic and energy consumption features and scaling up.

In this study, the comparison of theoretical consumption and laboratorial consumption of the electrodes aluminum and iron, as well as energy consumption calculations, have not been tackled, though they are very important (3, 4).

$$W_{\text{theoretical}} = (JtM)/(nF) \quad (1)$$

$$W_{\text{experimental}} = W_{\text{before}} - W_{\text{after}} \quad (2)$$

$$E = (Ut_{\text{EC}}) / V_{\text{EC}} \quad (3)$$

where U was the voltage (V), I was the applied electrolysis current (A),  $t_{\text{EC}}$  was the electrolysis time (h) and  $V_{\text{EC}}$  was the reactor volume ( $\text{m}^3$ ), W is the quantity of anode material dissolved (g of Al and Fe  $\text{cm}^{-2}$ ), J the current density ( $\text{A cm}^{-2}$ ), t the run time (s), M the relative molar mass of aluminum, n the number of electrons in oxidation/reduction reaction ( $n = 3$ ), F the Faraday's constant ( $F = 96.500 \text{ Cmol}^{-1}$ ),  $W_{\text{before}}$  and  $W_{\text{after}}$  are respectively the experimental anode weight before and after electrolysis.

Another problem with the article is that pH variations have not been reported regarding the reactions. However, in most studies on the application of the electrocoagulation measure for treating pollutants in water, the pH

value has been reported to fluctuate, even to two units (5, 6); thus, special buffer solutions should be used for pH optimizations.

## References

1. Seid-Mohammadi A, Sharifi Z, Shabanlo A, Asgari G. Simultaneous Removal of Turbidity and Humic Acid Using Electrocoagulation/Flotation Process in Aqua Solution. *Avicenna Journal of Environmental Health Engineering*. 2015; 2(1). doi:10.17795/ajehe-3310.
2. Rahmani AR, Nematollahi D, Godini K, Azarian G. Continuous thickening of activated sludge by electro-flotation. *Sep Purif Technol*. 2013;107:166-71. doi:10.1016/j.seppur.2013.01.022.
3. Chafi M, Gourich B, Essadki AH, Vial C, Fabregat A. Comparison of electrocoagulation using iron and aluminium electrodes with chemical coagulation for the removal of a highly soluble acid dye. *Desalin*. 2011;281:285-92. doi:10.1016/j.desal.2011.08.004.
4. Khandegar V, Saroha AK. Electrocoagulation for the treatment of textile industry effluent—a review. *J Environ Manage*. 2013;128:949-63. doi:10.1016/j.jenvman.2013.06.043. [PubMed: 23892280]
5. Azarian G, Nematollahi D, Rahmani AR, Godini K, Bazdar M, Zolghadrasab H. Monopolar Electro-Coagulation Process for Azo Dye C.I. Acid Red 18 Removal from Aqueous Solutions. *Avicenna Journal of Environmental Health Engineering*. 2014;1(1):e354. doi:10.17795/ajehe-354.
6. Curteanu S, Piuleac CG, Godini K, Azaryan G. Modeling of electrolysis process in wastewater treatment using different types of neural networks. *Chem Eng J*. 2011;172(1):267-76. doi:10.1016/j.cej.2011.05.104.

Archive of SID