ORIGINAL RESEARCH PAPER

Environmental risk assessment of a dam during construction phase

S. Rezaian¹, S.A. Jozi^{2,*}, N. Zaredar³

¹Department of the Environment, Islamic Azad University, Shahrood Branch, Shahrood, Iran ²Department of the Environment, Islamic Azad University, North Tehran Branch, Tehran, Iran ³Department of Environmental Sciences, Graduate School of the Environment and Energy, Science and Research Branch, Islamic Azad University, Tehran, Iran

Received 1 May 2016; revised 2 July 2016; accepted 20 July 2016; available online 1 September 2016

ABSTRACT: The present study was conducted to assess the possible risks induced by construction of Gavi Dam in Ilam Province; western part of Iran, using MIKE-11 model and technique for order of preference by similarity to ideal solution. For this purpose, vulnerable zone of the dam site against the flooding risk of Gavi River was calculated for different return periods. The flooding zones were stimulated by MIKE-11 model. In order to check whether or not the dam construction could affect the quality of the Gavi River, the physicochemical quality of the river water was also tested. Afterwards, a questionnaire was prepared containing an inventory of possible risks supposed to be induced by construction of Gavi Dam. The questionnaires were placed at disposal of experts to score the items based on their importance. The questionnaires were then analyzed using SPSS Software, version 16. According to which, a total number of 12 risk factors were identified. The dam construction risks were qualitatively assessed by preliminary hazard analysis. Based on the results, 3 of 12 identified risks were recognized unacceptable. The shortlisted risks were prioritized at final step using technique for order of preference by similarity to ideal solution. "Habitat fragmentation" with a weight of 0.3002, "water pollution" with a weight of 0.295, and "impacts on aquatics" with a weight of 0.293 were identified as three top priority flooding risks. Among the most important corrective measures for mitigation of the risks at construction phase can be pointed to "restoration of the land cover", "conservation of areas surrounding the dam as a new wildlife habitat", "prevention of water contamination", and "conservation of fish spawning sites".

KEYWORDS: Construction phase; Gavi Dam; MIKE-11; Preliminary hazard analysis (PHA); Risk; Technique for order of preference by similarity to ideal solution (TOPSIS)

INTRODUCTION

Nowadays, particular methods, techniques, and tools have been presented in order to control, eliminate, or minimize hazards to human health and the surrounding environment. Modern human, instead of dealing with risks in an emergency situation, takes action to identify, measure, prioritize and control their occurrence because he believes that prevention is better

December 1, 2016 on GJESM website at the "Show Article".

than cure. Thus, risk assessment and management is of the great issues of importance in human life. Large projects such as dam building can impose a variety of potential risks to the receiving environment either in construction or operational phases (Samaras *et al.*, 2014; Zhang *et al.*, 2009; Jozi *et al.*, 2015; Jozi and Seyfosadat, 2014). It can cause catastrophic flooding and immense damage at downstream areas (Hooshyaripor and Tahershamsi, 2015, Andrew Charles, 2012, Jozi and Malmir, 2014) and impose external costs

 ^{*}Corresponding Author Email: seyyedali.jozi@gmail.com Tel.: +98 21 4402 2067; Fax: +98 21 4402 2067
 Note: Discussion period for this manuscript open until

to local people (Monavari *et al.*, 2014, Tajziehchi *et al.*, 2012, Tajziehchi *et al.*, 2014, Tajziehchi *et al.*, 2013). Therefore, it is necessary to take steps for preparing against these risks, prior to deal with them (Marche and Robert, 2002; Wolfe *et al.*, 2015). Environmental risk assessment is a step beyond the risk assessment, by which in addition to the study of various aspects of risk, the fragility and particular values of the receiving environment should also be regarded (Heller, 2006; Morales-Torres *et al.*, 2016).

Bocchiola and Rosso in 2014 used generalized extreme value (GEV) distribution to study the return period of large dams in Italy. Xin et al. (2011), by using tailing dam failure probability analysis assessed consequences of dam failing. Goodarzi et al. (2014) investigated the application of risk and uncertainty analysis to assess the overtopping risk of Doroudzan Reservoir in southern Iran. They concluded that both increasing water level and wind speed have a significant impact on the risk of overflowing. Chen et al. (2010) predicted possible ecological risks induced from dam building. They could be able to show how an affected river ecosystem reacts to the artificial perturbation on a whole-ecosystem scale. Danso-Amoako et al. (2012) developed a rapid screening tool to study sustainable flood retention basins for the prediction of corresponding dam failure risks. They concluded that failure risks of dams located near cities are higher than those situated in rural locations. Tosun et al. (2007) discussed the seismic risks of a total number of 32 large dams in Euphrates basin. They revealed that fifteen large dams in the basin should be categorized in the class of high-risk. Haoyao et al. (2012) used Entropy theory and fuzzy matter-element method to establish a comprehensive risk assessment model for earth-rock dams under drought condition. Lee and You (2013) developed a framework for the management of reservoir risks. They found that the capacity of flood control has an influential effect on the induced risk.

The present study was conducted within one year period from 2011 to 2012 to assess the flooding risk of Gavi Dam in Ilam Province western Iran using MIKE- 11 Model and TOPSIS. It also identified and prioritized the most important risks induced by construction of the dam.

MATERIAL AND METHODS

Study area

The Gavi Dam is located in Mehran County in Ilam province in the western part of Iran, near the common borderline with Iraq. As a part of Gavi Basin, the study area is situated within the longitudes of 46° 23′- 46° 22′E and the latitudes of 33° 10′ - 33° 27′N. Table 1 presents the technical specifications of the Gavi Dam.

The Gavi Dam was constructed to supply drinking water to the Mehran County, control and store untimely floods, and to distribute appropriately irrigating water to 4 million ha of the farmlands. Major resources of surface water in the study area include Gavi River, Konjancham River, and Changoule River, with a total annual yield of 390 mcm. The average annual rainfall in the basin is 529 mm. The maximum and minimum temperatures in the dam basin are 52 °C and -27.5 °C. The study area provides habitats for Gavi Dam, small and large mammals, porcupine, birds of prey, saxicolous birds, plain birds, and aquatics. There are situated two villages of Amirabad and Konjancham in the study area (Puyab Consulting Engineers, 2005). Fig. 1 illustrates situation of the study area.

Research methodology

The study area was investigated by field visits to identify the fragile components of the environment in the basin. At first, in order to identify project risks, physicochemical quality of the river water for drinking and agricultural consumptions, as two main sources of water use in the study area, was checked. To evaluate the chemical quality of the river water, microbiological tests were conducted from February 2012 to December 2013 at the two selected stations of Tangbajak and dam site, using titration, reflux, gravimetric, photometry, and atomic absorption of various pollutants. The parameters of total suspended solids (TSS), total dissolved solids (TDS), chemical oxygen demand

Table 1: Technical specifications of Gavi Dam (Puyab Consulting Engineers, 2005)

Dam type	Earth dam with a vertical clay core
Height from foundation (m)	101.5
Crown length(m)	732.7
Crown width(m)	12
Total volume of the reservoir (mcm [*])	47.7

* Million cubic meters

(COD), biochemical oxygen demand (BOD), electrical connectivity (EC), salinity, some selected trace metals, total coliform, and fecal coliform were tested within the years 2012 and 2013. One of the most annoying agents in construction works was noise generation. This, in outdoor areas, such as Gavi Basin, can adversely affect wildlife habitats by scattering animal communities. The annoying sound can also leave a negatively influence generally on the ecological adverse and specifically on the process of egg-laying of birds and reproductive activities of other animals. All of the construction activities may generate annoying noise upper than the standard limits. These operations are "excavation and embankment", "clear-cutting", "harvesting borrow materials", "drilling and foundation", "transpiration", "camp construction", "tunnel construction", "construction of coffer and ostour dams", "operation of crusher machine", "detonation of explosives", "equipment and machinery operation" and "operation of fuel tanks". In order to assess noise level at the dam site, the equivalent sound level meter was measured towards 8 main directions, including north, east, south. west, northwest, northeast, southwest, and southeast. The measurements were done based on the standard method of 1979, 651IEC at a distance of 40m from the equipment by Cell 440 sound level meter, made in UK. According to the instructions presented by Iran

Department of the Environment (DOE, 2007), the equivalent sound level meter was measured at "A weighting network" for 30 min (). Besides, the flooding zone was determined by MIKE-11. Other risk factors were identified using the PHA (Preliminary hazard analysis) questionnaires. The filled out questionnaires were analyzed by SPSS16. The identified risks were then prioritized by TOPSIS as a widely used multi attribute decision making (MADM) method. Fig. 2 presents the research procedure.

MIKE-11 model and risk identification

Dimensions of hydraulic structures of dams are a function of flood discharge. Design flood is the expected discharge with a particular return period used for the design of a structure. For calculation of flooding extent, statistics on the maximum flow of hydrometric stations were required. According to which, the flooding of Gavi River was calculated for different return periods. The flooding zone of Gavi River was specified using MIKE 11 Model. The advanced MIKE-11 software developed by the Danish Hydraulic Institute (DHI) which helps users solving hydraulic issues. The software has been written in Pascal language. Investigation of the issues of flood control, assessment of permanent and non-permanent flows and flood routing are of capabilities of this software. Flood zoning



Fig. 1: Situation of the study area

Risk assessment of a dam



	period (year)		5	10	20	25	50	100	1000	10000
-	Tangebajak station	76.7	138.8	189.2	244.3	263.2	325.8	394.8	676	1052.5
_	Dam site station	75	148	211	282	307	392	489	904	1499
_		7								

by the MIKE-11 is a complex process. Firstly, the river network and the cross sections should be prepared. The river cross section can be taken from the digital elevation model (DEM) of the river. Then, the river flooding zones is prepared by entering the time series of flow data of the stations within the different return periods (Table 2). Fig. 3 is the output of the flood modeling by MIKE-11. After specifying the flooding zone, the risks of Gavi Dam at constructional phase were listed in the form of a questionnaire and placed at the disposal of experts. The experts were asked to score them based on Likert Scale as: (1, 3, 5, 7, and 9) (Table 3). The filled out questionnaires were analyzed by SPSS16 to calculate the mean, mode, and standard deviation of each risk factor.

PHA

The preliminary hazard analysis (PHA) is a systematic safety analysis used to assess the critical and safe areas. The main purpose of this analysis is to achieve significant risk assessment data to help prioritization of risks, allocation of resources and assessment of the compliance the risks. Coding is a common tool in risk assessment studies that is assigned to the intensity and occurrence probability of risks. The intensity and occurrence probability of risks are presented in Tables 4 and 5, respectively. Table 6 also provides the PHA matrix.

TOPSIS

Technique for order of preference by similarity to ideal solution (TOPSIS) is one of the best and widely used MADM models. In this method, a total number of "m" alternatives are evaluated by "n" attributes. The technique is based on the concept that the selected alternative should have the shortest distance from the positive ideal solution (the best possible state) and the maximum distance from the negative ideal solution (the worst possible state). This method includes 6 steps as described in Eqs. 1 to 6:

Step 1: formation of decision matrix: TOPSIS evaluates those decision matrices with "m" alternatives and "n" attributes.

Step 2: normalization of the decision matrix (Eq. 1)

$$n_{ij} = \frac{a_{ij}}{\sqrt{\sum_{i=1}^{m} a_{ij}^2}}$$
(1)

The normalized matrix is called N_D . Step 3: calculation of weighted N_D (Eq. 2)

$$V = N_D \times N_{n \times n} \tag{2}$$

Where, V is the weighted N_D and, W is a diagonal matrix of the weighted attributes.

Step 4: Calculation of the positive ideal and negative ideal alternatives (Eqs. 3 and 4)

Positive ideal alternative =

$$A^{+} = \{ (\max_{i} V_{i} \mid j \in J_{1}) . (\min V_{i} \mid j \in J_{2}) \mid i = 1.2. \dots . n \}$$
(3)

Negative ideal alternative =

$$A^{+} = \{ (\min_{i} V_{i} \mid j \in J_{1}) . (\max_{i} V_{i} \mid j \in J_{2}) \mid i = 1.2....m \}$$
(4)

Step 5: Deviation from the ideal positive and negative alternatives (EqS. 5 and 6):

$$a_{i}^{+} = \{\sum_{1}^{n} (V_{i} - V_{i}^{+})^{2}\}^{1/2}, \quad (i=1,2,...,m)$$
(5)



Fig. 3: Output of the MIKE-11 Model for flood zoning of Gavi Dam

S. Rezaian et al.

Table 4: Risk severity in PHA (Leggett 2012, Rooney et al., 1998)

Comment	Rank	Risk level
Death or severe impact on local ecosystems	1	Catastrophic
Damage to local ecosystems and human communities	2	Critical
Indirect effects on local ecosystems and human communities	3	Intermediate
Negligible effects on local ecosystems and human communities	4	Negligible

Table 5: Occurrence probability of risks in PHA (Wells et al., 1993; Rooney et al., 1998)

Comment	Rank	Frequency
Frequently occurs	А	Frequent
Occurs several times during the lifetime of a system (process)	В	Probable
Occasionally occurs during the lifetime of the system (process)	С	Casual
Occurrence probability is very low during the lifetime of the system (process)	D	Very low
Occurrence probability during the lifetime of the system(process) is so low that it can be assumed zero	Е	Improbable
· · · · · · · · · · · · · · · · · · ·		

Table 6: Risk assessment by PHA (Rooney et al.,

Catastrophic (1)	Critical (2)	Intermediate (3)	Negligible (4)
1A	2A	3A	4A
1B	2B	3B	4B
1C	2C	3C	4C
1D	2D	3D	4D
1E	2E	3E	4E
Unacceptable	Desirable	Accepted with revision of management	Accepted without revision
	Catastrophic (1) 1A 1B 1C 1D 1E Unacceptable	Catastrophic (1)Critical (2)1A2A1B2B1C2C1D2D1E2EUnacceptableDesirable	Catastrophic (1)Critical (2)Intermediate (3)1A2A3A1B2B3B1C2C3C1D2D3D1E2E3EUnacceptableDesirableAccepted with revision of management

Table 7. Chemical quality lest results of Gave River								
Parameters	Stations	Summer 2011	Winter 2011	Spring 2012	Autumn 2012	National standard limit for potable water use (NSI, 1992)	National standard for agricultural use (DOE, 2014)	Unit
BOD	Dam site Tanghajak	99 88	105 98	85 55	87 63	50	100	Mg/L
COD	Dam site	78 70	210 155	65 60	108 98	100	200	Mg/L

-

1500

1000

	- Ch	ennical	quanty	test res	suits	01 (Javi	RIVC
	_							

$$a_i^- = \{\sum_{1}^n (V_i - V_i^-)^2\}^{1/2}, \ (i=1.2.-.m)$$
(6)

Dam site

Tangbajak

Coliform

Step 6: calculation of C_i indicating the closeness to the positive ideal and distance from the negative ideal (Eq. 7):

$$C_i = \frac{\dot{a}_i^-}{(\dot{a}_i^- + \dot{a}_i^+)}, \quad (i=1.2...n)$$
(7)

Ultimately, the alternatives are ranked based on descending order of Ci. The available alternatives can be ranked based on the highest importance (Jozi et al., 2014; Heller, 2006).

RESULT AND DISCUSSION

400

1995

Results of water quality analysis revealed that all water quality parameters are within the standard limits, except for microbial and biological parameters in the station of the dam site. As such, electrical connectivity (EC) of the river was $851.1 \,\mu\text{s/cm}$, at the station of dam site, and 522.8 µs/cm, at Tangbajak Station, which is suitable for agricultural purposes (Ebadati and Houshmandzade, 2014). Table 7 shows the measurements were performed in four seasons of the year; summer (first turn), autumn (second turn), winter

400

NO./ml

(third turn), and spring (fourth turn). Due to the large volume of the chemical quality test results, a few of which are here mentioned. Also, due to limited access to laboratory facilities, coliform was only measured on the final turn in spring. Table 7 indicates the chemical quality test results of Gavi River. Noise pollution at dam site was assessed towards 8 main directions and the obtained results were compared with noise pollution standard limits for industrial-residential areas. According to the results, noise level exceeded the standard limits of 70 dB at the two stations. Table 8 shows the results of noise pollution assessment. The risk identification was done by experts. At this step, a total number of 24 risk factors were identified as presented in Table 9.

Qualitative flood zoning by MIKE-11

Qualitative flood zoning of Gavi River was obtained by MIKE-11. After specifying the flooding zone, the impacts of flooding on the surrounding villages were also investigated (Fig. 4). As Fig. 4 suggests, two villages, namely Amirabad and Konjancham, will be flooded by dam construction. Studies showed that these two villages are non-resident; thereby the flooding hazard will not be a threat to human life.

After determining the flooding zone, the major flooding risks were identified by questionnaires. The questionnaire data were analyzed using SPSS software, version 16. Those risk factors with an average score of 3 or higher were screened. Table 10 presents descriptive statistics of the identified risks induce by construction of Gavi Dam.

Risk analysis by PHA

After risk identification, the PHA was used to determine the risk level of each risk factor. According to which, three risks of "harvesting of borrow materials", "excavation and embankment", and "harmful effects on aquatics" were recognized as unaccepted risks. Furthermore, a total number of 5 risks including "drilling and foundation", "tunnel construction", "operation of crasher machine", "detonation of explosives", and "sedimentation" were evaluated as undesirable risks. Table 11 gives the results of the PHA.

Table 8: Noise assessment at the site of Gavi Dam

		Sampling	Measured	Standard
No.	Stations	duration	value	limit
		(min)	(dB)	(dB)
1	Extreme north side of the dam at the distance of 40 m	30	60.8	70
2	Extreme south side of the dam at the distance of 40 m	30	62.9	70
3	Extreme east side of the dam at the distance of 40 m	30	68.2	70
4	Extreme west side of the dam at the distance of 40 m	30	63.5	70
5	Extreme northwest side of the dam at the distance of 40 m	30	67.3	70
6	Extreme northeast side of the dam at the distance of 40 m	30	61.7	70
7	Extreme southwest side of the dam- at the distance of 40 m	30	66.1	70
8	Extreme southeast side of the dam- at the distance of 40 m	30	69.3	70

	Table 9. Identified fisks at constructional phase of Gavi Dam							
No.	Risk	No.	Risk					
1	Operation of fuel tanks	13	Excavation and embankment					
2	Flood	14	Clear-cutting					
3	Induced earthquake	15	Harvesting of borrow materials					
4	Earthquake	16	Drilling and foundation					
5	Internal erosion of the dam and foundation	17	Transportation					
6	Landscaping	18	Camp construction					
7	Drought	19	Tunnel construction					
8	Incidents while loading and unloading of materials	20	Construction of cofferdams and ostour dams					
9	Migration	21	Operation of crusher machine					
10	Concreting	22	Detonation of explosives					
11	Sedimentation	23	Equipment and machinery operation					
12	Harmful effects on aquatics	24	Generator operation					

Risk assessment of a dam



Table 10: Risks of Gavi Dam at constructional phase							
Operation	Mean	Mode	SD*				
Excavation and embankment	3.6	0	1.560				
Clear-cutting	2.5	0	2.167				
Harvesting borrow materials	4	5	1.264				
Drilling and foundation	3	4	1.549				
Transpiration	2.5	0	2.073				
Camp construction	3.2	0	1.651				
Tunnel construction	3.3	4	1.751				
Construction of cofferdams and ostour dams	3.5	3	0.547				
Operation of crusher machine	3.3	4	1.751				
detonation of explosives	4.8	5	1.834				
equipment and machinery operation	4.1	4	0.408				
Operation of fuel tanks	2.1	4	1.636				
Flood	4.3	5	1.816				
Induced earthquake	2.6	2	1.211				
Earthquake	2.5	3	1.643				
Internal erosion of the dam and foundation	0.8	0	1.329				
Landscaping	1.8	3	1.471				
Drought	2.1	0	1.834				
Incidents of loading and unloading materials	1.1	0	1.329				
Migration	1.6	0	1.861				
Concreting	2	0	1.673				
Sedimentation	3.1	3	0.408				
Generator operation	2.6	3	1.722				
Harmful effects on aquatics	4.3	5	0.816				

Global J. Environ. Sci. Manage., 2(4): 345-356, Autumn 2016

-		5			
Risk factor	Environmental risks	Probability	Intensity	Occurrence probability	Risk level
Harvesting borrow materials	Habitat fragmentation Habitat pollution Changes in aquatic ecosystems Loss of biodiversity Habitat deterioration Loss of land cover Destruction of natural landscape	В	1	1B	
Excavation and embankment	Loss of land cover Destruction of natural landscape Habitat deterioration	В	2	2B	
Drilling and foundation	Habitat fragmentation Habitat pollution Changes in aquatic ecosystems Loss of biodiversity Habitat deterioration Loss of land cover Destruction of natural landscape	В	3	38	
Tunnel construction	Lack of security for wildlife Habitat pollution Wildlife migration Loss of land cover	C	2	2C	
Construction of cofferdams and ostour dams	Habitat fragmentation Habitat pollution Loss of biodiversity Habitat deterioration	В	4	4B	
Operation of crusher machine	Noise pollution Wastewater Wildlife migration	С	2	2C	
Detonation of explosives	Noise pollution Wildlife migration	С	2	2C	
Flood	Loss of biodiversity Habitat deterioration Wildlife migration Going underwater villages near the dam Destruction of natural landscape	В	4	4B	
Construction of workshop and residential camps	Habitat pollution Wildlife migration	D	4	4D	
Operation of equipment and machineries	Habitat pollution Habitat deterioration	В	4	4B	
Sedimentation	Habitat pollution Wildlife migration	В	3	3B	
Harmful effects on aquatics	Decline in the quality of ecosystem Bioaccumulation of heavy metals Wildlife migration	А	1	1A	

Table 11: Ranking of risks by PHA

Prioritization of risks by TOPSIS

The identified risk factors were prioritized by TOPSIS. Out of the 24 risk factors, 9 risks were selected as top priority risks of the dam construction. Among which, "habitat fragmentation" with a score of 0.3002, "water pollution" with a score of 0.295, and "harmful effects on aquatics" with a score of 0.293 were given the first to third priorities, respectively. Moreover, the forth to sixth priorities were assigned respectively to the "loss of biodiversity" with a score of 0.273, "noise pollution" with a score of 0.245, and "air pollution" with a score of 0.239.

CONCLUSION

After identifying the risks of Gavi Dam at construction phase using MIKE-11 and questionnaires, the identified risks were prioritized by TOPSIS. Based on the results, 'habitat fragmentation", "water pollution", and "harmful effects on aquatics" were recognized as three top priority risks of Gavi Dam at construction phase. There are 8 habitats in the construction site of the dam. Large volume of earth works and blasting of explosives could affect the wildlife and cause habitat fragmentation. Borrow materials are harvested from the riverbed and the margins at a distance of 4 km downstream of the dam site. Harvesting is usually done mosaically, and sometimes creates holes in the riverbed. These holes in warm places such as Mehran County can cause blooming of cvanophyta algae and consequently increasing water turbidity and death of aquatics at downstream that threaten aquatic biodiversity. According to the results, the flooding risk of the Gavi Dam is not critical. There are several methods for risk management, one of which is risk mitigation. Risk mitigation reduces the probability of risk occurrence or the intensity of the corresponding consequences. As mentioned earlier, habitat fragmentation is one of the major risks of Gavi Dam that would be mitigated by restoration of land cover, and conservation of areas surrounding the dam lake as a new wildlife habitat. The risks can be reduced somewhat by preventing the discharge of construction materials and debris into the river, siting suitable waste disposal places, and conservation of fish spawning sites. In this regard, it is highly recommended to establish wastewater

treatment systems (preferably septic tanks) near the workshop camps and offices. Some construction operations such as explosion must be done in proper seasons in order to avoid coinciding with the sensitive periods for wildlife. Development of green spaces in the surrounding areas of the dam construction site, particularly around the workshop camps and offices, would be another important mitigation measure.

ACKNOWLEDGEMENT

Authors would like to express their deepest gratitude to the Puyab Consulting Engineers Co. as well as Mr. E. Farhadi, for providing data and all those who have contributed in implementing this research work.

CONFLICT OF INTEREST

The authors declare that there are no conflicts of interest regarding the publication of this manuscript.

REFERENCES

- Andrew Charles, J., (2012). Dam failures: Impact on reservoir safety legislation in Great Britain. Encyclopedia of lakes and reservoirs, Earth sciences series. pp 177-186.
- Bocchiola, D., Rosso, R. (2014). Safety of Italian dams in the face of flood hazard. Adv. Water Resour. 71:23-31 (9 pages).
- Chen, Sh;, Fath, B.D.; Chen, B., (2010). Ecological risk assessment of hydropower dam construction based on ecological network analysis. Procedia Environ. Sci., 2:725-728 (4 pages).
- Danso-Amoako, E.; Scholz, M.; Kalimeris, N.; Yang, Q.; Shao, J., (2012). Predicting dam failure risk for sustainable flood retention basins: A generic case study for the wider Greater Manchester area. Comput. Environ. Urban, 36(5):423-433 (11 pages).
- DOE, (2007). Administrative regulations on how to prevent noise pollution. Approved by Commission on the Infrastructure, Industry and Environmental Affairs. Department of theEnvironment, Tehran, Iran.
- DOE, (2014). Iran water resources quality indicator. Department of the Environment, Tehran, Iran.
- Ebadati, N.; Houshmandzadeh, M., (2014). Analysis of water quality of Dez River in Dezful Hydrometric Station. Ecohydrol., 1(2): 69-81 (13 pages).
- Goodarzi, E.; Teang Shui, L.; Ziaei, M., (2014). Risk and uncertainty analysis for dam overtopping – Case study: The Doroudzan Dam, Iran. J. Hydro Environ. Res., 8(1): 50-61 (12 pages).
- Haoyao, Z.; Jinbao, S.; Xuehui, P.; Dewei, Y., (2012). Earthrock dam risk consequence's comprehensive evaluation

under drought condition. Procedia Earth Planet Sci., 5:237-240 (4 pages).

- Heller, S., (2006). Managing industrial risk-having a tasted and proven system to prevent and assess risk. J. Hazard Mater., 130(1-2):58-63 (6 pages).
- Hooshyaripor, F.; Tahershamsi, A., (2015). Effect of reservoir side slopes on dam-break flood waves. Eng. Appl. Comp. Fluid., 9(1) 458-468 (11 pages).
- Jozi, S.A.; Malmir, M., (2014). Environmental risk assessment of dams by using multi-criteria decision making methods: A case study of the Polrood Dam, Guilan Province, Iran. Hum. Ecol. Risk Assess., 20(1): 69-85 (17 pages).
- Jozi, S.A.; Tabib Shoshtary, M.; Khayat Zadeh, A.R., (2015). Environmental risk assessment of dams in construction phase using a multi-criteria decision making (MCDM) method. Hum. Ecol. Risk Assess., 21(1), 1-16 (16 pages).
- Jozi, S.A.; Saffarian, Sh.; Shafiee, M.; Moradi Majd, N., (2014). Safety, health, and environmental risk assessment of a gas power plant: A case study from southern Iran. Hum. Ecol. Risk Assess., 21(6):1479-1495 (17 pages).
- Jozi, S.A.; Seyfosadat, S.H., (2014). Environmental risk assessment of Gotvand-Olia dam at operational phase using the integrated method of environmental failure mode and effects analysis (EFMEA) and preliminary hazard analysis. J. Environ. Stud., 40(1), 25-27 (3 pages).
- Leggett, D.J., (2012). Lab-HIRA: Hazard identification and risk analysis for the chemical research laboratory: Part 1. Preliminary hazard evaluation. J. Chem. Health Saf., 19(5):9-24 (16 pages).
- Lee, B. Sh.; You, G.J.Y., (2013). An assessment of long-term overtopping risk and optimal termination time of dam under climate change. J. Environ. Manage., 121:57-71 (15 pages).
- Marche, C.; Robert, B., (2002). Dam failure risk: Its definition and impact on safety assessment of dam structures. J. Decis. Syst., 11(3-4), 513-534 (22 pages).
- Monavari, S.M.; Tajziehchi, S.; Karbassi, A.; Shariat, S.M., (2014). Development of new model for computation of external costs of hydropower dams. OIDA Int. J. Sust. Dev., 7(4) 109-120 (12 pages).
- Morales-Torres, A.; Serrano-Lombillo, A.; Escuder-Bueno, I.; Altarejos-García, L., (2016). The suitability of risk reduction indicators to inform dam safety management. Structure and infrastructure engineering: Maintenance, management, life cycle design and performance, DOI: 10.1080/15732479.2015.1136830.

- NSI, (1992). Drinking water-physical and chemical specifications. Institute of Standards and Industrial Research of Iran, Standard 1053, Tehran, Iran.
- Puyab Consulting Engineers, (2005). Reported environmental studies cow Ilam Dam. Terhan, Iran.
- Rooney, J.J.; Turner, J.H.; Arendt, J.S., (1988). A preliminary hazards analysis of a fluid catalytic cracking unit complex. J. Loss Prevent. Proc., 1(2): 96-103 (8 pages).
- Salati, P.; Jozi, S.A., (2012). Environmental risk assessment of low density polyethylene unit using the method of failure mode and effect analysis. Chem. Ind. Chem. Eng. Q., 18(1):103-113 (11 pages).
- Samaras, G.D.; Gkanas, N.I.; Vitsa, K.C., (2014). Assessing risk in dam projects using AHP and ELECTRE I. Int. J. Constr. Manage. 14(4), 255-266 (12 pages).
- Tajziehchi, S.; Monavari, S.M.; Karbassi, A., (2012). An effective participatory-based method for dam social impact assessment. Pol. J. Environ. Stud., 21(6), 329-33 (5 pages).
- Tajziehchi, S.; Monavari, S.M.; Karbassi, A.R.; Shariat, S.M.; Khorasani, N., (2013). Quantification of social impacts of large hydropower dams: A case study of Alborz Dam in Mazandaran Province, Northern Iran. Int. J. Environ. Res., 7(2), 377-382 (6 pages).
- Tajziehchi, S.; Monavari, S.M.; Karbassi, A.R.; Shariat, S.M.; Khorasani, N.; Narimisa, P., (2014). A critical look at social impact evaluation of dam construction by revised SIMPACTS software: Aa case study of Alborz Dam in Northern Iran. Int. J. Environ. Res., 8(2): 329-334 (6 pages).
- Tosun, H.; Zorluer, Ý.; Orhan, A.; Seyrek, E.; Sava^o, H.; Türköz, M., (2007). Seismic hazard and total risk analyses for large dams in Euphrates basin. Turkey Eng. Geol., 89(1–2):155-170 (16 pages).
- Wells, G.; Wardman, M.; Whetton, C., (1993). Preliminary safety analysis. J. Loss, Prevent, Proc., 6(1):47-60 (14 pages).
- Wolfe, D.; Schorr, M.; Hanson, M.; Nelson, C.H.; Richards, S.M.,(2015). Hazard assessment for a pharmaceutical mixture detected in the upper Tennessee River using Daphnia magna. Global J. Environ. Sci. Manage., 1 (1): 1-14 (14 pages).
- Xin, Zh.; Xiaohu, X.; Kaili, X., (2011). Study on the risk assessment of the tailings dam break. Procedia Eng., 26: 2261-2269 (9 pages).
- Zhang, L.M.; Xu, Y.; Jia, J.S., (2009). Analysis of earth dam failures: A database approach. Special issue: Assessment and management of risk for engineered systems and geo-hazards, Georisk, 3(3), 184-189 (6 pages).

AUTHOR (S) BIOSKETCHES

Rezaian, S., Ph.D., Assistant Professor, Department of the Environment, Islamic Azad University, Shahrood Branch, Shahrood, Iran. Email: s_rezaian@ymail.com

Jozi, S.A., Ph.D., Associate Professor, Department of the Environment, Islamic Azad University, North Tehran Branch, Tehran, Iran. Email: seyyedali.jozi@gmail.com

Zaredar, N., Ph.D. Candidate, Department of Environmental Sciences, Graduate School of the Environment and Energy, Science and Research Branch, Islamic Azad University, Tehran, Iran. Email: *narges_zaredar@yahoo.com*

COPYRIGHTS

Copyright for this article is retained by the author(s), with publication rights granted to the journal. This is an open-access article distributed under the terms and conditions of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0/).

HOW TO CITE THIS ARTICLE

Rezaian, S.; Jozi, S.A.; Zaredar, N., (2016). Environmental risk assessment of a dam during construction phase. Global J. Environ. Sci. Manage., 2(4): 345-356.

DOI: 10.22034/gjesm.2016.02.04.004

URL: http://gjesm.net/article_20481.html

