



## A Blind Hammerstein Diversity Combining Technique for Flat Fading Channels

A. M. Aminian-Modarres\*<sup>a</sup>, M. Molavi-kakhki<sup>b</sup>

<sup>a</sup> Department of Electrical Engineering, Sadjad Institute of Higher Education, Mashhad, Iran

<sup>b</sup> Department of Electrical Engineering, Ferdowsi University of Mashhad, Mashhad, Iran

### PAPER INFO

#### Paper history:

Received 22 February 2012

Received in revised form 16 May 2012

Accepted 18 October 2012

#### Keywords:

Nonlinear Signal Processing  
Nonlinear Diversity Combining  
Hammerstein Filter  
Rayleigh Flat Fading Channel

### ABSTRACT

Diversity combining techniques play an important role in combating the destructive effects of channel fading in wireless communication systems. In this work, we present a blind diversity combining technique for Rayleigh flat fading channels based on Hammerstein type filters. We show that the performance of this technique is very close to ideal MRC system which is accepted as an optimum receiver over fading channels in presence of AWGN. This is a valuable result especially because higher bandwidth efficiency is also achieved as compared with MRC. We also show that in our proposed technique the variation of the combiner output values around the values of transmitted symbols is less than the corresponding variation in MRC system. Hence, for soft decision applications it is superior to MRC technique.

doi: 10.5829/idosi.ije.2013.26.03c.07

## 1. INTRODUCTION

The most destructive characteristic of a wireless channel is the random variation of its transfer function, known as fading phenomenon. Diversity combining is a well-known technique for combating this effect. Space, frequency, time and coding diversities, as well as combination of two or more of these, are employed in different systems. Various combining techniques have been suggested for multiple received signals [1, 2]. In presence of additive white Gaussian noise, maximal ratio combining (MRC) is a theoretically optimal combiner over fading channels in which the received signals from different paths are combined so as to maximize the instantaneous SNR at the combiner output [1]. Performance analysis of MRC system has been the subject of interest in many research works [3-21]. In ideal MRC scheme, it is assumed that the channel coefficients are known at the receiver. However, in practice, these coefficients have to be estimated using a training sequence. Hence, the performance of non-ideal MRC is affected considerably by the estimation error [10-12].

By R Annavajjala et al. [13, 14] an analytical relation

for average bit error rate has been derived for non-ideal MRC with BPSK modulation and independent Rayleigh channels. The performance of non-ideal MRC for independent Rayleigh, Rician and Nakagami channels has been analyzed and compared by W. M. Gifford et al. [15]. W. M. Gifford et al. [16] the previous work [15] has been extended to correlated channels. Non-ideal MRC with correlated Rayleigh channels in presence of colored noise is investigated by L. Schmitt, et al. [17]. Independent and non-identical distributed Rayleigh channels have been discussed by Y. C. Ko, and T. Luo, [18]. On the other hand, modified MRC receivers with improved performances have been proposed in vary articles [19-21] by employing practical channel estimations on fading channels. In these works, the receiver structures are linear and a training sequence is employed, which in turn decreases the bandwidth efficiency.

In present work, we offer a blind nonlinear diversity combining technique for Rayleigh flat fading channels. In our proposed combining technique, instead of estimating the channel coefficients, we directly estimate the transmitted symbols and show that the optimum estimator is a nonlinear polynomial system, which can be realized by a Hammerstein filter. We show that the performance of this blind combining technique is very close to ideal MRC. This is a valuable result, especially

\*Corresponding Author Email: [Aminian.mod@gmail.com](mailto:Aminian.mod@gmail.com) (A. M. Aminian-Modarres)

because higher bandwidth efficiency is also achieved. We also show that in our proposed technique, variation of the combiner output values around the values of transmitted symbols is less than the corresponding variation in MRC system. Hence, the proposed system is potentially superior to MRC for soft decision purposes.

Hammerstein filter is a nonlinear polynomial filter used in many applications such as system identification [22-24], modeling [25] echo cancellation [27, 28], and noise cancellation [29]. In one of our previous works [30], we have proposed a new nonlinear equalization technique (GHE) for frequency selective fading channels, based on Hammerstein filters.

Also, in other works [31, 32], we have presented a new Hammerstein diversity combining technique (HDC) for frequency selective fading channels. In these systems, training symbols are used for calculation of optimized filter coefficients.

This paper is organized as follows: In section 2, we present the system model. Section 3 introduces our nonlinear blind Hammerstein diversity combining technique. Theoretical basis of our proposed system is presented in section 4. In section 5 a proper cost function is introduced for obtaining the optimized filter coefficients in a blind manner. Section 6 provides the simulation results and discussions, before concluding the paper in section 7.

## 2. SYSTEM MODEL

The equivalent low-pass discrete time model of the system is illustrated in Figure 1. In this work, we employ BPSK modulation. The transmitted sequence  $x(n) \in \{+1, -1\}$  is drawn from an i.i.d. source with equiprobable symbols. The communication system consists of  $M$  diversity branches. These branches are assumed to be identical Rayleigh flat fading channels.

Hence, the SIMO channel can be presented by an  $M \times 1$  vector, as:

$$\mathbf{H} = [h_1 \ h_2 \ \dots \ h_M]^T \quad (1)$$

where  $h_i$  is the complex Rayleigh distributed random gain of the  $i$ th channel as:

$$h_i = h_{Ii} + j h_{Qi} \quad (2)$$

$h_{Ii}$  and  $h_{Qi}$  are the real and the imaginary component of the channel gain respectively. These two components are independent, zero mean, Gaussian random variables with variance  $\sigma_{hi}^2 = 1$ . Furthermore, the branches are assumed uncorrelated, i.e. :

$$E\{h_i, h_j^*\} = 0 \quad \text{for } i \neq j \quad (3)$$

The channel fading is assumed sufficiently slow, such that the channel gains do not vary during one data frame. The received signal from the  $i$ th channel is given by:

$$y_i(n) = h_i x(n) + w_i(n) \quad i = 1, 2, \dots, M \quad (4)$$

where  $w_i(n)$  is the complex additive white Gaussian noise at the  $i$ th receiver branch written as:

$$w_i(n) = w_{Ii}(n) + j w_{Qi}(n) \quad (5)$$

$w_{Ii}(n)$  and  $w_{Qi}(n)$  are uncorrelated, zero mean, Gaussian random variables with variance  $\sigma_w^2$ . Equation (4) can be expressed in matrix form:

$$\mathbf{Y}(n) = \mathbf{H} x(n) + \mathbf{W}(n) \quad (6)$$

where  $\mathbf{H}$  is the channel vector and  $\mathbf{Y}(n)$  and  $\mathbf{W}(n)$  are the received data vector and the noise vector, respectively. These vectors are defined as:

$$\mathbf{Y}(n) = [y_1(n) \ \dots \ y_M(n)]^T \quad (7)$$

$$\mathbf{W}(n) = [w_1(n) \ \dots \ w_M(n)]^T \quad (8)$$




Figure 1. System model

As shown in Figure 1, the receiver consists of two correlators banks, namely, inphase and quadrature correlators. The complex received signal  $y_i(n)$  from each branch is applied to both correlators. The outputs of the inphase and quadrature correlators are the real part ( $y_{Ii}(n)$ ) and the imaginary part ( $y_{Qi}(n)$ ) of  $y_i(n)$  respectively. According to Equations (2) and Equation (5), we can write:

$$\begin{aligned} y_{Ii}(n) &= h_{Ii} x(n) + w_{Ii}(n) \quad i=1,2,\dots,M \\ y_{Qi}(n) &= h_{Qi} x(n) + w_{Qi}(n) \end{aligned} \quad (9)$$

We define the  $2M \times 1$  real vector  $\tilde{\mathbf{Y}}(n)$  as:

$$\begin{aligned} \tilde{\mathbf{Y}}(n) &= [\tilde{y}_1(n) \ \tilde{y}_2(n) \ \dots \ \tilde{y}_{2M}(n)]^T \\ &= [y_{I1}(n) \ \dots \ y_{IM}(n) \ y_{Q1}(n) \ \dots \ y_{QM}(n)]^T \end{aligned} \quad (10)$$

where:

$$\tilde{y}_i(n) = \begin{cases} y_{Ii}(n) & 1 \leq i \leq M \\ y_{Q(i-M)}(n) & M+1 \leq i \leq 2M \end{cases} \quad (11)$$

As shown in Figure 1,  $\tilde{\mathbf{Y}}(n)$  is the input to the diversity combining filters. This model is very convenient for computational purposes, as we deal with real values only. It is in fact similar to having  $2M$  real fading diversity branches modeled as Gaussian random variables.

The output of the combiner,  $z(n)$ , is applied to a hard detector for making the output decision  $\hat{x}(n)$ .

### 3. BLIND HAMMERSTEIN DIVERSITY COMBINING TECHNIQUE

A Blind Hammerstein Diversity Combining (BHDC) system is shown in Figure 2. In this approach, a Hammerstein filter of order  $D$  is employed for each diversity branch. The output polynomial of the  $i$ th filter is:

$$z_i(n) = \sum_{k=1(k \text{ odd})}^D g_{ik} \tilde{y}_i^k(n) \quad i=1,2,\dots,2M \quad (12)$$

where  $g_{ik}$  is the  $k$ th coefficient of the output polynomial of the  $i$ th filter and  $\tilde{y}_i(n)$  is defined by Equation (11). Note that only the odd powers appear in the summation of Equation (12). Similar to our previous works, [30] and [31], it can be proved that the terms corresponding to the even powers are equal to zero.

The outputs of the filters are summed to produce the combiner output  $z(n)$ , i.e. :

$$z(n) = \sum_{i=1}^{2M} \sum_{k=1(k \text{ odd})}^D g_{ik} \tilde{y}_i^k(n) \quad (13)$$

Equation (13) can be expressed in matrix form:

$$z(n) = \mathbf{G}_H^T \mathbf{Y}_H(n) \quad (14)$$

where  $\mathbf{G}_H$  is an  $M(D+1) \times 1$  vector given by:

$$\mathbf{G}_H(n) = [g_{11} \ g_{21} \ \dots \ g_{(2M)1} \ g_{13} \ g_{23} \ \dots \ g_{(2M)D}]^T, \quad D \text{ odd} \quad (15)$$

and  $\mathbf{Y}_H(n)$  is an  $M(D+1) \times 1$  vector defined as:

$$\mathbf{Y}_H(n) = [\tilde{\mathbf{Y}}_1^T(n) \ \tilde{\mathbf{Y}}_3^T(n) \ \tilde{\mathbf{Y}}_5^T(n) \ \dots \ \tilde{\mathbf{Y}}_D^T(n)]^T, \quad D \text{ odd} \quad (16)$$

where  $\tilde{\mathbf{Y}}_p(n)$  is defined as the  $p$ th power of  $\tilde{\mathbf{Y}}(n)$ :

$$\tilde{\mathbf{Y}}_p(n) = [\tilde{y}_1^p(n) \ \tilde{y}_2^p(n) \ \dots \ \tilde{y}_{2M}^p(n)]^T \quad (17)$$

In fact, as shown in Figure 3, a Hammerstein combiner can be modeled as a nonlinear subsystem for generating  $\mathbf{Y}_H(n)$  followed by a linear subsystem defined by the vector  $\mathbf{G}_H$ .

Our goal is to find  $\mathbf{G}_H$  such that the combiner output  $z(n)$  is an optimum estimate of the transmitted symbol. In section 5, we present a proper cost function for obtaining the optimum filter coefficients.




Figure 2. Blind Hammerstein Diversity Combining Technique (BHDC)

#### 4. THEORETICAL BASIS

In this section, we explain our motivation for using Hammerstein filters in the proposed system. For simplicity, we first consider a system with  $M=1$ . In this case, at any specific time  $n$ , the observed signals at the receiver are:

$$\begin{cases} \tilde{y}_1(n) = h_{t1} x(n) + w_{t1}(n) \\ \tilde{y}_2(n) = h_{Q1} x(n) + w_{Q1}(n) \end{cases} \quad (18)$$

Based on the observed data, we would like to estimate the transmitted symbol  $x(n)$ . Using MMSE criterion, the optimum Bayesian estimator  $z(n)$  is defined as below [33]:

$$z = E\{x | \tilde{y}_1, \tilde{y}_2\} = \int_{-\infty}^{+\infty} x p(x | \tilde{y}_1, \tilde{y}_2) dx \quad (19)$$

where the notation  $p(\cdot)$  denotes the probability density function (PDF), and the time index is omitted for notation simplicity. The conditional PDF can be written as:

$$p(x | \tilde{y}_1, \tilde{y}_2) = \frac{p(\tilde{y}_1, \tilde{y}_2 | x) p(x)}{\int_{-\infty}^{+\infty} p(\tilde{y}_1, \tilde{y}_2 | x) p(x) dx} \quad (20)$$

The noise components in Equation (18) are uncorrelated zero mean Gaussian random variables. Hence, for a particular channel occurrence, the joint conditional PDF of the observed data  $\{\tilde{y}_1, \tilde{y}_2\}$ , conditioned on the transmitted sequence becomes:

$$\begin{aligned} p(\tilde{y}_1, \tilde{y}_2 | x) &= p(\tilde{y}_1 | x) p(\tilde{y}_2 | x) \\ &= \frac{1}{(2\pi\sigma_w^2)} \exp\left\{-\frac{(\tilde{y}_1 - h_{t1}x)^2}{2\sigma_w^2} - \frac{(\tilde{y}_2 - h_{Q1}x)^2}{2\sigma_w^2}\right\} \end{aligned} \quad (21)$$

Also, based on our assumptions, we have:

$$p(x) = \frac{1}{2} [\delta(x+1) + \delta(x-1)] \quad (22)$$

Finally, by substituting Equations (20)-(22) in Equation (19), the MMSE estimator can be obtained as:

$$z = \tanh[2(h_{t1}\tilde{y}_1 + h_{Q1}\tilde{y}_2)] \quad (23)$$

Now, we generalize this result for any arbitrary value of  $M$  as below:

$$z(n) = \tanh\left[2 \sum_{i=1}^{2M} \tilde{h}_i \tilde{y}_i(n)\right] \quad (24)$$

where:

$$\tilde{h}_i = \begin{cases} h_{ti} & 1 \leq i \leq M \\ h_{Q(i-M)} & M+1 \leq i \leq 2M \end{cases} \quad (25)$$

The Maclaurin expansion of Equation (24) yields:

$$\begin{aligned} z(n) &= \left[2 \sum_{i=1}^{2M} \tilde{h}_i \tilde{y}_i(n)\right] - \frac{1}{3} \left[2 \sum_{i=1}^{2M} \tilde{h}_i \tilde{y}_i(n)\right]^3 \\ &\quad + \frac{2}{15} \left[2 \sum_{i=1}^{2M} \tilde{h}_i \tilde{y}_i(n)\right]^5 - \dots \end{aligned} \quad (26)$$




Figure 3. Hammerstein combiner

We can write this equation as  $z(n) = S_1(n) + S_2(n)$ , where:

$$\begin{cases} S_1(n) = \sum_{i=1}^{2M} \sum_{k=1}^{\infty} C_{ik} \tilde{y}_i^k(n) \\ S_2(n) = \text{Other Terms} \end{cases} \quad (27)$$

Here, the coefficients  $C_{ik}$  are known parameters that can be obtained from Equation (26). As can be seen,  $S_1(n)$  is similar to Equation (13) which is the output of a BHDC system. Furthermore,  $S_1(n)$  is a subset of the optimum estimator  $z(n)$ . From the above discussion, we conclude that a BHDC system can be considered as a subset of the optimum estimator for the transmitted symbols.

#### 5. CALCULATION OF THE OPTIMUM COEFFICIENTS

**5.1. Cost Function** Since in blind systems no training sequence exists, an exact value of error signal is not available. Hence, instead of MMSE criteria we present a more convenient cost function for our optimization problem. To obtain a closed form for our cost function, we first recall that a system with  $M$  complex Rayleigh channels can be modeled by a system with  $2M$  real Gaussian channels. Hence, to simplify our notations, in this section we assume real values for the channel and the noise vectors, without any loss of generality. Having made this assumption, Equation (16) becomes:

$$\mathbf{Y}_H(n) = [y_1(n) \dots y_M(n) \ y_1^3(n) \dots y_M^3(n) \dots y_1^p(n) \dots y_M^p(n)]^T \quad (28)$$

Each element of this vector can be divided into two terms as below:

$$\begin{aligned} y_i^k(n) &= (h_i x(n) + w_i(n))^k = \sum_{j=0}^k \binom{k}{j} (h_i x(n))^j (w_i(n))^{k-j} = \\ &h_i^k x^k(n) + \sum_{j=0}^{k-1} \binom{k}{j} (h_i x(n))^j (w_i(n))^{k-j} = s_{ik}(n) + n_{ik}(n) \end{aligned} \quad (29)$$

where  $s_{ik}(n)$  and  $n_{ik}(n)$  are the noise-free (signal) term and the noisy term respectively.

From Equations (28) and (29) we have:

$$\begin{aligned} \mathbf{Y}_H(n) &= [y_1(n) \dots y_M(n) \dots y_M^p(n)]^T \\ &= [s_{11}(n) \dots s_{M1}(n) \dots s_{MD}(n)]^T \\ &\quad + [n_{11}(n) \dots n_{M1}(n) \dots n_{MD}(n)]^T = \mathbf{SIG}(n) + \mathbf{NOI}(n) \end{aligned} \quad (30)$$

where as shown in Figure 3,  $\mathbf{SIG}(n)$  and  $\mathbf{NOI}(n)$  are the signal vector and the noise vector at the output of the nonlinear subsystem of the Hammerstein combiner, respectively. The combiner output can then be written as:

$$z(n) = \mathbf{G}_H^T \mathbf{Y}_H(n) = \mathbf{G}_H^T (\mathbf{SIG}(n) + \mathbf{NOI}(n)) \quad (31)$$

$$= \underbrace{\mathbf{G}_H^T \mathbf{SIG}(n)}_{\text{Output signal term}} + \underbrace{\mathbf{G}_H^T \mathbf{NOI}(n)}_{\text{Output noise term}} = z_S(n) + z_N(n)$$

where  $z_S(n)$  and  $z_N(n)$  are the signal part and the noise part of the combiner output respectively.

Now, we define our proposed cost function as below:

$$J = \frac{P_S}{P_N} \quad (32)$$

where  $P_S$  and  $P_N$  are the average powers of  $z_S(n)$  and  $z_N(n)$  respectively, given by:

$$P_S = E\{z_S^2\} = E\{(\mathbf{G}_H^T \mathbf{SIG}(n))(\mathbf{SIG}^T(n) \mathbf{G}_H)\} \quad (33)$$

$$P_N = E\{z_N^2\} = E\{(\mathbf{G}_H^T \mathbf{NOI}(n))(\mathbf{NOI}^T(n) \mathbf{G}_H)\} \quad (34)$$

Hence, we can write:

$$J = \frac{P_S}{P_N} = \frac{\mathbf{G}_H^T \mathbf{R}_S \mathbf{G}_H}{\mathbf{G}_H^T \mathbf{R}_N \mathbf{G}_H} \quad (35)$$

where  $\mathbf{R}_S$  and  $\mathbf{R}_N$  are the autocorrelation matrices of  $\mathbf{SIG}(n)$  and  $\mathbf{NOI}(n)$  respectively:

$$\mathbf{R}_S = E\{\mathbf{SIG}(n) \mathbf{SIG}^T(n)\} \quad (36)$$

$$\mathbf{R}_N = E\{\mathbf{NOI}(n) \mathbf{NOI}^T(n)\} \quad (37)$$

Our goal is to achieve an estimate for the transmitted symbol using the noise free part of the combiner output. On the other hand since the transmitter employs BPSK signaling,  $P_S$  must be equal to one in absence of AWGN and the fading effect. Hence, we maximize the cost function  $J$  in Equation (32) with the constraint  $P_S = 1$ . This constrained optimization problem will be solve in subsection 5-3.

## 5. 2. Blind Estimation of the Autocorrelation Matrices

To find the cost function  $J$  in Equation (32), we first need to calculate the autocorrelation matrices  $\mathbf{R}_S$  and  $\mathbf{R}_N$ . An insight into Equations (29) and (30) reveals that while the elements of  $\mathbf{Y}_H(n)$  are observable at the receiver, the elements of  $\mathbf{SIG}(n)$  and  $\mathbf{NOI}(n)$  are not directly available. Hence,  $\mathbf{R}_S$  and  $\mathbf{R}_N$  have to be estimated from the observable information, using an indirect method.

In this blind method, as the first step, we obtain the closed forms of  $\mathbf{R}_S$  and  $\mathbf{R}_N$ . To explain our method, without loss of generality, we calculate these autocorrelation matrices for the special case where  $M=2$  and  $D=3$ . Using the equations and the

assumptions mentioned before, in this case we obtain:

$$\mathbf{R}_S = \begin{bmatrix} h_1^2 & h_1 h_2 & h_1^4 & h_1 h_2^3 \\ h_1 h_2 & h_2^2 & h_1^3 h_2 & h_2^4 \\ h_1^4 & h_1^3 h_2 & h_1^6 & h_1^3 h_2^3 \\ h_1 h_2^3 & h_2^4 & h_1^3 h_2^3 & h_2^6 \end{bmatrix} \quad (38)$$

and:

$$\mathbf{R}_N = \begin{bmatrix} \sigma_w^2 & 0 & 3h_1^2 \sigma_w^2 + 3\sigma_w^4 & 0 \\ 0 & \sigma_w^2 & 0 & 3h_2^2 \sigma_w^2 + 3\sigma_w^4 \\ 3h_1^4 \sigma_w^2 + 3\sigma_w^4 & 0 & 9h_1^4 \sigma_w^2 + 60h_1^2 \sigma_w^6 & 9h_1 h_2 \sigma_w^4 \\ 0 & 3h_2^2 \sigma_w^2 + 3\sigma_w^4 & 9h_1 h_2 \sigma_w^4 & 9h_2^4 \sigma_w^2 + 60h_2^2 \sigma_w^6 \end{bmatrix} \quad (39)$$

As can be seen, the elements  $\mathbf{R}_S$  and  $\mathbf{R}_N$  are functions of channel taps and noise moments. To estimate these parameters, we first calculate the following statistical averages:

$$\alpha = E\{y_1^2(n)\} = h_1^2 + \sigma_w^2 \quad (40)$$

$$\beta = E\{y_2^2(n)\} = h_2^2 + \sigma_w^2 \quad (41)$$

$$\gamma = E\{y_1(n) y_2(n)\} = h_1 h_2 \quad (42)$$

Using the above equations, we can write:

$$\theta = h_1^2 = \frac{(\alpha - \beta) + \sqrt{(\alpha - \beta)^2 + 4\gamma^2}}{2} \quad (43)$$

$$\eta = h_2^2 = \frac{\gamma^2}{\theta} \quad (44)$$

$$\zeta = \sigma_w^2 = |\alpha - \theta| \quad (45)$$

Since the signals  $y_1(n)$  and  $y_2(n)$  are observable at the receiver, it is possible to estimate the parameters at the left hand side of Equations (40)-(45). The estimated values are:

$$\hat{\alpha} = \frac{1}{N_r} \sum_{n=1}^{N_r} y_1^2(n) \quad (46)$$

$$\hat{\beta} = \frac{1}{N_r} \sum_{n=1}^{N_r} y_2^2(n) \quad (47)$$

$$\hat{\gamma} = \frac{1}{N_r} \sum_{n=1}^{N_r} y_1(n) y_2(n) \quad (48)$$

$$\hat{\theta} = \frac{(\hat{\alpha} - \hat{\beta}) + \sqrt{(\hat{\alpha} - \hat{\beta})^2 + 4\hat{\gamma}^2}}{2} \quad (49)$$

$$\hat{\eta} = \frac{\hat{\gamma}^2}{\hat{\theta}} \quad (50)$$

$$\hat{\zeta} = |\hat{\alpha} - \hat{\theta}| \quad (51)$$

where  $N_r$  is the number of received symbols. Having calculated these parameters, the estimated values of  $\mathbf{R}_S$  and  $\mathbf{R}_N$  can be obtained from Equations (38) and (39). Note that in our technique, there is not any training sequence and  $N_r$  received symbols used for the estimations are parts of information data. Hence, BHDC is a completely blind method. It is worth saying

that the proposed technique can easily be applied to any modulation scheme and any arbitrary value of  $M$  and  $D$ .

**5. 3. Optimization** As mentioned before, in BHDC technique the filter coefficients are calculated such that the cost function  $J$  in Equation (32) is maximized with the constraint  $P_s=1$ . Hence, we are encountered with a constrained optimization problem, which depending on the rank of matrix  $\mathbf{R}_s$ , has two different solutions as follows:

**5. 3. 1. Case 1**  $\mathbf{R}_s$  has a full rank. In this case we have  $r=t$ , where  $r$  and  $t=M(D+1)$  are the rank and the dimension of  $\mathbf{R}_s$  respectively. We can write the singular value decomposition (SVD) of the positive definite matrix  $\mathbf{R}_s$  as:

$$\mathbf{R}_s = \mathbf{Q} \mathbf{\Lambda}^2 \mathbf{Q}^T = (\mathbf{Q} \mathbf{\Lambda}) (\mathbf{Q} \mathbf{\Lambda})^T \quad (52)$$

where  $\mathbf{Q}$  is a  $t \times t$  matrix that consists of the orthonormal eigenvectors of  $\mathbf{R}_s$ :

$$\mathbf{Q} = [\mathbf{q}_1 \quad \mathbf{q}_2 \quad \dots \quad \mathbf{q}_t] \quad (53)$$

and  $\mathbf{\Lambda}^2$  is a diagonal  $t \times t$  matrix of the eigenvalues of  $\mathbf{R}_s$ :

$$\mathbf{\Lambda}^2 = \begin{bmatrix} \lambda_1 & 0 & \dots & 0 \\ 0 & \lambda_2 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \lambda_t \end{bmatrix} \quad (54)$$

and  $\mathbf{\Lambda}$  is a matrix with elements equal to the square root of the elements of  $\mathbf{\Lambda}^2$ . Note that since  $\mathbf{R}_s$  has a full rank, its eigenvalues are all positive. We, then define the  $t \times t$  matrix  $\tilde{\mathbf{R}}_N$  as below:

$$\tilde{\mathbf{R}}_N = (\mathbf{Q} \mathbf{\Lambda})^{-1} \mathbf{R}_N (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \quad (55)$$

Finally, as proved in the Appendix, the optimum values of the filter coefficients are:

$$\mathbf{G}_{\text{opt}} = (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \mathbf{I}_{\min} \quad (56)$$

where  $\tilde{\lambda}_{\min}$  is the minimum eigenvalue of  $\tilde{\mathbf{R}}_N$ , and  $\mathbf{I}_{\min}$  is its unit-length vector corresponding eigenvector.

**5. 3. 2. Case 2**  $\mathbf{R}_s$  has not a full rank. In this case, we have  $r < t$  and the SVD of the positive semidefinite matrix  $\mathbf{R}_s$  is written as:

$$\mathbf{R}_s = [\mathbf{U} | \mathbf{N}] \begin{bmatrix} \mathbf{S}^2 & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix} [\mathbf{U} | \mathbf{N}]^T \quad (57)$$

where  $\mathbf{S}^2$  is a diagonal  $r \times r$  matrix of the non-zero eigenvalues of  $\mathbf{R}_s$  as:

$$\mathbf{S}^2 = \begin{bmatrix} \lambda_1 & \dots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \dots & \lambda_r \end{bmatrix} \quad (58)$$

and  $\mathbf{U}$  is a  $t \times r$  matrix that consists of the eigenvectors of  $\mathbf{R}_s$  corresponding to signal space:

$$\mathbf{U} = [\mathbf{u}_1 \dots \mathbf{u}_r] \quad (59)$$

Also,  $\mathbf{N}$  is a  $t \times (t-r)$  matrix that consists of the eigenvectors of  $\mathbf{R}_s$  corresponding to null space:

$$\mathbf{N} = [\mathbf{n}_{r+1} \dots \mathbf{n}_t] \quad (60)$$

We now define the  $r \times r$  matrix  $\tilde{\mathbf{R}}_N$  as:

$$\tilde{\mathbf{R}}_N = \mathbf{S}^{-1} \mathbf{U}^T \left[ \mathbf{I} - \mathbf{R}_N \mathbf{N} (\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \right] \mathbf{R}_N \left[ \mathbf{I} - \mathbf{N} (\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \mathbf{R}_N \right] \mathbf{U} \mathbf{S}^{-1} \quad (61)$$

where  $\mathbf{S}$  is a matrix that its elements are the square root of the elements of  $\mathbf{S}^2$ . As proved in the Appendix, the optimum values of the filter coefficients in this case are now obtained as:

$$\mathbf{G}_{\text{opt}} = \left[ \mathbf{I} - \mathbf{N} (\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \mathbf{R}_N \right] \mathbf{U} \mathbf{S}^{-1} \mathbf{I}_{\min} \quad (62)$$

where  $\mathbf{I}_{\min}$  is the eigenvector of  $\tilde{\mathbf{R}}_N$  corresponding to its minimum eigenvalue.

## 6. SIMULATION RESULTS AND DISCUSSION

In this section, the simulation results of our proposed BHDC technique are presented and compared with the results obtained from an ideal maximal ratio combining (MRC) system. In this work, Rayleigh flat fading channels are considered, and simulations are performed for 200,000 random channel realizations. The average system performance is then obtained by Monte Carlo method. Since each Rayleigh channel is equivalent to two Gaussian channels, our results are also valid for Gaussian flat fading channels. As mentioned before, BHDC is a blind technique in which, the received bits used for estimation are a part of information data. In this work, the received data blocks with block length  $N_r=100$  are used for channel estimation.

**6. 1. Average System Performance** The average BER versus SNR for both BHDC and ideal MRC systems are shown in Figure 4. This figure is plotted for one Rayleigh channel equivalent to two Gaussian channels, and simulations are performed for two different filter orders  $D=3$  and  $D=5$ . As can be seen, the performance of BHDC is very close to ideal MRC. This is a valuable result, especially because higher

bandwidth efficiency is also achieved as compared with MRC.

A similar comparison is shown in Figure 5 for two Rayleigh channels equivalent to four Gaussian channels. As in the previous case, the performance of BHDC is very close to ideal MRC, especially at lower values of SNRs. It is also apparent from these results that the system performance does not change significantly when  $D$  changes, hence, we choose  $D=3$  in our simulations.

To see the effect of received data block length  $N_r$  on system performance, simulations are performed for three different values of  $N_r \in \{20, 100, 500\}$ . As can be seen from Figure 6, the results are almost the same, and we therefore choose  $N_r=100$ .

**6. 2. Reliability** Although the BER, averaged over all possible channel realizations, is usually considered as a measure for system performance, in many practical situations like voice communications, the users expect reliable communications while using the system and do not care about the average performance. On the other hand, there are some rare channel realizations that cause significant error rate reducing the average system performance.

Here, we focus on individual channel realizations and compare the performances of BHDC and ideal MRC systems. Based on the above discussion, we define *Relative Reliability Factor (RRF)* as the probability that for a particular channel occurrence,  $H$  the BER of BHDC is less than or equal to the BER of ideal MRC, i.e.:

$$RRF = \text{Prob}(BER_{BHDC} \leq BER_{MRC} | H) \quad (63)$$

RRF versus SNR is calculated for 200,000 two Rayleigh diversity channels and the result is plotted in Figure 7. As can be seen, when  $SNR \geq 7$  dB, in almost 90 percent of channel realizations the performance of BHDC is equal to or better than ideal MRC. For  $SNR \geq 10$  dB this probability is almost 100 percent. This result shows that at moderate and high SNRs the performance of BHDC for most channel realizations is not worse than ideal MRC.

### 6. 3. Comparison of MRC and BHDC for Soft Decision Applications

In soft decision systems where no hard limiter is present, the combiner output is taken as the decoding information [2]. To compare our proposed combiner with ideal MRC in soft decision purposes, we have plotted the histograms representing the variation of the combiner output values around the transmitted symbol values. The simulations were performed for a particular two diversity Rayleigh channel with normalized coefficients and 4,000,000 transmitted binary symbols. The results for both MRC and BHDC techniques are plotted in Figures 8 and 9 for

$SNR=5$  dB and  $SNR=20$  dB respectively. It is apparent from these figures that for both SNRs, the outputs of BHDC combiner are much closer to the desired symbol values  $\pm 1$  as compared with the corresponding values in MRC system. Hence, for soft decision applications it is superior to MRC technique.




Figure 4. Average BER for BHDC and MRC




Figure 5. Average BER for BHDC and MRC




Figure 6. Effect of received data block length in BHDC






Figure 7. Relative Reliability Factor




(b)

Figure 9. The variation of the combiner output values around the transmitted symbol values. (a). BHDC (b). MRC




(a)



(b)

Figure 8. The variation of the combiner output values around the transmitted symbol values. (a). BHDC (b). MRC



(a)

## 7. CONCLUSION

In this paper, we proposed a blind diversity combining technique using Hammerstein type filters. To show the performance of our proposed technique, simulations were performed for Rayleigh flat fading channels and BPSK modulation in presence of AWGN. Simulation results of BHDC technique were compared with the results obtained from an ideal maximal ratio combining (MRC) system. We also defined relative reliability factor (RRF) to compare the performances of BHDC and ideal MRC for any channel realization. From our simulation results, we conclude that:

- i) The average BER of BHDC is very close to ideal MRC. This is a valuable result, especially because higher bandwidth efficiency is also achieved as compared with MRC.
- ii) At moderate and high SNRs, for any channel realization, the probability of the BER of BHDC being lower than or equal to ideal MRC is very high.
- i) The outputs of BHDC combiner are much closer to the desired symbol values  $\pm 1$  as compared with the corresponding values in MRC system. Hence, for soft decision applications it is superior to MRC technique.

## 8. REFERENCES

1. Simon, M. K. and Alouini, M. S., "Digital communication over fading channels, Wiley-IEEE Press, Vol. 86, (2004).
2. Proakis, J. G. and Salehi, M., "Digital Communications, ed. 5th, Singapore, McGraw-Hill, (2008).
3. Rahimzadeh, P. D. and Beaulieu, N., "New simple closed-form BER expressions for MRC diversity BPSK in correlated Rayleigh fading and CCI", *Communications, IEEE Transactions on*, Vol. 57, No. 3, (2009), 630-634.
4. Loskot, P. and Beaulieu, N., "A unified approach to computing error probabilities of diversity combining schemes over



- correlated fading channels", *Communications, IEEE Transactions on*, Vol. 57, No. 7, (2009), 2031-2041.
5. Liu, S., Cheng, J. and Beaulieu, N. C., "Asymptotic error analysis of diversity schemes on arbitrarily correlated rayleigh channels", *Communications, IEEE Transactions on*, Vol. 58, No. 5, (2010), 1351-1355.
  6. Mallik, R. K. and Winters, J. H., "Deterministic linear combining receivers for random fading channels", *Communications, IEEE Transactions on*, Vol. 58, No. 9, (2010), 2630-2638.
  7. Lu, Y. and Yang, N., "Symbol error probability of QAM with MRC diversity in two-wave with diffuse power fading channels", *Communications Letters, IEEE*, Vol. 15, No. 1, (2011), 10-12.
  8. Skraparlis, D., Sakarellos, V. K., Panagopoulos, A. D. and Kanellopoulos, J. D., "New results on the statistics and the capacity of dual-branch MRC and EGC diversity in correlated lognormal channels", *Communications Letters, IEEE*, Vol. 15, No. 6, (2011), 617-619.
  9. Beaulieu, N. C. and Rabiei, A. M., "Linear diversity combining on Nakagami-0.5 fading channels", *Communications, IEEE Transactions on*, Vol. 59, No. 10, (2011), 2742-2752.
  10. Gans, M., "The effect of Gaussian error in maximal ratio combiners", *Communication Technology, IEEE Transactions on*, Vol. 19, No. 4, (1971), 492-500.
  11. Tomiuk, B. R., Beaulieu, N. C. and Abu-Dayya, A. A., "General forms for maximal ratio diversity with weighting errors", *Communications, IEEE Transactions on*, Vol. 47, No. 4, (1999), 488-492.
  12. Annavajjala, R. and Milstein, L. B., "On the performance of diversity combining schemes on rayleigh fading channels with noise estimates", in *Military Communications, IEEE*, Vol. 1, (2003), 320-325.
  13. Annavajjala, R. and Milstein, L. B., "Performance analysis of linear diversity-combining schemes on Rayleigh fading channels with binary signaling and Gaussian weighting errors", *Wireless Communications, IEEE Transactions on*, Vol. 4, No. 5, (2005), 2267-2278.
  14. Annavajjala, R., Cosman, P. C. and Milstein, L. B., "Performance analysis of linear modulation schemes with generalized diversity combining on Rayleigh fading channels with noisy channel estimates", *Information Theory, IEEE Transactions on*, Vol. 53, No. 12, (2007), 4701-4727.
  15. Gifford, W. M., Win, M. Z. and Chiani, M., "Diversity with practical channel estimation", *Wireless Communications, IEEE Transactions on*, Vol. 4, No. 4, (2005), 1935-1947.
  16. Gifford, W. M., Win, M. Z. and Chiani, M., "Diversity combining with imperfect channel estimates in correlated fading", *Aerospace and Electronic Systems, IEEE Transactions on*, Vol. 44, No. 3, (2008), 852-860.
  17. Schmitt, L., Grundler, T., Schreyoegg, C., Viering, I. and Meyr, H., "Maximum ratio combining of correlated diversity branches with imperfect channel state information and colored noise", in *Spread Spectrum Techniques and Applications, IEEE Eighth International Symposium on*, (2004), 859-863.
  18. Ko, Y. C. and Luo, T., "Effect of noise imbalance on dual-MRC over Rayleigh fading channels", *Wireless Communications, IEEE Transactions on*, Vol. 5, No. 3, (2006), 514-518.
  19. Hui, H. T., "The performance of the maximum ratio combining method in correlated Rician-fading channels for antenna-diversity signal combining", *Antennas and Propagation, IEEE Transactions on*, Vol. 53, No. 3, (2005), 958-964.
  20. You, R., Li, H. and Bar-Ness, Y., "Diversity combining with imperfect channel estimation", *Communications, IEEE Transactions on*, Vol. 53, No. 10, (2005), 1655-1662.
  21. Wu, J. and Xiao, C., "Optimal diversity combining based on linear estimation of rician fading channels", in *Communications, 2007. ICC'07. International Conference on*, IEEE, (2007), 3999-4004.
  22. Jeraj, J. and Mathews, V. J., "A stable adaptive Hammerstein filter employing partial orthogonalization of the input signals", *Signal Processing, IEEE Transactions on*, Vol. 54, No. 4, (2006), 1412-1420.
  23. Jeraj, J. and Mathews, V. J., "Stochastic mean-square performance analysis of an adaptive Hammerstein filter", *Signal Processing, IEEE Transactions on*, Vol. 54, No. 6, (2006), 2168-2177.
  24. Kalouptsidis, N. and Koukoulas, P., "Blind identification of Volterra-Hammerstein systems", *Signal Processing, IEEE Transactions on*, Vol. 53, No. 8, (2005), 2777-2787.
  25. Mkaem, F. and Boumaiza, S., "Extended Hammerstein behavioral model using artificial neural networks", *Microwave Theory and Techniques, IEEE Transactions on*, Vol. 57, No. 4, (2009), 745-751.
  26. Le Caillec, J. M., "Time series modeling by a second-order Hammerstein system", *Signal Processing, IEEE Transactions on*, Vol. 56, No. 1, (2008), 96-110.
  27. Shi, K., Ma, X. and Zhou, G. T., "Acoustic echo cancellation using a pseudocoherence function in the presence of memoryless nonlinearity", *Circuits and Systems I: Regular Papers, IEEE Transactions on*, Vol. 55, No. 9, (2008), 2639-2649.
  28. Shi, K., Zhou, G. T. and Viberg, M., "Compensation for nonlinearity in a Hammerstein system using the coherence function with application to nonlinear acoustic echo cancellation", *Signal Processing, IEEE Transactions on*, Vol. 55, No. 12, (2007), 5853-5858.
  29. Zhou, D. and DeBrunner, V., "Efficient adaptive nonlinear filters for nonlinear active noise control", *Circuits and Systems I: Regular Papers, IEEE Transactions on*, Vol. 54, No. 3, (2007), 669-681.
  30. Aminian-Modarres, A. M. and Molavi, M., "A nonlinear equalization technique for frequency selective fading channels", in *Signal and Image Processing Applications (ICSIPA), IEEE International Conference on*, IEEE, (2009), 369-373.
  31. Aminian-Modarres, A. M. and Molavi-kakhki, M., "A Nonlinear Signal Processing Method for Diversity Combining Using Hammerstein Type Filter", *International Journal of Computer Science and Network Security (IJCSNS)*, Vol. 9, No. 1, (2009).
  32. Molavi Kakhki, M., "A Hammerstein Diversity Combining Technique", *International Journal of Information and Communication Technology-IJICT*, Vol. 2, No., (2010).
  33. Kay, S. M., "Fundamentals of Statistical Signal Processing, New Jersey, Prentice Hall, Vol. 1, (1993).

## APPENDIX

In this appendix the proofs of the Equations (56) and (62) are presented. As explained in section 5.3, we desire to maximize the cost function  $J$  in Equation (32) with the constraint  $P_s = 1$ , i.e., to find  $\mathbf{G}_H$  such that  $P_N = \mathbf{G}_H^T \mathbf{R}_N \mathbf{G}_H$  is minimized given  $P_s = \mathbf{G}_H^T \mathbf{R}_s \mathbf{G}_H = 1$ . We consider two cases:

**Case 1:**  $\mathbf{R}_s$  has a full rank. In this case we have  $r = t$ , where  $r$  and  $t = M(D+1)$  are the rank and the

dimension of  $\mathbf{R}_s$  respectively. According to Equation (33) and Equations (52)- (54) we have:

$$P_s = \mathbf{G}_H^T \mathbf{R}_s \mathbf{G}_H = \mathbf{G}_H^T (\mathbf{Q} \mathbf{\Lambda}) (\mathbf{Q} \mathbf{\Lambda})^T \mathbf{G}_H = 1 \quad (\text{A-1})$$

and:

$$\mathbf{Q} \mathbf{Q}^T = \mathbf{Q}^T \mathbf{Q} = \mathbf{I} \quad (\text{A-2})$$

We define the  $t \times 1$  vector  $\mathbf{a}$  as:

$$\mathbf{a} = (\mathbf{Q} \mathbf{\Lambda})^T \mathbf{G}_H = (\mathbf{\Lambda} \mathbf{Q}^T) \mathbf{G}_H \quad (\text{A-3})$$

the constraint  $P_s = 1$  can now be written as:

$$\mathbf{G}_H^T \mathbf{R}_s \mathbf{G}_H = \mathbf{a}^T \mathbf{a} = 1 \quad (\text{A-4})$$

This means that  $\mathbf{a}$  is a unite-length vector. Moreover, since  $\mathbf{R}_s$  has a full rank, the matrix  $\mathbf{\Lambda} \mathbf{Q}^T$  is invertible and we have:

$$\mathbf{G}_H = (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \mathbf{a} \quad (\text{A-5})$$

Substituting Equation (A-5) in Equation (34) leads to:

$$\begin{aligned} P_N &= \mathbf{G}_H^T \mathbf{R}_N \mathbf{G}_H = \mathbf{a}^T \left( (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \right)^T \mathbf{R}_N (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \mathbf{a} \\ &= \mathbf{a}^T (\mathbf{Q} \mathbf{\Lambda})^{-1} \mathbf{R}_N (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \mathbf{a} \\ &= \mathbf{a}^T \tilde{\mathbf{R}}_N \mathbf{a} \end{aligned} \quad (\text{A-6})$$

where  $\tilde{\mathbf{R}}_N$  is defined by Equation (55). Finally,  $P_N$  in Equation (A-6) is minimized with the constraint Equation (A-4). Using the lagrangian method for optimization [33], the following equation must be minimized:

$$A = \mathbf{a}^T \tilde{\mathbf{R}}_N \mathbf{a} - K(\mathbf{a}^T \mathbf{a} - 1) \quad (\text{A-7})$$

where  $K$  is constant value. We have:

$$\nabla_a A = 2\tilde{\mathbf{R}}_N \mathbf{a} - 2K\mathbf{a} = \mathbf{0} \Rightarrow \tilde{\mathbf{R}}_N \mathbf{a} = K\mathbf{a} \quad (\text{A-8})$$

where  $\nabla$  is the gradient operator. Consequently, if  $\mathbf{a}$  is an orthonormal eigenvector of  $\tilde{\mathbf{R}}_N$ , it can be a solution for Equation (A-8) and  $K$  is its corresponding eigenvalue. Therefore, there exist  $t$  solutions for the above equation among which only one leads to the global minimum. To find this global minimum, we use the SVD of the positive definite matrix  $\tilde{\mathbf{R}}_N$  as below:

$$\tilde{\mathbf{R}}_N = \mathbf{L} \mathbf{\Gamma}^2 \mathbf{L}^T \quad (\text{A-9})$$

where  $\mathbf{L}$  is a  $t \times t$  matrix that consists of the orthonormal eigenvectors of  $\tilde{\mathbf{R}}_N$ :

$$\mathbf{L} = [\mathbf{l}_1 \ \mathbf{l}_2 \ \dots \ \mathbf{l}_t] \quad (\text{A-10})$$

and  $\mathbf{\Gamma}^2$  is a diagonal  $t \times t$  matrix with eigenvalues of  $\mathbf{R}_s$ :

$$\mathbf{\Gamma}^2 = \begin{bmatrix} \tilde{\lambda}_1 & 0 & \dots & 0 \\ 0 & \tilde{\lambda}_2 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \tilde{\lambda}_t \end{bmatrix} \quad (\text{A-11})$$

Equation (A-9) can be written as:

$$\tilde{\mathbf{R}}_N = \sum_{i=1}^t \tilde{\lambda}_i \mathbf{l}_i \mathbf{l}_i^T \quad (\text{A-12})$$

Using Equations (A-6) and (A-12)  $P_N$  can be written as:

$$P_N = \sum_{i=1}^t \tilde{\lambda}_i \mathbf{a}^T \mathbf{l}_i \mathbf{l}_i^T \mathbf{a} = \sum_{i=1}^t \tilde{\lambda}_i \left| \mathbf{a}^T \mathbf{l}_i \right|^2 \quad (\text{A-13})$$

According to Equation (A-8), the vector  $\mathbf{a}$  can be each of the eigenvectors  $\mathbf{l}_i$ . Therefore, due to orthonormality of the eigenvectors we have:

$$\mathbf{a}_{\text{opt}} = \mathbf{l}_{\min} \Rightarrow P_{N_{\min}} = \tilde{\lambda}_{\min} \quad (\text{A-14})$$

where  $\mathbf{a}_{\text{opt}}$  is a solution of Equation (A-8) that leads to the global minimum  $P_{N_{\min}}$ . Also,  $\tilde{\lambda}_{\min}$  is the minimum eigenvalue of  $\tilde{\mathbf{R}}_N$ , and  $\mathbf{l}_{\min}$  is its unite-length corresponding eigenvector. Using Equations (A-5) and (A-14) the optimum values of the filter coefficients are:

$$\mathbf{G}_H = (\mathbf{\Lambda} \mathbf{Q}^T)^{-1} \mathbf{l}_{\min} \quad (\text{A-15})$$

**Case 2:**  $\mathbf{R}_s$  has not a full rank. In this case we have  $r < t$ . According to Equations (57)- (60) we have:

$$\begin{cases} \mathbf{U}^T \mathbf{U} = \mathbf{I} \\ \mathbf{N}^T \mathbf{N} = \mathbf{I} \end{cases}, \begin{cases} \mathbf{U}^T \mathbf{N} = \mathbf{0} \\ \mathbf{N}^T \mathbf{U} = \mathbf{0} \end{cases} \quad (\text{A-16})$$

Note that:

$$\begin{cases} \mathbf{U} \mathbf{U}^T \neq \mathbf{I} \\ \mathbf{N} \mathbf{N}^T \neq \mathbf{I} \end{cases} \quad (\text{A-17})$$

Using Equations (57)- (59)  $\mathbf{R}_s$  can be written as:

$$\mathbf{R}_s = \mathbf{U} \mathbf{S}^2 \mathbf{U}^T = (\mathbf{U} \mathbf{S})(\mathbf{U} \mathbf{S})^T \quad (\text{A-18})$$

where:

$$\mathbf{S} = \begin{bmatrix} \sqrt{\lambda_1} & \dots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \dots & \sqrt{\lambda_r} \end{bmatrix} \quad (\text{A-19})$$

the constraint  $P_s = 1$  can now be written as:

$$P_s = \mathbf{G}_H^T \mathbf{R}_s \mathbf{G}_H = \mathbf{G}_H^T \mathbf{U} \mathbf{S} (\mathbf{U} \mathbf{S})^T \mathbf{G}_H = 1 \quad (\text{A-20})$$

Suppose that similar to Equation (A-3), the  $r \times 1$  unite-length vector  $\mathbf{a}$  is defined as below:

$$\mathbf{a} = (\mathbf{U} \mathbf{S})^T \mathbf{G}_H \quad (\text{A-21})$$

However, because  $\mathbf{R}_s$  has not a full rank, this equation is not invertible and a unique solution for  $\mathbf{G}_H$  cannot be obtained. Hence, in this case we cannot use the definition Equation (A-21). We can write Equation (A-21) as:

$$\begin{aligned} \mathbf{a} &= (\mathbf{U} \mathbf{S})^T \mathbf{G}_H = \mathbf{S} \mathbf{U}^T \mathbf{G}_H \\ &= \begin{bmatrix} \sqrt{\lambda_1} & \dots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \dots & \sqrt{\lambda_r} \end{bmatrix} \begin{bmatrix} \mathbf{u}_1^T \\ \vdots \\ \mathbf{u}_r^T \end{bmatrix} \mathbf{G}_H = \begin{bmatrix} \sqrt{\lambda_1} \mathbf{u}_1^T \mathbf{G}_H \\ \vdots \\ \sqrt{\lambda_r} \mathbf{u}_r^T \mathbf{G}_H \end{bmatrix} \end{aligned} \quad (\text{A-22})$$

In fact, Equation (A-22) implies that the  $r \times 1$  vector  $\mathbf{a}$

is a mapping of the  $t \times 1$  vector  $\mathbf{G}_H$  in the signal space. To avoid the above problem, we now write  $\mathbf{G}_H$  as below:

$$\mathbf{G}_H = \mathbf{U}\mathbf{c} + \mathbf{N}\mathbf{b} \quad (\text{A-23})$$

where  $\mathbf{c}$  and  $\mathbf{b}$  are arbitrary  $r \times 1$  and  $(t-r) \times 1$  vectors respectively. Note that Equation (A-23) can be written as:

$$\mathbf{G}_H = \underbrace{c_1 \mathbf{u}_1 + c_2 \mathbf{u}_2 + \dots + c_r \mathbf{u}_r}_{\text{mapping in the signal space}} + \underbrace{b_1 \mathbf{n}_{r+1} + \dots + b_{t-r} \mathbf{n}_t}_{\text{mapping in the null space}} \quad (\text{A-24})$$

$$= \mathbf{U} \begin{bmatrix} c_1 \\ c_2 \\ \vdots \\ c_r \end{bmatrix} + \mathbf{N} \begin{bmatrix} b_1 \\ b_2 \\ \vdots \\ b_{t-r} \end{bmatrix}$$

Substituting Equations (A-18), (A-23) and (A-16) in Equation (A-20) we have:

$$P_s = \mathbf{G}_H^T \mathbf{R}_s \mathbf{G}_H = (\mathbf{c}^T \mathbf{U}^T + \mathbf{b}^T \mathbf{N}^T) (\mathbf{R}_s \mathbf{U} \mathbf{c} + \mathbf{R}_s \mathbf{N} \mathbf{b}) \quad (\text{A-25})$$

$$= \mathbf{c}^T \mathbf{U}^T \mathbf{U} \mathbf{S}^2 \mathbf{U}^T \mathbf{U} \mathbf{c} = \mathbf{c}^T \mathbf{S}^2 \mathbf{c} = 1$$

Now, we define the  $t \times 1$  vector  $\mathbf{a}$  as:

$$\mathbf{a} = \mathbf{S} \mathbf{c} \Rightarrow \mathbf{c} = \mathbf{S}^{-1} \mathbf{a} \quad (\text{A-26})$$

Hence, we have:

$$\mathbf{c}^T \mathbf{S}^2 \mathbf{c} = (\mathbf{S} \mathbf{c})^T (\mathbf{S} \mathbf{c}) = \mathbf{a}^T \mathbf{a} = 1 \quad (\text{A-27})$$

This means that  $\mathbf{a}$  is a unite-length vector. Substituting Equation (A-26) in Equation (A-23) becomes:

$$\mathbf{G}_H = \mathbf{U} \mathbf{S}^{-1} \mathbf{a} + \mathbf{N} \mathbf{b} \quad (\text{A-28})$$

Substituting Equation (A-28) in Equation (34) leads to:

$$P_N = \mathbf{G}_H^T \mathbf{R}_N \mathbf{G}_H \quad (\text{A-29})$$

$$= (\mathbf{a}^T \mathbf{S}^{-1} \mathbf{U}^T + \mathbf{b}^T \mathbf{N}^T) \mathbf{R}_N (\mathbf{U} \mathbf{S}^{-1} \mathbf{a} + \mathbf{N} \mathbf{b})$$

$$= \mathbf{a}^T \mathbf{S}^{-1} \mathbf{U}^T \mathbf{R}_N \mathbf{U} \mathbf{S}^{-1} \mathbf{a} + \mathbf{b}^T \mathbf{N}^T \mathbf{R}_N \mathbf{U} \mathbf{S}^{-1} \mathbf{a}$$

$$+ \mathbf{a}^T \mathbf{S}^{-1} \mathbf{U}^T \mathbf{R}_N \mathbf{N} \mathbf{b} + \mathbf{b}^T \mathbf{N}^T \mathbf{R}_N \mathbf{N} \mathbf{b}$$

Finally,  $P_N$  in Equation (A-29) is minimized with the

constraint Equation (A-27). Using the lagrangian method, the following equation must be minimized:

$$A = P_N - K(\mathbf{a}^T \mathbf{a} - 1) \quad (\text{A-30})$$

Setting the derivative of Equation (A-30) with respect to  $\mathbf{b}$  equal to zero we get:

$$\nabla_{\mathbf{b}} A = \mathbf{N}^T \mathbf{R}_N \mathbf{U} \mathbf{S}^{-1} \mathbf{a} + \mathbf{N}^T \mathbf{R}_N^T \mathbf{U} \mathbf{S}^{-1} \mathbf{a} + 2 \mathbf{N}^T \mathbf{R}_N \mathbf{N} \mathbf{b} = \mathbf{0} \quad (\text{A-31})$$

Note that  $\mathbf{R}_N = \mathbf{R}_N^T$ , and therefore we have:

$$\mathbf{b}_{opt} = -(\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \mathbf{R}_N \mathbf{U} \mathbf{S}^{-1} \mathbf{a} \quad (\text{A-32})$$

Substituting Equation (A-32) in Equation (A-29) yields:

$$P_N = \mathbf{a}^T \left\{ \mathbf{S}^{-1} \mathbf{U}^T \left[ \mathbf{I} - \mathbf{R}_N \mathbf{N} (\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \right] \right\} \quad (\text{A-33})$$

$$\mathbf{R}_N \left\{ \left[ \mathbf{I} - \mathbf{N} (\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \mathbf{R}_N \right] \mathbf{U} \mathbf{S}^{-1} \right\} \mathbf{a}$$

$$= \mathbf{a}^T \tilde{\mathbf{R}}_N \mathbf{a}$$

where  $\tilde{\mathbf{R}}_N$  is defined by Equation (61). Substituting Equation (A-33) in Equation (A-30) we have:

$$A = \mathbf{a}^T \tilde{\mathbf{R}}_N \mathbf{a} - K(\mathbf{a}^T \mathbf{a} - 1) \quad (\text{A-34})$$

This equation is the same as Equation (A-7) and therefore the optimum value for  $\mathbf{a}$  is obtained as:

$$\mathbf{a}_{opt} = \mathbf{I}_{min} \Rightarrow P_{Nmin} = \tilde{\lambda}_{min} \quad (\text{A-35})$$

where  $\tilde{\lambda}_{min}$  is the minimum eigenvalue of  $\tilde{\mathbf{R}}_N$ , and  $\mathbf{I}_{min}$  is its unite-length corresponding eigenvector. Finally, substituting Equations (A-35) and (A-32) in Equation (A-28) the optimum values of the filter coefficients are:

$$\mathbf{G}_{Hopt} = \left[ \mathbf{I} - \mathbf{N} (\mathbf{N}^T \mathbf{R}_N \mathbf{N})^{-1} \mathbf{N}^T \mathbf{R}_N \right] \mathbf{U} \mathbf{S}^{-1} \mathbf{I}_{min} \quad (\text{A-36})$$

# A Blind Hammerstein Diversity Combining Technique for Flat Fading Channels

A. M. Aminian-Modarres <sup>a</sup>, M. Molavi-kakhki<sup>b</sup>

<sup>a</sup> Department of Electrical Engineering, Sadjad Institute of Higher Education, Mashhad, Iran

<sup>b</sup> Department of Electrical Engineering, Ferdowsi University of Mashhad, Mashhad, Iran

## PAPER INFO

## چکیده

### Paper history:

Received 22 February 2012

Received in revised form 16 May 2012

Accepted 18 October 2012

### Keywords:

Nonlinear Signal Processing  
Nonlinear Diversity Combining  
Hammerstein Filter  
Rayleigh Flat Fading Channel

پدیده‌ی تارکنندگی کانال مهم‌ترین عامل مخرب در سیستم‌های مخابرات بی‌سیم می‌باشد. استفاده از روش‌های ترکیب دایورسیتی راه حل شناخته شده‌ای برای مقابله با پدیده‌ی فوق است. در این مقاله یک روش غیرخطی جدید مبتنی بر فیلتر هم‌رشتاین برای ترکیب دایورسیتی در کانال‌های تارکننده تخت ریلی پیشنهاد می‌شود که روشی کاملاً کور است. همان‌طور که می‌دانیم روش بهینه در مورد کانال‌های تخت روش MRC ایده‌آل است. روش پیشنهادی ما از لحاظ نرخ متوسط وقوع خطا به روش MRC ایده‌آل خیلی نزدیک است. ضمن آن که بهره‌ی عرض باند بیشتری نیز دارد. همچنین نشان می‌دهیم که در روش ما پراکندگی داده‌های خروجی ترکیب‌کننده حول مقادیر مطلوب نسبت به روش MRC خیلی کمتر است. این موضوع می‌تواند در سیستم‌هایی که از تصمیم‌گیری نرم استفاده می‌کنند مورد بهره‌برداری قرار گیرد.

doi: 10.5829/idosi.ije.2013.26.03c.07