

## Pythagorean interval 2-tuple linguistic VIKOR method for evaluating human factors in construction project management

T. He<sup>1</sup>, G. Wei<sup>2</sup>, R. Lin<sup>3</sup>, J. Lu<sup>4</sup>, C. Wei<sup>5</sup> and J. Wu<sup>6</sup>

<sup>1,2,4</sup>*School of Business, Sichuan Normal University, Chengdu, 610101, P.R. China*

<sup>3</sup>*School of Economics and Management, Chongqing University of Arts and Sciences, Chongqing 402160, China*

<sup>5,6</sup>*School of Statistics, Southwestern University of Finance and Economics, Chengdu, 611130, P.R. China*

m\_hetingting@163.com, weiguiwu@163.com, linrui@cqwu.edu.cn, lujp2002@163.com, weicun1990@163.com, wujiang@swufe.edu.cn

### Abstract

In a construction project, there are many factors that affect the project quality, such as people, materials, machinery, environment, etc. Among them, people have the greatest influence on the project quality, whether people participate directly or indirectly. This paper mainly evaluates human factors in the process of construction project management, such as workers proficiency, workers safety awareness, technical workers quality, and workers emergency capacity, with the purpose of helping Chinas construction project to proceed smoothly. In this manuscript, a multi-attribute group decision-making (MAGDM) technique based on Pythagorean interval 2-tuple linguistic numbers (PI2TLNs) and VIKOR method is proposed to evaluate human factors in construction projects. PI2TLNs are used to represent performance assessments of decision makers. Relying on Pythagorean interval 2-tuple linguistic weighted averaging (PI2TLWA)/Pythagorean interval 2-tuple linguistic weighted geometric (PI2TLWG) operator, the evaluation information given by experts is fused into a group decision matrix. Combined with the essential VIKOR method, PI2TLN-VIKOR framework is established. The effectiveness of this method is verified by an example, and compared with two algorithms and PI2TLN-TODIM method.

**Keywords:** Multiple attribute group decision making (MAGDM), Pythagorean interval 2-tuple linguistic numbers (PI2TLNs), VIKOR method, construction project management.

## 1 Introduction

In the related projects of engineering construction, the management problems mainly involve safety management, it is closely related to people, things and environment. Safety management involved in engineering construction project management problems need to be eliminated or avoided in time to ensure that construction is completed on time to protect the personal safety and property safety of construction personnel. However, in engineering construction project management, human factors play a very important role, can effectively guide the construction project construction management results. In recent years, there have been a series of explorations and researches on capital construction management at home and abroad. Mete [40] proposed FMEA-based AHP-MOORA comprehensive evaluation method based on Pythagorean fuzzy sets (PFSs) for a natural gas pipeline construction project. Carr and Tah [5] used the language variables to describe the risks and their consequences in the construction industry, and fuzzy approximations and combinations were used to determine the relationship between risk sources and project performance evaluation results and to quantify them consistently. Dagdeviren and Yuksel [7] constructed the project construction behavior safety management evaluation model by using data fuzzy processing and analytic hierarchy process. Gupta and Thakkar [18] adopted TOPSIS method to prioritize risk and compared it with the results of quantitative risk analysis and shown that this approach can provide stronger results and contribute to the management control of project risks. On the basis of 2-tuple linguistic Pythagorean fuzzy Numbers (2TLPFNS) and Bonferroni mean (BM) operator, Deng, Wei,

Gao and Wang [9] defined several operators and applied them to evaluate the safety management of construction projects. Lu [36] combined TOPSIS model and 2-tuple linguistic set to consider the fuzziness of evaluation in the field of building management and applied scientific ranking method to obtain the optimal solution. Biswas and Zaman [3] utilized the triangular fuzzy number to integrate expert assessment information and historical data for assessing the risks in construction projects. Wang, Wei and Lu [59] extended the original TODIM model to the context of the 2-tuple linguistic neutrosophic set. Wang, Zhang, Wang and Li [62] constructed a new VIKOR model with a picture fuzzy projection to determine the priority of risk factors in a building project. Roy, Das, Kar and Pamucar [49] extended CODAS into the interval value IFSs for the MADM problem with incomplete weight information.

The above scholars studied the safety evaluation, performance evaluation and risk management of construction projects from different perspectives and methods, but none of them involved the evaluation of human factors in construction projects. Therefore, this paper intends to adopt a fuzzy evaluation method to complete this task. The following are about PFSs and VIKOR. The PFSs is put forward by Yager and Abbasov [73] compared with intuitionistic fuzzy sets [1], which expanded the membership and the non-membership degree to meet the conditions of the sum of the squares less than or equal to 1. Since the introduction of PFSs, many scholars have done a lot of research and expansion on it. Zhang and Xu [79] proposed a sort optimization method based on similar ideal solution for MADM problem with PFSs. Liang, Zhang and Liu [30] proposed a concept based on interval Pythagorean fuzzy number (IVPFN) and innovated a method to deal with MAGDM problem. In order to better understand PFSs, Peng and Yang [45] redefined the division and subtraction operation of PFS and discussed their properties in detail. Garg [12] first pointed out the shortcomings of calculating the correlation coefficients of intuitionistic fuzzy sets (IFSS) and designed a new (weighted) correlation coefficient formula to measure the relationship between two PFSs. Garg [11] defined several operators of PFSs and studied the corresponding properties. In order to enrich the PFS theory, Gou, Xu and Ren [16] studied the basic properties of continuity, derivability and differentiability for PFSs. Ma and Xu [37] defined a new class of operators based on the given algorithm and compared with the existing operators for PFSs. Peng and Yang [46] studied the MAGDM problem of interval valued PFSs. Liang and Xu [29] combined PFSs with hesitating fuzzy sets, in which the membership and non-membership of PFS were expressed as hesitating fuzzy numbers and combined this new environment with the TOPSIS approach. Qin, Liu and Hong [47] studied the new distance measurement method for PFSs, and innovatively introduced the generalized Pythagorean fuzzy weighted averaging distance (GPFWAD) operator and generalized Pythagorean fuzzy ordered weighted averaging distance (GPFOWAD) operator. Bolturk [4] extended the CODAS method to the PFSs and considered the decision maker's hesitation. Wei, Gao, Wang and Huang [63] defined the TODIM method based on the Pythagorean 2-tuple linguistic fuzzy sets (P2TLSs) by combining PFSs [27, 58] with 2-tuple linguistic set. Ding and Liu [10] innovated a new method to apply to the example of emergency decision-making which firstly used the best-worst method to calculate the attribute weight. Liu, Quan, Shi and Guo [32] used the interval-valued Pythagorean uncertain linguistic sets to express the subjectivity and uncertainty of decision makers and used the QUALIFLEX technology to select the most suitable robot.

The ViseKriterijumska Optimizacija I Kompromisno Resenje (VIKOR) method is put forward by Opricovic and Tzeng [43], which is a multi-attributes decision-making (MADM) method based on the ideal point method. Opricovic and Tzeng [44] popularized the VIKOR method by using a higher-level relationship. Compared with previous methods, such as ELECTRE [2], PROMETHEE [39], GRA[25], TOPSIS [22, 24, 35], TODIM [15, 59], MABAC [57, 60, 65, 78] and EDAS method [19, 28, 56], the advantage of this approach is that conflicts between attributes are considered, the best solution is the closest to the ideal solution, and a compromise with priority is obtained. Mete, Serin, Oz and Gul [41] provided the VIKOR method based on the PFSs for risk assessment of gas pipeline construction with a view to contributing to stakeholders in the energy industry. Muhammet Gul, M. Fatih Ak and Guneri. [17] put forward the VIKOR method to evaluate the overall safety level of underground mining under PFSs. Cui, You, Shi and Liu [6] established a Pythagorean fuzzy VIKOR model to solve the location problem of charging stations for electric vehicles. Zeng, Chen and Kuo [77] designed the MADM method based on novel score function of intuitionistic fuzzy values and modified VIKOR method. Wang, Xu, Wang and Ren [61] defined an interval MADM method by coupling interval DEMATEL and interval VIKOR. Wang, Sun and Zhou [55] designed an intuitionistic fuzzy MAGDM method with incomplete weight information based on improved VIKOR. Wu, Gao and Wei [68] proposed the VIKOR method for financing risk assessment of rural tourism projects under interval-valued intuitionistic fuzzy environment. Rani, Mishra, Pardasani, Mardani, Liao and Streimikiene [48] defined a novel VIKOR method based on entropy and divergence measures of PFSs to evaluate renewable energy technologies. Narayanamoorthy, Geetha, Rakkiyappan and Joo [42] proposed the interval-valued intuitionistic hesitant fuzzy entropy based-VIKOR algorithms for industrial robot selection. Wang, Pan and He [53] defined a novel interval Type-2 fuzzy VIKOR model for MADM. Wang, Song, Ren, Li, Duan and Wang [54] Selected the sustainable energy conversion technologies for agricultural residues by using a fuzzy AHP-VIKOR-based prioritization from life cycle point. Wu, Xu, Jiang and Zhong [71] developed two MAGDM methods based on hesitant fuzzy linguistic term sets along with VIKOR and TOPSIS method. Wu, Zhou, Chen and Chen [72]

defined the integrated algorithms to green supplier selection with the interval type-2 fuzzy best-worst and extended VIKOR methods. Yang and Pang [74] proposed the hesitant interval-valued Pythagorean fuzzy VIKOR method. Gao, Ran, Wei, Wei and Wu [14] devised the VIKOR method to solve the MAGDM based on q-rung interval-valued orthopair fuzzy information for supplier selection of medical consumption products.

Although the previous studies involved the selection of construction projects, they did not mention the evaluation of human factors in the process of construction project management. Therefore, it is necessary to use relevant evaluation criteria to evaluate human factors. In this paper, we use PI2TLNs to extend the VIKOR approach to evaluate human factors in a construction project. The remainder of this article is mainly as follows: Section 2: some basic definitions of PI2TLNs; Section 3: the extending VIKOR method with PI2TLNs; Section 4: A case study of evaluating human factors in the process of construction project management and contrastive analysis; Section 5: conclusions.

## 2 Preliminaries

### 2.1 Pythagorean interval 2-tuple linguistic sets

Wei, Lu, Alsaadi, Hayat and Alsaedi [65]proposed the Pythagorean interval 2-tuple linguistic sets (PI2TLSs) based on the PFSs[75] and 2-tuple linguistic information [20].

**Definition 2.1.** [64] *A PI2TLS A in X is given*

$$A = \{ [(\varphi(x), \rho(x)), (\phi(x), \sigma(x))], (u_A(x), \nu_A(x)), x \in X \}. \tag{1}$$

Where  $[(\varphi(x), \rho(x)), (\phi(x), \sigma(x))]$  is an interval 2-tuple linguistic variable,  $\varphi(x), \phi(x) \in S, S = \{S_0, S_1 \dots S_T\}$  is a linguistic term set and  $\rho(x), \sigma(x) \in [-0.5, 0.5], u_A(x), \nu_A(x) \in [0, 1]$  represent the degree of membership and degree of non-membership of the element  $x$  to an interval 2-tuple linguistic  $[(\varphi(x), \rho(x)), (\phi(x), \sigma(x))]$ . Then for  $x \in X, \pi_A(x) = \sqrt{1 - (u_A(x))^2 - (\nu_A(x))^2}$ . When  $(\varphi_A, \rho_A) = (\phi_A, \sigma_A)$  then the Pythagorean interval 2-tuple linguistic sets (PI2TLSs) reduce to Pythagorean 2-tuple linguistic sets(P2TLSs). For conveniences sake,  $A = \langle [(\varphi_A, \rho_A), (\phi_A, \sigma_A)], (u_A, \nu_A) \rangle$  can be called a Pythagorean interval 2-tuple linguistic number (PI2TLN).

**Definition 2.2.** [64] *Given  $\tilde{a} = \langle [(\varphi_a, \rho_a), (\phi_a, \sigma_a)], (u_a, \nu_a) \rangle$  is a PI2TLN, the score function of PI2TLN can be depicted as follows:*

$$Sf(\tilde{a}) = \Delta \left( \frac{\Delta^{-1}(\varphi_a, \rho_a) + \Delta^{-1}(\phi_a, \sigma_a)}{2} \times \frac{1 + (u_a)^2 - (\nu_a)^2}{2} \right). \tag{2}$$

**Definition 2.3.** [64] *Given  $\tilde{a} = \langle [(\varphi_a, \rho_a), (\phi_a, \sigma_a)], (u_a, \nu_a) \rangle$  is a PI2TLN, the accuracy function of PI2TLN can be depicted as follows:*

$$Af(\tilde{a}) = \Delta \left( \frac{\Delta^{-1}(\varphi_a, \rho_a) + \Delta^{-1}(\phi_a, \sigma_a)}{2} \times \frac{(u_a)^2 + (\nu_a)^2}{2} \right). \tag{3}$$

**Definition 2.4.** [64] *Given  $\tilde{a}_1 = \langle [(\varphi_{a_1}, \rho_{a_1}), (\phi_{a_1}, \sigma_{a_1})], (u_{a_1}, \nu_{a_1}) \rangle$  and  $\tilde{a}_2 = \langle [(\varphi_{a_2}, \rho_{a_2}), (\phi_{a_2}, \sigma_{a_2})], (u_{a_2}, \nu_{a_2}) \rangle$  are two PI2TLNs. Respectively, the scores of  $\tilde{a}_1$  and  $\tilde{a}_2$  are*

$$Sf(\tilde{a}_1) = \Delta \left( \frac{\Delta^{-1}(\varphi_{a_1}, \rho_{a_1}) + \Delta^{-1}(\phi_{a_1}, \sigma_{a_1})}{2} \times \frac{1 + (u_{a_1})^2 - (\nu_{a_1})^2}{2} \right),$$

and

$$Sf(\tilde{a}_2) = \Delta \left( \frac{\Delta^{-1}(\varphi_{a_2}, \rho_{a_2}) + \Delta^{-1}(\phi_{a_2}, \sigma_{a_2})}{2} \times \frac{1 + (u_{a_2})^2 - (\nu_{a_2})^2}{2} \right),$$

and let

$$Af(\tilde{a}_1) = \Delta \left( \frac{\Delta^{-1}(\varphi_{a_1}, \rho_{a_1}) + \Delta^{-1}(\phi_{a_1}, \sigma_{a_1})}{2} \times \frac{(u_{a_1})^2 + (\nu_{a_1})^2}{2} \right),$$

and

$$Af(\tilde{a}_2) = \Delta \left( \frac{\Delta^{-1}(\varphi_{a_2}, \rho_{a_2}) + \Delta^{-1}(\phi_{a_2}, \sigma_{a_2})}{2} \times \frac{(u_{a_2})^2 + (\nu_{a_2})^2}{2} \right),$$

be the accuracy degrees of  $\tilde{a}_1$  and  $\tilde{a}_2$ , then some operational laws of PI $\mathcal{I}$ TLNs can be defined as follows:

- (1) if  $Sf(\tilde{a}_1) < Sf(\tilde{a}_2)$ , then  $\tilde{a}_1 < \tilde{a}_2$ ;
- (2) if  $Sf(\tilde{a}_1) > Sf(\tilde{a}_2)$ , then  $\tilde{a}_1 > \tilde{a}_2$ ;
- (3) if  $Sf(\tilde{a}_1) = Sf(\tilde{a}_2)$ ,  $Af(\tilde{a}_1) < Af(\tilde{a}_2)$ , then  $\tilde{a}_1 < \tilde{a}_2$ ;
- (4) if  $Sf(\tilde{a}_1) = Sf(\tilde{a}_2)$ ,  $Af(\tilde{a}_1) > Af(\tilde{a}_2)$ , then  $\tilde{a}_1 > \tilde{a}_2$ ;
- (5) if  $Sf(\tilde{a}_1) = Sf(\tilde{a}_2)$ ,  $Af(\tilde{a}_1) = Af(\tilde{a}_2)$ , then  $\tilde{a}_1 = \tilde{a}_2$ ;

**Definition 2.5.** [64] Given  $\tilde{a}_1 = \langle [(\varphi_{a_1}, \rho_{a_1}), (\phi_{a_1}, \sigma_{a_1})], (u_{a_1}, v_{a_1}) \rangle$  and  $\tilde{a}_2 = \langle [(\varphi_{a_2}, \rho_{a_2}), (\phi_{a_2}, \sigma_{a_2})], (u_{a_2}, v_{a_2}) \rangle$  are two PI $\mathcal{I}$ TLNs, the normalized Hamming distance ( $H_d$ ) between  $\tilde{a}_1$  and  $\tilde{a}_2$  can be depicted below:

$$H_d(\tilde{a}_1, \tilde{a}_2) = \frac{1}{4L} \left[ \left| \begin{array}{l} \left( 1 + (u_{a_1})^2 - (v_{a_1})^2 \right) \cdot \left( \Delta^{-1}(\varphi_{a_1}, \rho_{a_1}) + \Delta^{-1}(\phi_{a_1}, \sigma_{a_1}) \right) - \\ \left( 1 + (u_{a_2})^2 - (v_{a_2})^2 \right) \cdot \left( \Delta^{-1}(\varphi_{a_2}, \rho_{a_2}) + \Delta^{-1}(\phi_{a_2}, \sigma_{a_2}) \right) \end{array} \right| \right], \quad (4)$$

where  $L$  represents the length of the language scale. It is a numerical value.

**Definition 2.6.** [64] Given  $\tilde{a}_1 = \langle [(\varphi_{a_1}, \rho_{a_1}), (\phi_{a_1}, \sigma_{a_1})], (u_{a_1}, v_{a_1}) \rangle$  and  $\tilde{a}_2 = \langle [(\varphi_{a_2}, \rho_{a_2}), (\phi_{a_2}, \sigma_{a_2})], (u_{a_2}, v_{a_2}) \rangle$  are two PI $\mathcal{I}$ TLNs, then

$$\begin{aligned} \tilde{a}_1 \oplus \tilde{a}_2 &= \left\langle \left[ \begin{array}{l} \Delta \left( \Delta^{-1}(\varphi_{a_1}, \rho_{a_1}) + \Delta^{-1}(\varphi_{a_2}, \rho_{a_2}) \right), \\ \Delta \left( \Delta^{-1}(\phi_{a_1}, \sigma_{a_1}) + \Delta^{-1}(\phi_{a_2}, \sigma_{a_2}) \right) \end{array} \right], \left( \sqrt{(u_{a_1})^2 + (u_{a_2})^2 - (u_{a_1})^2(u_{a_2})^2}, \nu_{a_1}\nu_{a_2} \right) \right\rangle; \\ \tilde{a}_1 \otimes \tilde{a}_2 &= \left\langle \left[ \begin{array}{l} \Delta \left( \Delta^{-1}(\varphi_{a_1}, \rho_{a_1}) \times \Delta^{-1}(\varphi_{a_2}, \rho_{a_2}) \right), \\ \Delta \left( \Delta^{-1}(\phi_{a_1}, \sigma_{a_1}) \times \Delta^{-1}(\phi_{a_2}, \sigma_{a_2}) \right) \end{array} \right], \left( u_{a_1}u_{a_2}, \sqrt{(\nu_{a_1})^2 + (\nu_{a_2})^2 - (\nu_{a_1})^2(\nu_{a_2})^2} \right) \right\rangle; \\ \lambda \tilde{a}_1 &= \left\langle \left[ \begin{array}{l} \Delta \left( \lambda \Delta^{-1}(\varphi_{a_1}, \rho_{a_1}) \right), \\ \Delta \left( \lambda \Delta^{-1}(\phi_{a_1}, \sigma_{a_1}) \right) \end{array} \right], \left( \sqrt{1 - (1 - (u_{a_1})^2)^\lambda}, (\nu_{a_1})^\lambda \right) \right\rangle; \\ (\tilde{a}_1)^\lambda &= \left\langle \left[ \begin{array}{l} \Delta \left( (\Delta^{-1}(\varphi_{a_1}, \rho_{a_1}))^\lambda \right), \\ \Delta \left( (\Delta^{-1}(\phi_{a_1}, \sigma_{a_1}))^\lambda \right) \end{array} \right], \left( (u_{a_1})^\lambda \sqrt{1 - (1 - (\nu_{a_1})^2)^\lambda} \right) \right\rangle. \end{aligned}$$

**Theorem 2.7.** [64] For any two PI $\mathcal{I}$ TLNs  $\tilde{a}_1 = \langle [(\varphi_{a_1}, \rho_{a_1}), (\phi_{a_1}, \sigma_{a_1})], (u_{a_1}, v_{a_1}) \rangle$  and  $\tilde{a}_2 = \langle [(\varphi_{a_2}, \rho_{a_2}), (\phi_{a_2}, \sigma_{a_2})], (u_{a_2}, v_{a_2}) \rangle$ , According to the Definition 6, naturally, we can get the following properties of the operation laws:

$$\begin{aligned} \tilde{a}_1 \oplus \tilde{a}_2 &= \tilde{a}_2 \oplus \tilde{a}_1, \\ \tilde{a}_1 \otimes \tilde{a}_2 &= \tilde{a}_2 \otimes \tilde{a}_1, \\ k(\tilde{a}_1 \oplus \tilde{a}_2) &= k\tilde{a}_1 \oplus k\tilde{a}_2, 0 \leq k \leq 1, \\ k_1\tilde{a}_1 \oplus k_2\tilde{a}_1 &= (k_1 \oplus k_2)\tilde{a}_1, 0 \leq k_1, k_2, k_1 + k_2 \leq 1, \\ \tilde{a}_1^{k_1} \otimes \tilde{a}_1^{k_2} &= (\tilde{a}_1)^{k_1+k_2}, 0 \leq k_1, k_2, k_1 + k_2 \leq 1, \\ \tilde{a}_1^{k_1} \otimes \tilde{a}_2^{k_2} &= (\tilde{a}_1 \otimes \tilde{a}_2)^{k_1}, k_1 \geq 0, \\ \left( (\tilde{a}_1)^{k_1} \right)^{k_2} &= (\tilde{a}_1)^{k_1k_2}, \end{aligned}$$

## 2.2 Pythagorean interval 2-tuple linguistic arithmetic aggregation operators

In this section, some arithmetic aggregation operators with Pythagorean interval 2-tuple linguistic information will be introduced[65], such as Pythagorean interval 2-tuple linguistic weighted averaging (PI $\mathcal{I}$ TLWA) operator and Pythagorean interval 2-tuple linguistic weighted geometric (PI $\mathcal{I}$ TLWG) operator.

**Definition 2.8.** [64] Assume that  $\tilde{a}_j = \langle [(\varphi_{a_j}, \rho_{a_j}), (\phi_{a_j}, \sigma_{a_j})], (u_{a_j}, v_{a_j}) \rangle$  ( $j = 1, 2, \dots, n$ ) is a collection of PI $\mathcal{I}$ TLNs. PI $\mathcal{I}$ TLWA operator can be depicted as follows:

$$\text{PI}\mathcal{I}\text{TLWA}_\omega(\tilde{a}_1, \tilde{a}_2, \dots, \tilde{a}_n) = \bigoplus_{j=1}^n (\omega_j \tilde{a}_j) = \left\langle \left[ \begin{array}{l} \Delta \left( \sum_{j=1}^n \omega_j \Delta^{-1}(\varphi_{a_j}, \rho_{a_j}) \right), \\ \Delta \left( \sum_{j=1}^n \omega_j \Delta^{-1}(\phi_{a_j}, \sigma_{a_j}) \right) \end{array} \right], \left( \sqrt{1 - \prod_{j=1}^n (1 - (u_{a_j})^2)^{\omega_j}}, \prod_{j=1}^n (\nu_{a_j})^{\omega_j} \right) \right\rangle, \quad (5)$$

where  $\omega = (\omega_1, \omega_2, \dots, \omega_n)^T$  is the weight vector of  $\tilde{a}_j$  ( $j = 1, 2, \dots, n$ ) and  $\omega_j > 0, \sum_{j=1}^n \omega_j = 1$ .

**Definition 2.9.** [64] Assume that  $\tilde{a}_j = \langle [(\varphi_{a_j}, \rho_{a_j}), (\phi_{a_j}, \sigma_{a_j})], (u_{a_j}, v_{a_j}) \rangle$  ( $j = 1, 2, \dots, n$ ) is a collection of PI2TLNs. PI2TLWG operator can be depicted as follows:

$$PI2TLWG_{\omega}(\tilde{a}_1, \tilde{a}_2, \dots, \tilde{a}_n) = \bigotimes_{j=1}^n (\omega_j \tilde{a}_j) = \left\langle \left[ \begin{array}{c} \Delta \left( \prod_{j=1}^n \Delta^{-1}(\varphi_{a_j}, \rho_{a_j})^{\omega_j} \right) \\ \Delta \left( \prod_{j=1}^n \Delta^{-1}(\phi_{a_j}, \sigma_{a_j})^{\omega_j} \right) \end{array} \right], \left( \prod_{j=1}^n (u_{a_j})^{\omega_j} \sqrt{1 - \prod_{j=1}^n (1 - (v_{a_j})^2)^{\omega_j}} \right) \right\rangle, \tag{6}$$

where  $\omega = (\omega_1, \omega_2, \dots, \omega_n)^T$  is the weight vector of  $\tilde{a}_j$  ( $j = 1, 2, \dots, n$ ) and  $\omega_j > 0, \sum_{j=1}^n \omega_j = 1$ .

### 3 VIKOR method for PI2TL MADM problems

Suppose that  $\Theta_i = \{\Theta_1, \Theta_2, \dots, \Theta_m\}$  and  $\xi_j = \{\xi_1, \xi_2, \dots, \xi_n\}$  are respectively  $m$  alternatives and  $n$  criteria. Let  $\omega = \{\omega_1, \omega_2, \dots, \omega_n\}$  be the criterias weighting vector which satisfies  $\omega_j \in [0, 1]$  and  $\sum_{j=1}^n \omega_j = 1$ . Let  $\Psi = \{\Psi_1, \Psi_2, \dots, \Psi_k\}$  be the group of DMS,  $w = \{w_1, w_2, \dots, w_k\}$  be the weight of DMS, with  $w = \{w_1, w_2, \dots, w_k\}$  and  $\sum_{t=1}^k w_t = 1$ . Construct a decision matrix  $R^{(t)} = (r_{ij}^{(t)})_{m \times n}$ , where  $R^{(t)} = (r_{ij}^{(t)})_{m \times n} = \langle [(\varphi_{r_{ij}}^{(t)}, \rho_{r_{ij}}^{(t)}), (\phi_{r_{ij}}^{(t)}, \sigma_{r_{ij}}^{(t)})], (u_{r_{ij}}^{(t)}, v_{r_{ij}}^{(t)}) \rangle_{m \times n}$ , means the performance of the alternative  $\Theta_i$  ( $i = 1, 2, \dots, m$ ) with respect to criteria  $\xi_j$  ( $j = 1, 2, \dots, n$ ) by expert  $\Psi^{(t)}$  ( $t = 1, 2, \dots, k$ ) using a PI2TLN,  $0 \leq u_{r_{ij}}^{(t)} \leq 1, 0 \leq v_{r_{ij}}^{(t)} \leq 1$  and  $0 \leq (u_{r_{ij}}^{(t)})^2 + (v_{r_{ij}}^{(t)})^2 \leq 1, i = 1, 2, \dots, m, j = 1, 2, \dots, n, t = 1, 2, \dots, k$ .

According to the PI2TLNs theory and steps in the VIKOR method, a PI2TLN-VIKOR method is proposed to effectively deal with the MADM problem. The new model is as follows:

**Step 1.** Set up a decision-making group composed of several experts, choose the best attributes to measure alternatives, and finally get a series of PI2TL fuzzy decision matrix  $R^{(t)} = (r_{ij}^{(t)})_{m \times n}$  from each decision maker.

$$R^{(t)} = [r_{ij}^{(t)}]_{m \times n} = \begin{bmatrix} r_{11}^{(t)} & r_{12}^{(t)} & \dots & r_{1n}^{(t)} \\ r_{21}^{(t)} & r_{22}^{(t)} & \dots & r_{2n}^{(t)} \\ \vdots & \vdots & \vdots & \vdots \\ r_{m1}^{(t)} & r_{m2}^{(t)} & \dots & r_{mn}^{(t)} \end{bmatrix}, \tag{7}$$

where  $r_{ij}^{(t)}$  denotes the fuzzy performance value of  $i$ -th alternative ( $i = 1, 2, \dots, m$ ) with respect to  $j$ -th criterion ( $j = 1, 2, \dots, n$ ) and decision-maker ( $t = 1, 2, \dots, k$ ).

**Step 2.** Utilize PI2TLWA operator or PI2TLWG operator to fuse assessment information, then the group PI2TL fuzzy decision matrix  $R = (r_{ij})_{m \times n}$  can be obtained by the calculation.

$$R = [r_{ij}]_{m \times n} = \begin{bmatrix} r_{11} & r_{12} & \dots & r_{1n} \\ r_{21} & r_{22} & \dots & r_{2n} \\ \vdots & \vdots & \vdots & \vdots \\ r_{m1} & r_{m2} & \dots & r_{mn} \end{bmatrix}, \tag{8}$$

$$r_{ij} = \bigoplus_{t=1}^k r_{ij}^{(k)} = PI2TLWA(r_{ij}^{(1)}, r_{ij}^{(2)}, \dots, r_{ij}^{(k)}) \\ = \left\langle \left[ \begin{array}{c} \Delta \left( \sum_{t=1}^k \omega_t \Delta^{-1}(\varphi_{r_{ij}}^{(t)}, \rho_{r_{ij}}^{(t)}) \right) \\ \Delta \left( \sum_{t=1}^k \omega_t \Delta^{-1}(\phi_{r_{ij}}^{(t)}, \sigma_{r_{ij}}^{(t)}) \right) \end{array} \right], \left( \sqrt{1 - \prod_{t=1}^k (1 - (u_{r_{ij}}^{(t)})^2)^{\omega_t}}, \prod_{t=1}^k (v_{r_{ij}}^{(t)})^{\omega_t} \right) \right\rangle, \tag{9}$$

or

$$r_{ij} = \bigotimes_{t=1}^k r_{ij}^{(k)} = PI2TLWG(r_{ij}^{(1)}, r_{ij}^{(2)}, \dots, r_{ij}^{(k)}) \\ = \left\langle \left[ \begin{array}{c} \Delta \left( \prod_{t=1}^k \Delta^{-1}(\varphi_{r_{ij}}^{(t)}, \rho_{r_{ij}}^{(t)})^{\omega_t} \right) \\ \Delta \left( \prod_{t=1}^k \Delta^{-1}(\phi_{r_{ij}}^{(t)}, \sigma_{r_{ij}}^{(t)})^{\omega_t} \right) \end{array} \right], \left( \prod_{t=1}^k (u_{r_{ij}}^{(t)})^{\omega_t}, \sqrt{1 - \prod_{t=1}^k (1 - (v_{r_{ij}}^{(t)})^2)^{\omega_t}} \right) \right\rangle, \tag{10}$$

where  $r_{ij}$  means the average fuzzy performance value of  $i$ -th alternative in relative to  $j$ -th criterion.

**Step 3.** Determine the positive ideal solutions  $R_j^+$  and  $R_j^-$  negative ideal solutions

$$R_j^+ = \left\{ \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right\}, \quad (11)$$

$$R_j^- = \left\{ \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right\}, \quad (12)$$

For all benefit criteria:

$$\left\{ \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right\} = \left\{ \left[ \begin{array}{l} \max(\Delta^{-1}(\varphi_{a_j}, \rho_{a_j})) \\ \max(\Delta^{-1}(\phi_{a_j}, \sigma_{a_j})) \end{array} \right], (\max(u_{a_j}), \min(v_{a_j})) \right\}, \quad (13)$$

$$\left\{ \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right\} = \left\{ \left[ \begin{array}{l} \min(\Delta^{-1}(\varphi_{a_j}, \rho_{a_j})) \\ \min(\Delta^{-1}(\phi_{a_j}, \sigma_{a_j})) \end{array} \right], (\min(u_{a_j}), \max(v_{a_j})) \right\}. \quad (14)$$

For all cost criteria:

$$\left\{ \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right\} = \left\{ \left[ \begin{array}{l} \min(\Delta^{-1}(\varphi_{a_j}, \rho_{a_j})) \\ \min(\Delta^{-1}(\phi_{a_j}, \sigma_{a_j})) \end{array} \right], (\min(u_{a_j}), \max(v_{a_j})) \right\}. \quad (15)$$

$$\left\{ \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right\} = \left\{ \left[ \begin{array}{l} \max(\Delta^{-1}(\varphi_{a_j}, \rho_{a_j})) \\ \max(\Delta^{-1}(\phi_{a_j}, \sigma_{a_j})) \end{array} \right], (\max(u_{a_j}), \min(v_{a_j})) \right\}. \quad (16)$$

**Step 4.** Calculate  $S_i$  and  $P_i$  values using the following equations:

$$S_i = \sum_{j=1}^n \omega_j \frac{H_d \left( \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right), \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right) \right)}{H_d \left( \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right), \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right) \right)}, \quad (17)$$

$$P_i = \max \left\{ \omega_j \frac{H_d \left( \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right), \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right) \right)}{H_d \left( \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^+ \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^+ \end{array} \right], (u_{a_j}^+, v_{a_j}^+) \right), \left( \left[ \begin{array}{l} (\Delta^{-1}(\varphi_{a_j}, \rho_{a_j}))^- \\ (\Delta^{-1}(\phi_{a_j}, \sigma_{a_j}))^- \end{array} \right], (u_{a_j}^-, v_{a_j}^-) \right) \right)} \right\}, \quad (18)$$

here  $d$  denotes the normalized Hamming distance and  $\omega_j$  means the weight of attributes with these  $0 \leq \omega_j \leq 1$   $\sum_{j=1}^n \omega_j = 1$

**Step 5.** Compute  $Q_i$  values as follows:

$$Q_i = v \frac{S_i - S_i^*}{S_i^- - S_i^*} + (1 - v) \frac{P_i - P_i^*}{P_i^- - P_i^*}. \quad (19)$$

Where

$$S_i^* = \min_i S_i, S_i^- = \max_i S_i. \quad (20)$$

$$P_i^* = \min_i P_i, P_i^- = \max_i P_i. \quad (21)$$

Where  $v$  can be described as the decision-making mechanism coefficient. If  $v > 0.5$ , then it denotes the maximum group utility. If  $v < 0.5$ , then it denotes the minimum regret, and if  $v = 0.5$ , denotes equality.

**Step 6.** According to  $Q_i$  values, rank alternatives and the optimal decision is the alternative with the minimum  $Q$  value.

## 4 Numerical example and comparative analysis

### 4.1 Numerical example

There are many factors that affect the quality of construction projects. In the theory of quality control of construction projects, human factors are the leading, key and the first factor, and also the most difficult to control. Therefore, the evaluation of human factors is conducive to improving the overall quality of construction projects. The issue of evaluating human factors in construction project management is a classical MAGDM issue [18, 32, 53, 62, 66, 69, 71, 72].

In this section, we shall provide a numerical example to evaluate human factors in the process of construction project management by using PI2TL-VIKOR model. Assume that five possible construction projects  $\Theta_i$  ( $i = 1, 2, 3, 4, 5$ ) to be selected and four evaluation criteria  $\xi_j$  ( $j = 1, 2, 3, 4$ ) to evaluate these construction projects:

- (1)  $\xi_1$  is the workers proficiency;
- (2)  $\xi_2$  is the workers safety awareness;
- (3)  $\xi_3$  is the technical workers quality;
- (4)  $\xi_4$  is the workers emergency capacity.

The five possible construction projects  $\Theta_i$  ( $i = 1, 2, 3, 4, 5$ ) are to be evaluated through using PI2TLNs with the four criteria by three experts  $\Psi^k$  (experts weight  $w = (0.35, 0.37, 0.28)$ , attributes weight  $\omega = (0.28, 0.29, 0.23, 0.20)^T$ ).

**Step 1.** Construct the evaluation matrix  $R^{(3)} = (r_{ij}^3)_{5 \times 4}$  ( $i = 1, 2, \dots, 5, j = 1, 2, \dots, 4$ ) of each decision-maker as in Table 1-3. Based on table 1-3 and Equations (9), the group Pythagorean interval 2-tuple linguistic fuzzy decision matrix is computed. Table 4 shows the results.

Table 1: Rating alternatives on each criterion by  $\Psi_1$

	$\xi_1$	$\xi_2$
$\Theta_1$	$\langle [(S2, 0), (S4, 0)], (0.3, 0.7) \rangle$	$\langle [(S5, 0), (S2, 0)], (0.6, 0.3) \rangle$
$\Theta_2$	$\langle [(S3, 0), (S2, 0)], (0.8, 0.3) \rangle$	$\langle [(S3, 0), (S4, 0)], (0.6, 0.5) \rangle$
$\Theta_3$	$\langle [(S4, 0), (S3, 0)], (0.5, 0.6) \rangle$	$\langle [(S1, 0), (S0, 0)], (0.3, 0.8) \rangle$
$\Theta_4$	$\langle [(S3, 0), (S2, 0)], (0.6, 0.1) \rangle$	$\langle [(S2, 0), (S4, 0)], (0.2, 0.9) \rangle$
$\Theta_5$	$\langle [(S1, 0), (S3, 0)], (0.3, 0.6) \rangle$	$\langle [(S2, 0), (S5, 0)], (0.5, 0.7) \rangle$
	$\xi_3$	$\xi_4$
$\Theta_1$	$\langle [(S5, 0), (S2, 0)], (0.8, 0.5) \rangle$	$\langle [(S1, 0), (S3, 0)], (0.5, 0.1) \rangle$
$\Theta_2$	$\langle [(S5, 0), (S3, 0)], (0.8, 0.7) \rangle$	$\langle [(S3, 0), (S4, 0)], (0.7, 0.4) \rangle$
$\Theta_3$	$\langle [(S3, 0), (S1, 0)], (0.9, 0.1) \rangle$	$\langle [(S3, 0), (S2, 0)], (0.2, 0.4) \rangle$
$\Theta_4$	$\langle [(S5, 0), (S6, 0)], (0.1, 0.3) \rangle$	$\langle [(S5, 0), (S3, 0)], (0.6, 0.5) \rangle$
$\Theta_5$	$\langle [(S2, 0), (S4, 0)], (0.5, 0.1) \rangle$	$\langle [(S3, 0), (S4, 0)], (0.7, 0.1) \rangle$

Table 2: Rating alternatives on each criterion by  $\Psi_2$

	$\xi_1$	$\xi_2$
$\Theta_1$	$\langle [(S1, 0), (S5, 0)], (0.2, 0.3) \rangle$	$\langle [(S2, 0), (S4, 0)], (0.3, 0.5) \rangle$
$\Theta_2$	$\langle [(S3, 0), (S4, 0)], (0.4, 0.5) \rangle$	$\langle [(S1, 0), (S3, 0)], (0.6, 0.5) \rangle$
$\Theta_3$	$\langle [(S4, 0), (S3, 0)], (0.6, 0.5) \rangle$	$\langle [(S3, 0), (S2, 0)], (0.8, 0.5) \rangle$
$\Theta_4$	$\langle [(S3, 0), (S3, 0)], (0.6, 0.8) \rangle$	$\langle [(S1, 0), (S6, 0)], (0.1, 0.5) \rangle$
$\Theta_5$	$\langle [(S4, 0), (S2, 0)], (0.2, 0.9) \rangle$	$\langle [(S5, 0), (S4, 0)], (0.2, 0.3) \rangle$
	$\xi_3$	$\xi_4$
$\Theta_1$	$\langle [(S1, 0), (S4, 0)], (0.7, 0.3) \rangle$	$\langle [(S3, 0), (S4, 0)], (0.1, 0.8) \rangle$
$\Theta_2$	$\langle [(S2, 0), (S2, 0)], (0.7, 0.8) \rangle$	$\langle [(S4, 0), (S4, 0)], (0.4, 0.7) \rangle$
$\Theta_3$	$\langle [(S5, 0), (S6, 0)], (0.9, 0.6) \rangle$	$\langle [(S3, 0), (S5, 0)], (0.1, 0.6) \rangle$
$\Theta_4$	$\langle [(S4, 0), (S3, 0)], (0.6, 0.4) \rangle$	$\langle [(S2, 0), (S6, 0)], (0.4, 0.3) \rangle$
$\Theta_5$	$\langle [(S2, 0), (S1, 0)], (0.2, 0.2) \rangle$	$\langle [(S3, 0), (S5, 0)], (0.4, 0.8) \rangle$

Table 3: Rating alternatives on each criterion by  $\Psi_3$

	$\xi_1$	$\xi_2$
$\Theta_1$	$\langle [(S2, 0), (S2, 0)], (0.8, 0.6) \rangle$	$\langle [(S3, 0), (S4, 0)], (0.5, 0.7) \rangle$
$\Theta_2$	$\langle [(S5, 0), (S2, 0)], (0.7, 0.3) \rangle$	$\langle [(S5, 0), (S2, 0)], (0.1, 0.4) \rangle$
$\Theta_3$	$\langle [(S3, 0), (S5, 0)], (0.7, 0.6) \rangle$	$\langle [(S5, 0), (S4, 0)], (0.2, 0.4) \rangle$
$\Theta_4$	$\langle [(S2, 0), (S3, 0)], (0.4, 0.6) \rangle$	$\langle [(S4, 0), (S5, 0)], (0.5, 0.6) \rangle$
$\Theta_5$	$\langle [(S1, 0), (S4, 0)], (0.3, 0.1) \rangle$	$\langle [(S1, 0), (S3, 0)], (0.7, 0.5) \rangle$
	$\xi_3$	$\xi_4$
$\Theta_1$	$\langle [(S2, 0), (S3, 0)], (0.8, 0.4) \rangle$	$\langle [(S2, 0), (S4, 0)], (0.1, 0.2) \rangle$
$\Theta_2$	$\langle [(S1, 0), (S1, 0)], (0.4, 0.4) \rangle$	$\langle [(S2, 0), (S5, 0)], (0.6, 0.4) \rangle$
$\Theta_3$	$\langle [(S5, 0), (S4, 0)], (0.8, 0.3) \rangle$	$\langle [(S3, 0), (S1, 0)], (0.4, 0.1) \rangle$
$\Theta_4$	$\langle [(S3, 0), (S2, 0)], (0.8, 0.8) \rangle$	$\langle [(S1, 0), (S4, 0)], (0.3, 0.5) \rangle$
$\Theta_5$	$\langle \langle [(S5, 0), (S1, 0)], (0.5, 0.6) \rangle$	$\langle [(S1, 0), (S2, 0)], (0.4, 0.5) \rangle \rangle$

Table 4: Rating alternatives on each criterion by  $\Psi_4$

	$\xi_1$	$\xi_2$
$\Theta_1$	$\langle [(S2, -0.37), (S4, -0.19)], (0.533, 0.5552) \rangle$	$\langle [(S3, 0.33), (S3, 0.3)], (0.4877, 0.7002) \rangle$
$\Theta_2$	$\langle [(S4, -0.44), (S3, -0.26)], (0.676, 0.5523) \rangle$	$\langle [(S3, -0.18), (S3, 0.07)], (0.5262, 0.5987) \rangle$
$\Theta_3$	$\langle [(S4, -0.28), (S4, -0.44)], (0.6043, 0.6707) \rangle$	$\langle [(S3, -0.14), (S2, -0.14)], (0.587, 0.5987) \rangle$
$\Theta_4$	$\langle [(S3, -0.28), (S3, -0.35)], (0.5562, 0.798) \rangle$	$\langle [(S2, 0.19), (S5, 0.02)], (0.3064, 0.6707) \rangle$
$\Theta_5$	$\langle [(S2, 0.11), (S3, -0.09)], (0.268, 0.5047) \rangle$	$\langle [(S3, -0.17), (S4, 0.07)], (0.5122, 0.5275) \rangle$
	$\xi_3$	$\xi_4$
$\Theta_1$	$\langle [(S3, -0.32), (S3, 0.02)], (0.7684, 0.4956) \rangle$	$\langle [(S2, 0.02), (S4, -0.35)], (0.3189, 0.5867) \rangle$
$\Theta_2$	$\langle [(S3, -0.23), (S2, 0.07)], (0.6934, 0.7124) \rangle$	$\langle [(S3, 0.09), (S4, 0.28)], (0.5885, 0.6781) \rangle$
$\Theta_3$	$\langle [(S4, 0.3), (S4, -0.31)], (0.8791, 0.5909) \rangle$	$\langle [(S3, 0), (S3, -0.17)], (0.2542, 0.4344) \rangle$
$\Theta_4$	$\langle [(S4, 0.07), (S4, -0.23)], (0.6045, 0.6693) \rangle$	$\langle [(S3, -0.23), (S4, 0.39)], (0.4679, 0.5275) \rangle$
$\Theta_5$	$\langle [(S3, -0.16), (S2, 0.05)], (0.4222, 0.4778) \rangle$	$\langle [(S2, 0.44), (S4, -0.19)], (0.5428, 0.7583) \rangle$

**Step 2.** Determine the and by Equations (13) and (14).

$$R_j^+ = \left\{ \begin{array}{l} \langle [(S4, -0.28), (S4, -0.19)], (0.676, 0.5047) \rangle \\ \langle [(S3, 0.33), (S5, 0.02)], (0.587, 0.5275) \rangle \\ \langle [(S4, 0.3), (S4, -0.23)], (0.8791, 0.4778) \rangle \\ \langle [(S3, 0.09), (S4, 0.39)], (0.5885, 0.4344) \rangle \end{array} \right\}.$$

$$R_j^- = \left\{ \begin{array}{l} \langle [(S2, -0.37), (S3, -0.35)], (0.268, 0.798) \rangle \\ \langle [(S2, 0.19), (S2, -0.14)], (0.3064, 0.7002) \rangle \\ \langle [(S3, -0.32), (S4, 0.05)], (0.4222, 0.7124) \rangle \\ \langle [(S2, 0.02), (S3, -0.17)], (0.2542, 0.7583) \rangle \end{array} \right\}.$$

**Step 3.** Compute  $S_i$  and  $P_i$  values by Equation (17) and (18).

$$S_1 = 0.5807, S_2 = 0.4863, S_3 = 0.4238, S_4 = 0.5948, S_5 = 0.6136.$$

$$P_1 = 0.1772, P_2 = 0.1919, P_3 = 0.1908, P_4 = 0.2119, P_5 = 0.1935.$$

**Step 4.** Calculate  $Q_i$  values as follows (Let  $v = 0.4$ ):

$$Q_1 = 0.3305, Q_2 = 0.3863, Q_3 = 0.2345, Q_4 = 0.9604, Q_5 = 0.6827.$$

**Step 5.** According to the order of  $Q_i$  values, the smaller the  $Q_i$  values, the better the evaluation of human factors of the construction project. Therefore the ranking is  $\Theta_3 > \Theta_1 > \Theta_2 > \Theta_5 > \Theta_4$  and  $\Theta_3$  is the best.



## 4.2 Comparative analyses

In this part, we compare the proposed PI2TLN-VIKOR model with other methods, the PI2TLWA and PI2TLWG operators [64] and PI2TL-TODIM method proposed by Wei, Gao, Wang and Huang [64].

The comparison results of different methods are as follows.

Table 5: Rank of Alternatives

Methods	Order
PI2TLWA	$\Theta_3 > \Theta_2 > \Theta_1 > \Theta_4 > \Theta_5$
PI2TLWG	$\Theta_3 > \Theta_2 > \Theta_1 > \Theta_4 > \Theta_5$
PI2TLN-TODIM	$\Theta_3 > \Theta_2 > \Theta_4 > \Theta_1 > \Theta_5$
PI2TLN-VIKOR	$\Theta_3 > \Theta_1 > \Theta_2 > \Theta_5 > \Theta_4$

Discussion:

From the above comparison results, we can draw two conclusions. First, the comparison with PI2TLWA/PI2TLWG, the two original operators, shows that the ranking results of the alternatives are slightly different, but the best alternative is the same.  $\Theta_3$  is considered to be the best performance in human factor evaluation among the five construction projects, which verifies the stability and accuracy of this method. Second, compared with the traditional PI2TL-TODIM, although the ranking results are slightly inconsistent, the best alternative is also the same. We analyze the difference between the two methods, PI2TL-VIKOR method can reflect the alternatives and the proximity of the positive and negative ideal solution, and at the same time can take the group utility maximization and individual regret minimization into consideration, can fully considering the subjective preferences of decision makers, thus make decisions more reasonable, and PI2TL-TODIM is used to depict the decision-maker of the psychological behavior of the risk, so the PI2TL-VIKOR is more suited for evaluation of human factors in construction project evaluation.

## 5 Conclusions

In the total quality management of construction projects, human factors not only play a leading role in the factors affecting quality, but also the most basic and core factors in the quality assurance system. Therefore, it is particularly important to evaluate human factors in construction projects. The evaluation of human factors in engineering projects is a multi-attribute decision making problem. Therefore, the use of PI2TLNs to express the evaluation information of experts can reflect the uncertain or fuzzy information. Then, a new decision-making method was obtained by combining PI2TLNs with VIKOR, which was applied to the evaluation of human factors of five construction projects to find the construction project with the best performance. The comparative study shows that it is a feasible and effective decision-making method. In the future, this method can be used to deal with other practical decision-making problems, such as the selection of green suppliers [8, 13, 23, 26, 31, 34, 66, 67, 75] and the location of waste disposal station, and so on [38, 50, 76].

## References

- [1] K. T. Atanassov, *Intuitionistic fuzzy sets*, Fuzzy Sets and Systems, **20**(1) (1986), 87-96.
- [2] R. B. Benayoun, B. Roy, B. Sussman, *Electre: Une méthode pour guider le choix en présence de points de vue multiples*, Revue Française d'Informatique et de Recherche Opérationnelle, **3** (1966), 31-56.
- [3] T. K. Biswas, K. Zaman, *A fuzzy-based risk assessment methodology for construction projects under epistemic uncertainty*, International Journal of Fuzzy Systems, **21**(4) (2019), 1221-1240.
- [4] E. Bolturk, *Pythagorean fuzzy CODAS and its application to supplier selection in a manufacturing firm*, Journal of Enterprise Information Management, **31**(4) (2018), 550-564.
- [5] V. Carr, J. H. M. Tah, *A fuzzy approach to construction project risk assessment and analysis: Construction project risk management system*, Advances in Engineering Software, **32**(10-11) (2001), 847-857.
- [6] F. B. Cui, X. Y. You, H. Shi, H. C. Liu, *Optimal siting of electric vehicle charging stations using pythagorean fuzzy VIKOR approach*, Mathematical Problems in Engineering, **2018** (2018), 1-12, <https://doi.org/10.1155/2018/9262067>.

- [7] M. Dagdeviren, I. Yuksel, *Developing a fuzzy analytic hierarchy process (AHP) model for behavior-based safety management*, Information Sciences, **178**(6) (2008), 1717-1733.
- [8] X. M. Deng, H. Gao, *TODIM method for multiple attribute decision making with 2-tuple linguistic Pythagorean fuzzy information*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1769-1780.
- [9] X. M. Deng, G. W. Wei, H. Gao, J. Wang, *Models for safety assessment of construction project with some 2-tuple linguistic pythagorean fuzzy bonferroni mean operators*, IEEE Access, **6** (2018), 52105-52137.
- [10] X. F. Ding, H. C. Liu, *A new approach for emergency decision-making based on zero-sum game with Pythagorean fuzzy uncertain linguistic variables*, International Journal of Intelligent Systems, **34**(7) (2019), 1667-1684.
- [11] H. Garg, *A new generalized Pythagorean fuzzy information aggregation using einstein operations and its application to decision making*, International Journal of Intelligent Systems, **31**(9) (2016), 886-920.
- [12] H. Garg, *A novel correlation coefficients between Pythagorean fuzzy sets and its applications to decision-making processes*, International Journal of Intelligent Systems, **31**(12) (2016), 1234-1252.
- [13] H. Gao, M. Lu, Y. Wei, *Dual hesitant bipolar fuzzy hamacher aggregation operators and their applications to multiple attribute decision making*, Journal of Intelligent and Fuzzy Systems, **37**(4) (2019), 5755-5766.
- [14] H. Gao, L. G. Ran, G. W. Wei, C. Wei, J. Wu, *VIKOR method for MAGDM based on q-rung interval-valued orthopair fuzzy information and its application to supplier selection of medical consumption products*, International Journal of Environmental Research and Public Health, **17**(2) (2020), 525, doi.org/10.3390/ijerph17020525.
- [15] L. Gomes, M. Lima, *TODIM: Basics and application to multicriteria ranking of projects with environmental impacts*, Foundations of Computing and Decision Sciences, **16** (1979), 113-127.
- [16] X. J. Gou, Z. S. Xu, P. J. Ren, *The properties of continuous Pythagorean fuzzy information*, International Journal of Intelligent Systems, **31**(5) (2016), 401-424.
- [17] M. Gul, M. Fatih Ak, A. F. Guneri, *Pythagorean fuzzy VIKOR-based approach for safety risk assessment in mine industry*, Journal of Safety Research, **69** (2019), 135-153.
- [18] V. K. Gupta, J. J. Thakkar, *A quantitative risk assessment methodology for construction project*, Sadhana-Academy Proceedings in Engineering Sciences, **43**(7) (2018), 1-18.
- [19] Y. He, F. Lei, G. W. Wei, R. Wang, J. Wu, C. Wei, *EDAS method for multiple attribute group decision making with probabilistic uncertain linguistic information and its application to green supplier selection*, International Journal of Computational Intelligence Systems, **12**(2) (2019), 1361-1370.
- [20] T. T. He, G. W. Wei, J. P. Lu, C. Wei, R. Lin, *Pythagorean 2-tuple linguistic Taxonomy method for supplier selection in medical instrument industries*, International Journal of Environmental Research and Public Health, **16**(23) (2019), 4875, doi.10.3390/ijerph16234875.
- [21] F. Herrera, L. Martinez, *A 2-tuple fuzzy linguistic representation model for computing with words*, IEEE Transactions on Fuzzy Systems, **8**(6) (2000), 746-752.
- [22] C. L. Y. Hwang, *Multiple attribute decision making*, Economics and Mathematical Systems, Springer-Verlag Berlin Heidelberg, **186** (1981), doi.10.1007/978-3-642-48318-9.
- [23] M. Keshavarz Ghorabae, E. K. Zavadskas, M. Amiri, A. Esmaeili, *Multi-criteria evaluation of green suppliers using an extended WASPAS method with interval type-2 fuzzy sets*, Journal of Cleaner Production, **137** (2016), 213-229.
- [24] F. Lei, G. W. Wei, H. Gao, J. Wu, C. Wei, *TOPSIS method for developing supplier selection with probabilistic linguistic information*, International Journal of Fuzzy Systems, **22**(3) (2020), 749-759.
- [25] F. Lei, G. W. Wei, J. P. Lu, C. Wei, J. Wu, *GRA method for probabilistic linguistic multiple attribute group decision making with incomplete weight information and its application to waste incineration plants location problem*, International Journal of Computational Intelligence Systems, **12**(2) (2019), 1547-1556.

- [26] Z. X. Li, M. Lu, *Some novel similarity and distance and measures of Pythagorean fuzzy sets and their applications*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1781-1799.
- [27] Z. X. Li, G. W. Wei, M. Lu, *Pythagorean fuzzy hamy mean operators in multiple attribute group decision making and their application to supplier selection*, Symmetry-Basel, **10**(10) (2018), 505, doi.org/10.3390/sym10100505.
- [28] Z. X. Li, G. W. Wei, R. Wang, J. Wu, C. Wei, Y. Wei, *EDAS method for multiple attribute group decision making under q-rung orthopair fuzzy environment*, Technological and Economic Development of Economy, **26**(1) (2020), 86-102.
- [29] D. C. Liang, Z. S. Xu, *The new extension of TOPSIS method for multiple criteria decision making with hesitant Pythagorean fuzzy sets*, Applied Soft Computing, **60** (2017), 167-179.
- [30] W. Liang, X. L. Zhang, M. F. Liu, *The maximizing deviation method based on interval-valued Pythagorean fuzzy weighted aggregating operator for multiple criteria group decision analysis*, Discrete Dynamics in Nature and Society, **2015** (2015), 1-15.
- [31] J. J. H. Liou, J. Tamosaitiene, E. K. Zavadskas, G. H. Tzeng, *New hybrid COPRAS-G MADM model for improving and selecting suppliers in green supply chain management*, International Journal of Production Research, **54**(1) (2016), 114-134.
- [32] H. C. Liu, M. Y. Quan, H. Shi, C. Guo, *An integrated MCDM method for robot selection under interval-valued Pythagorean uncertain linguistic environment*, International Journal of Intelligent Systems, **34**(2) (2019), 188-214.
- [33] J. P. Lu, T. T. He, G. W. Wei, J. Wu, C. Wei, *Cumulative prospect theory: Performance evaluation of government purchases of home-based elderly-care services using the Pythagorean 2-tuple linguistic TODIM method*, International Journal of Environmental Research and Public Health, **17**(6) (2020), 1939.
- [34] J. P. Lu, C. Wei, *TODIM method for performance appraisal on social-integration-based rural reconstruction with interval-valued intuitionistic fuzzy information*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1731-1740.
- [35] J. P. Lu, C. Wei, J. Wu, G. W. Wei, *TOPSIS method for probabilistic linguistic MAGDM with entropy weight and its application to supplier selection of new agricultural machinery products*, Entropy, **21**(10) (2019), 953, doi.org/10.3390/e21100953.
- [36] Y. Lu, *Research of models and methods of construction project information management with 2-tuple linguistic information*, Information and International Interdisciplinary Journal, **15**(10) (2012), 3911-3916.
- [37] Z. M. Ma, Z. S. Xu, *Symmetric Pythagorean fuzzy weighted geometric/averaging operators and their application in multicriteria decision-making problems*, International Journal of Intelligent Systems, **31**(12) (2016), 1198-1219.
- [38] A. Mardani, E. K. Zavadskas, Z. Khalifah, N. Zakuan, A. Jusoh, K. M. Nor, M. Khoshnoudi, *A review of multi-criteria decision-making applications to solve energy management problems: Two decades from 1995 to 2015*, Renewable and Sustainable Energy Reviews, **71** (2017), 216-256.
- [39] B. J. P. Mareschal, B. Vincke, P. Prométhée, *A new family of outranking methods in multicriteria analysis*, Operational Research, **3** (1984), 477-490.
- [40] S. Mete, *Assessing occupational risks in pipeline construction using FMEA-based AHP-MOORA integrated approach under Pythagorean fuzzy environment*, Human and Ecological Risk Assessment, **25**(7) (2019), 1645-1660.
- [41] S. Mete, F. Serin, N. E. Oz, M. Gul, *A decision-support system based on Pythagorean fuzzy VIKOR for occupational risk assessment of a natural gas pipeline construction*, Journal of Natural Gas Science and Engineering, **71** (2019), <https://doi.org/10.1016/j.jngse.2019.102979>.
- [42] S. Narayanamoorthy, S. Geetha, R. Rakkiyappan, Y. H. Joo, *Interval-valued intuitionistic hesitant fuzzy entropy based VIKOR method for industrial robots selection*, Expert Systems with Applications, **121** (2019), 28-37.
- [43] S. Opricovic, G. H. Tzeng, *Compromise solution by MCDM methods: A comparative analysis of VIKOR and TOPSIS*, European Journal of Operational Research, **156**(2) (2004), 445-455.
- [44] S. Opricovic, G. H. Tzeng, *Extended VIKOR method in comparison with outranking methods*, European Journal of Operational Research, **178**(2) (2007), 514-529.

- [45] X. D. Peng, Y. Yang, *Some results for Pythagorean fuzzy sets*, International Journal of Intelligent Systems, **30**(11) (2015), 1133-1160.
- [46] X. D. Peng, Y. Yang, *Fundamental properties of interval-valued Pythagorean fuzzy aggregation operators*, International Journal of Intelligent Systems, **31**(5) (2016), 444-487.
- [47] Y. Qin, Y. Liu, Z. Hong, *Multicriteria decision making method based on generalized Pythagorean fuzzy ordered weighted distance measures*, Journal of Intelligent and Fuzzy Systems, **33**(6) (2017), 3665-3675.
- [48] P. Rani, A. R. Mishra, K. R. Pardasani, A. Mardani, H. C. Liao, D. Streimikiene, *A novel VIKOR approach based on entropy and divergence measures of Pythagorean fuzzy sets to evaluate renewable energy technologies in India*, Journal of Cleaner Production, **238** (2019), <https://doi.org/10.1016/j.jclepro.2019.117936>.
- [49] J. Roy, S. Das, S. Kar, D. Pamucar, *An extension of the CODAS approach using interval-valued intuitionistic fuzzy set for sustainable material selection in construction projects with incomplete weight information*, Symmetry-Basel, **11**(3) (2019), 393, doi.10.3390/sym11030393.
- [50] D. Stanujkic, D. Karabasevic, E. K. Zavadskas, F. Smarandache, W. K. M. Brauers, *A bipolar fuzzy extension of the MULTIMOORA method*, Informatica, **30**(1) (2019), 135-152.
- [51] R. Wang, *Research on the application of the financial investment risk appraisal models with some interval number muirhead mean operators*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1741-1752.
- [52] J. Wang, H. Gao, M. Lu, *Approaches to strategic supplier selection under interval neutrosophic environment*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1707-1730.
- [53] H. D. Wang, X. Pan, S. F. He, *A new interval type-2 fuzzy VIKOR method for multi-attribute decision making*, International Journal of Fuzzy Systems, **21**(1) (2019), 145-156.
- [54] B. Wang, J. N. Song, J. Z. Ren, K. X. Li, H. Y. Duan, X. E. Wang, *Selecting sustainable energy conversion technologies for agricultural residues: A fuzzy AHP-VIKOR based prioritization from life cycle perspective*, Resources Conservation and Recycling, **142** (2019), 78-87.
- [55] Q. F. Wang, H. N. Sun, L. D. Zhou, *An intuitionistic fuzzy multi-attribute group decision making method with incomplete weight information based on improved VIKOR*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1639-1647.
- [56] P. Wang, J. Wang, G. W. Wei, *EDAS method for multiple criteria group decision making under 2-tuple linguistic neutrosophic environment*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 1597-1608.
- [57] P. Wang, J. Wang, G. W. Wei, C. Wei, Y. Wei, *The multi-attributive border approximation area comparison (MABAC) for multiple attribute group decision making under 2-tuple linguistic neutrosophic environment*, Informatica, **30**(4) (2019), 799-818.
- [58] J. Wang, G. W. Wei, H. Gao, *Approaches to multiple attribute decision making with interval-valued 2-tuple linguistic Pythagorean fuzzy information*, Mathematics, **6**(10) (2018), 201, doi.org/10.3390/math6100201.
- [59] J. Wang, G. W. Wei, M. Lu, *TODIM method for multiple attribute group decision making under 2-tuple linguistic neutrosophic environment*, Symmetry-Basel, **10**(10) (2018), 486, doi.10.3390/sym10100486.
- [60] J. Wang, G. W. Wei, C. Wei, Y. Wei, *MABAC method for multiple attribute group decision making under q-rung orthopair fuzzy environment*, Defence Technology, **1**(6) (2020), 208-216.
- [61] Z. F. Wang, G. Y. Xu, H. Wang, J. Z. Ren, *Distributed energy system for sustainability transition: A comprehensive assessment under uncertainties based on interval multi-criteria decision making method by coupling interval DEMATEL and interval VIKOR*, Energy, **169** (2019), 750-761.
- [62] L. Wang, H. Y. Zhang, J. Q. Wang, L. Li, *Picture fuzzy normalized projection-based VIKOR method for the risk evaluation of construction project*, Applied Soft Computing, **64** (2018), 216-226.
- [63] G. W. Wei, H. Gao, J. Wang, Y. H. Huang, *Research on risk evaluation of enterprise human capital investment with interval-valued bipolar 2-tuple linguistic information*, IEEE Access, **6** (2018), 35697-35712.

- [64] G. W. Wei, M. Lu, F. E. Alsaadi, T. Hayat, A. Alsaedi, *Pythagorean 2-tuple linguistic aggregation operators in multiple attribute decision making*, Journal of Intelligent and Fuzzy Systems, **33**(2) (2017), 1129-1142.
- [65] G. W. Wei, C. Wei, J. Wu, H. J. Wang, *Supplier selection of medical consumption products with a probabilistic linguistic MABAC method*, International Journal of Environmental Research and Public Health, **16**(24) (2019), 5082, doi.org/10.3390/ijerph16245082.
- [66] G. W. Wei, J. Wu, C. Wei, J. Wang, J. P. Lu, *Models for MADM with 2-tuple linguistic neutrosophic dombi bonferroni mean operators*, IEEE Access, **7** (2019), 108878-108905.
- [67] G. W. Wei, S. Q. Zhang, J. P. Lu, J. Wu, C. Wei, *An extended bidirectional projection method for picture fuzzy MAGDM and its application to safety assessment of construction project*, IEEE Access, **7**(1) (2019), 166138-166147.
- [68] L. P. Wu, H. Gao, C. Wei, *VIKOR method for financing risk assessment of rural tourism projects under interval-valued intuitionistic fuzzy environment*, Journal of Intelligent and Fuzzy Systems, **37**(2) (2019), 2001-2008.
- [69] L. P. Wu, J. Wang, H. Gao, *Models for competitiveness evaluation of tourist destination with some interval-valued intuitionistic fuzzy Hamy mean operators*, Journal of Intelligent and Fuzzy Systems, **36**(6) (2019), 5693-5709.
- [70] L. P. Wu, G. W. Wei, J. Wu, C. Wei, *Some interval-valued intuitionistic fuzzy dombi Heronian mean operators and their application for evaluating the ecological value of forest ecological tourism demonstration areas*, International Journal of Environmental Research and Public Health, **17**(3) (2020), 829.
- [71] Z. B. Wu, J. P. Xu, X. L. Jiang, L. Zhong, *Two MAGDM models based on hesitant fuzzy linguistic term sets with possibility distributions: VIKOR and TOPSIS*, Information Sciences, **473** (2019), 101-120.
- [72] Q. Wu, L. G. Zhou, Y. Chen, H. Y. Chen, *An integrated approach to green supplier selection based on the interval type-2 fuzzy best-worst and extended VIKOR methods*, Information Sciences, **502** (2019), 394-417.
- [73] R. R. Yager, A. M. Abbasov, *Pythagorean membership grades, complex numbers, and decision making*, International Journal of Intelligent Systems, **28**(5) (2013), 436-452.
- [74] W. Yang, Y. F. Pang, *Hesitant interval-valued Pythagorean fuzzy VIKOR method*, International Journal of Intelligent Systems, **34**(5) (2019), 754-789.
- [75] M. Yazdani, S. Hashemkhani Zolfani, E. K. Zavadskas, *New integration of MCDM methods and QFD in the selection of green suppliers*, Journal of Business Economics and Management, **17**(6) (2016), 1097-1113.
- [76] E. K. Zavadskas, Z. Turskis, J. Antucheviciene, *Solution models based on symmetric and asymmetric information*, Symmetry-Basel, **11**(4) (2019), 202 pages.
- [77] S. Z. Zeng, S. M. Chen, L. W. Kuo, *Multiattribute decision making based on novel score function of intuitionistic fuzzy values and modified VIKOR method*, Information Sciences, **488** (2019), 76-92.
- [78] S. Zhang, G. Wei, F. E. Alsaadi, T. Hayat, C. Wei, Z. Zhang, *MABAC method for multiple attribute group decision making under picture 2-tuple linguistic environment*, Soft Computing, **24**(8) (2020), 5819-5829.
- [79] X. L. Zhang, Z. S. Xu, *Extension of TOPSIS to multiple criteria decision making with Pythagorean fuzzy sets*, International Journal of Intelligent Systems, **29**(12) (2014), 1061-1078.

## Pythagorean interval 2-tuple linguistic VIKOR method for evaluating human factors in construction project management

T. He, G. Wei, R. Lin, J. Lu, C. Wei and J. Wu

### روش VIKOR زبان شناختی ۲-تایی بازه‌ای فیثاغورسی جهت ارزیابی فاکتورهای انسانی در مدیریت پروژه ساخت

**چکیده.** در یک پروژه ساخت، فاکتورهای بسیاری چون مردم، مصالح، ماشین آلات، محیط و غیره در کیفیت پروژه مؤثر می‌باشند. در بین آنها، مردم بطور مستقیم یا غیرمستقیم دارای بیشترین تأثیر در کیفیت پروژه می‌باشند. این مقاله بیشتر فاکتورهای انسانی نظیر مهارت کارگران، آگاهی ایمنی کارگران، کیفیت کارگران فنی، و توانایی اورژانسی کارگران را در فرآیند مدیریت پروژه ساخت، با هدف کمک به پروژه ساخت چین جهت اقدام تدریجی ارزیابی می‌کند. در این نوشته، یک تکنیک تصمیم‌گیری گروهی چندجانبه‌ای (MAGDM) براساس اعداد زبان شناختی ۲-تایی بازه‌ای فیثاغورسی (PI 2TLNs) و روش VIKOR، به منظور ارزیابی فاکتورهای انسانی در پروژه ساخت پیشنهاد گردیده‌است. PI 2TLNs جهت برآورد کارایی تصمیم‌گیرنده‌ها بکار برده می‌شوند. با تکیه بر میانگین وزن‌دار زبان شناختی ۲-تایی بازه‌ای فیثاغورسی (PI 2TLNs) / عملگر هندسی وزن‌دار زبان شناختی ۲-تایی بازه‌ای فیثاغورسی (PI 2TLWG)، اطلاعات ارزیابی داده شده توسط متخصصین، در ماتریس تصمیم‌گیری ذوب شده‌است. از ترکیب با روش اصلی VIKOR، چارچوب PI 2TLN-VIKOR بنا شده‌است. مفید بودن این روش توسط یک مثال تأیید شده‌است و با دو روش، الگوریتم و PI 2TLN-TODIM مقایسه شده‌است.