

(تاریخ دریافت ۸۵/۱۲/۲۶ ، تاریخ دریافت روایت اصلاح شده ۸۷/۲/۷ ، تاریخ تصویب ۸۷/۶/۵)

Archive of SID

$MPa$        $mm$        $MPa$        $l$        $mm$   
 $MPa$        $N/m$        $MPa$   
 (FRC)  
 [ ]  
 HPFRCC  
 [ ]      [ - ]      (HPFRCC)      FRC  
 [ ]      Reinhardt      Naaman      HPFRCC  
 ( )      HPFRCC      [ ]      FRC  
 HPFRCC      FRC  
 :       $G_f, f_y, f_{sp}, \sigma_c, D_f, L_f, \nu_f$       HPFRCC  
 .HPFRCC      FRC

**.HPFRCC**

<b>Material</b>	<i>Reference No.</i>	$v_f$ (%)	$L_f$ (mm)	$D_f$ (mm)	$\sigma_c$ (MPa)	$f_{sp}$ (MPa)	$f_r$ (MPa)	$G_f$ (N/m)
CARDIFRC®	[3-5]	6	6(5%) & 13(1%)	0.16	207	25	-	21000
Densit	[1]	6	12	0.4	140	-	-	-
Ductal	[1]	2	13-15	0.2	160-240	-	-	-
RPC	[7]	4	6	0.16	200-800	-	60	45000
SIFCON	[1]	12	30	0.5	56-120	41	90	134000
Torex-HPFRCC	[1]	2	30	0.3	84	-	-	-

II

Seko Dense NSF PCE

/ mm

( )

/ -

/ mm - MPa



( )

	Agg/C	SF/C	Fine Quartz Sand				W/(C+SF)	SP/(C+SF)
			0-300 $\mu\text{m}$	0-0.25 mm	0.25-1 mm	1-4 mm		
RPC	1.1	0.25	100%	---	---	---	0.22	0.019
DSP	1.58	0.25	---	14%	29%	57%	0.15	0.06

		MIX-A1	MIX-A2	MIX-A3	MIX-A4	MIX-A5
	AGG/C	1.1	2	1.1	1.1	1.34
	S.F/C	0.25	0.25	0.15	0.25	0.25
AGGREGATE	50% (0.1-0.25mm)	50% (0.1-0.25mm)	50% (0.1-0.25mm)	50% (0.1-0.25mm)	100% (0-0.6mm)	50% (0-0.3mm)
	50% (0-0.3mm)	50% (0-0.3mm)	50% (0-0.3mm)	50% (0-0.3mm)	----	50% (0.3-1.2mm)
	----	----	----	----	----	----
	----	----	----	----	----	----
(MPa) 7days-20°C		88	61	72	73	73
		MIX-A6	MIX-A7	MIX-A8	MIX-A9	MIX-A10
	AGG/C	1.58	1.58	2.5	2.9	2.9
	S.F/C	0.25	0.15	0.15	0.15	0.15
AGGREGATE	14% (0-0.3mm)	14% (0-0.3mm)	14% (0-0.3mm)	14% (0-0.3mm)	10% (0-0.3mm)	7% (0-0.3mm)
	28.5% (0.3-1.2mm)	28.5% (0.3-1.2mm)	28.5% (0.3-1.2mm)	28.5% (0.3-1.2mm)	25% (0.3-1.2mm)	10% (0.3-1.2mm)
	57.5% (1.2-4.75mm)	57.5% (1.2-4.75mm)	57.5% (1.2-4.75mm)	57.5% (1.2-4.75mm)	65% (1.2-4.75mm)	10% (1.2-2.4mm)
	----	----	----	----	----	73% (2.4-4.75mm)
(MPa) 7days-20°C		128	84	70	90	76

(Planar Mixer)

(MIX-A1...10)

× × cm

(MIX-A6)

[ ] RPC

FRC

.( )

[ ] DSP

(Drum Mixer)

/ PCE

% / - /

( °C )

MPa MPa

°C

MPa

MIX-A6

W/(C+SF)


SP/(C+SF)

.(MIX-A6)

<b>Constituents</b> ( $kg/m^3$ )		<b>Properties</b>	
Portland Cement	<b>813</b>	7days-20°C	<b>128 MPa</b>
Fine Quartz Sand(0-0.3mm)	<b>183</b>	28days-20°C	<b>154 MPa</b>
Fine Quartz Sand (0.3-1.2mm)	<b>367</b>	7days-90°C	<b>169 MPa</b>
Fine Quartz Sand (1.2-4.75mm)	<b>734</b>		<b>0.3-0.4 %</b>
Silica Fume	<b>203</b>		<b>7.6 MPa</b>
Superplasticizer(PCE)	<b>15.2</b>	(28days-	<b>7.7 MPa</b>
Water	<b>175</b>		<b>5×10<sup>4</sup> MPa</b>
W/C	<b>0.215</b>	( $G_r$ )	<b>60 N/m</b>
W/(C+S.F)	<b>0.172</b>		<b>20-25 cm</b>
S.P/(C+S.F)	<b>1.5%</b>		<b>2500 kg/m<sup>3</sup></b>

cm

(mm)	(kgf)	
0.9	11.73	
0.75	11.40	
0.55	11.35	
0.40	13.00	
0.0	6.32	



mm / mm)

( / mm / mm /

( )

( ) / mm

Archive of SID

FRC

/ mm  
%

( × × cm)

[ ]

( × × cm)

/ mm

mm

mm

(

( × × cm)

( )

MIX-A6

(Pull-out)

SFRC-5

( )

( )

( )

%

( )


$(kg/m^3)$

:

	MIX-A6	SFRC-1	SFRC-2	SFRC-3	SFRC-4	SFRC-5
Portland Cement	813	796	791	787	782	777
Fine Quartz Sand(0-0.3mm)	183	180	179	178	176	175
Fine Quartz Sand (0.3-1.2mm)	367	359	357	355	353	351
Fine Quartz Sand (1.2-4.75mm)	734	719	715	710	706	702
Silica Fume	203	199	198	197	195	194
Superplasticizer (PCE)	15.2	14.9	15.8	16.7	17.6	18.5
Water	175	171	170	169	168	167
Steel Fiber(volume percent)	Without fiber	157(2%)	196(2.5%)	236(3%)	275(3.5%)	314(4%)
W/C	0.215	0.215	0.215	0.215	0.215	0.215
W/(C+S.F)	0.172	0.172	0.172	0.172	0.172	0.172
S.P/(C+S.F)	1.5%	1.5%	1.6%	1.7%	1.8%	1.9%

:

	MIX-A6	SFRC-1	SFRC-2	SFRC-3	SFRC-4	SFRC-5
$(MPa)$	151.3	176.2	175.9	179	180.7	193.6
$(N.m) \%$	686	8035.4	8144.6	8648.7	9442.9	10065.2



SFRC-5

:

( )

/


( )

SFRC-5 ( )

(MIX-A6)

:

	MIX-A6	SFRC-1	SFRC-2	SFRC-3	SFRC-4	SFRC-5
(Mpa)	77	17.7	17.9	19.4	19.2	23.3
(mm)	0.75	1.01	1.42	1.76	2.07	2.64
(N.m)	7.9	29.4	38.4	54.1	63.8	108.6
(N.m)	7.9	75.4	97.2	131.7	157.9	247.2



(MIX-A6)

SFRC-5

:

:

	MIX-A6	SFRC-1	SFRC-2	SFRC-3	SFRC-4	SFRC-5
(MPa)	7.7	18.9	20	20.4	20.7	23.2

( )

( )

MIX-A6

SFRC-5


( )

( )

°C

SFRC-5

	MIX-A6	SFRC-1	SFRC-2	SFRC-3	SFRC-4	SFRC-5
( $N.m$ )	0.3	16.1	30	39	39.2	47.5
( $G_f$ ) ( $N/m$ )	60	3220	6000	7800	7840	<b>9500</b>




(MIX-A6)

SFRC-5

:



Constituents ( $kg/m^3$ )		Properties	
Portland Cement	777	<i>SFRC-5</i>	
Fine Quartz Sand (0-0.3mm)	175	(MPa)	193.6
Fine Quartz Sand (0.3-1.2mm)	315	(N.m)%	10065
Fine Quartz Sand (1.2-4.75mm)	702	(MPa)	23.3
Silica Fume	194	(mm)	2.64
Superplasticizer(PCE)	18.5	(N.m)	108.6
Water	167	(N.m)	247.2
Steel Fiber(volume percent)	314(4%)	(N/m)(G <sub>r</sub> )	9500
W/C	0.215	(MPa)	23.2
W/(C+S.F)	0.172		
S.P/(C+S.F)	1.9%		



°C

MPa

MPa

mm

mm

mm

mm

MIX-A6

MIX-A6

)

% / (

% /

)

MPa

---

(

SFRC-5

(

SFRC-5

) / MPa

( )

(

) N/m

- 1 - Li, V.C. and Wang, S. (2003). "On high performance fiber reinforced cementitious composites." Japan concrete institute, Vol. JCI-C61, PP. 13-23.
- 2 - JCI-DFRCC Committee (2003). "DFRCC terminology and application concepts." J. of Adv. Conc. technology, Vol. 1, No. 3, PP. 335-340.
- 3 - Karihaloo, B.L., Benson, S.D.P. and Alaei, F.J. (2004). "CARDIFRC<sup>®</sup>-Properties and application to retrofitting." Proc., 5<sup>th</sup> Int. Conf. on Fracture Mechanics of Conc. & Conc. Struct., USA, 12-16 April.
- 4 - Alaei, F.J. and Karihaloo, B.L. (2003). "Fracture Model for Flexural Failure of Beams Retrofitted with CARDIFRC." ASCE, J. of Eng. Mechanics, Vol. 129, No. 9, PP. 1028-1038.
- 5 - Alaei, F.J. and Karihaloo, B.L. (2003). "Retrofitting of RC beams with CARDIFRC." ASCE, J. of Comp. for Construction, Vol. 7, No. 3, PP. 174-186.
- 6 - Fukuyama, H. and Suwada, H. (2003). "Experimental response of HPRCC dampers for structural control." J. of Adv. Conc. technology, Vol. 1, No. 3, PP. 317-326.
- 7 - Sadrekarimi, A. (2004). "Development of light weight reactive powder concrete." Japan concrete institute, J. of Adv. Conc. technology, Vol. 2, No. 3, PP. 409-417.
- 8 - Alaei, F. J. (2002). "Retrofitting of concrete structures using high performance fiber reinforced cementitious composites (HPRCC)." PhD thesis, Cardiff Univ., UK.
- 9 - ACI Committee 446.1R (2004). "Fracture Mechanics of Concrete: Concepts, Models and Determination of Material Properties." ACI manual of concrete practice.
- 10 - Cotterell, B. and Mai, Y. M (1996). "Fracture Mechanics of Cementitious Materials." Chapman & Hall, 1<sup>st</sup>. Ed.

- 1 - Fiber Reinforced Concrete (FRC)
- 2 - Matrix
- 3 - High Performance Fiber Reinforced Cementitious Composite (HPRCC)
- 4 - Strain Hardening
- 5 - Fracture Energy
- 6 - First Crack Strength
- 7 - Pseudo Strain Hardening
- 8 - Damping
- 9 - Reactive Powder Concrete (RPC)
- 10 - Densified System Containing Homogeneously Arranged Ultra Fine Particles (DSP or Densit)
- 11 - Notched Beam
- 12 - Bridging Action